Link Study: trn/WSKADT-Paris29.trn



SIGNAL™

Prop. model: FCC + RMD
Time: 50.00 % Loc.: 50.00 %
Margin: 0.00 dB
Climate: Continental Temperate
Atm. factor: none
K factors: 1.333, 0.500, 2.000

Reliability Analysis
Fade outage method: Vigants-Barnett
C param. for Vigants-Barnett:
average prop. conditions: C=1
ITU-R terrain type: Inland
ITU-R refract. grad.: 10.0 %
External interf.: -200.0 dBmW
Dispersive fade margin: 80.0 dB
Ant. spacing (diversity): 0.0 m
Rain outage method: Crane
Rain region: A

Transmitter Site: WSKADT
Name: Transmitter Site
Location:
N42°08'29.73" W77°04'39.11"
Site elevation: 512.0 m
Antenna height: 177.0 m
Pointing azimuth: 295.5 °
Transmitter power: 10.14 dBkW
Trans. line loss: 1.00 dB
Other losses: 0.00 dB
Antenna gain: 7.85 dBd
Antenna file:
Total ERP: 19.14 dBkW

Name: WSKADT ->Paris29
Frequency: 567.2500 MHz
Polarization: vertical
Length: 261.75 km
Number of obstacles: 9
Excess path loss: 167.68 dB
Atm. absorption loss: 0.00 dB
Path loss for stats: 303.56 dB
Flat fade margin: -99.90 dB
Total fade margin: -99.90 dB
Annual fade outage: 3942000.00 s
Annual rain outage: 0.00 s
Link availability: 50.0000 %

Receiver Site: Paris29
Name: Canadian DTV left center
Location:
N43°07'05.42" W79°59'27.19"
Site elevation: 212.9 m
Antenna height: 9.1 m
Pointing azimuth: 115.5 °
Trans. line loss: 0.00 dB
Other losses: 0.00 dB
Antenna gain: 6.00 dBd
Antenna file:
Received signal level: -276.27 dBkW

Notes

prepared by
Larry H. Will, P.E.
Glen Mills PA 19342

TERRAIN PROFILE

WSKA-DT to Paris ON

Figure 5C 295.4 degree radial