

ENGINEERING REPORT
Minor Change Application
Change in Site Location and Frequency

W269AQ – Chisholm, MN

File No. BLFT-19870318TG

July, 2003

COPYRIGHT 2003

TABLE OF CONTENTS

Discussion of Report

FM Booster/Fill-in Translator Requirements (none required)

Interference Requirements

- Exhibit 11.1 - Map of Transmitter Site
- Exhibit 11.2 - Vertical Plan of Antenna System and Support Tower
- Exhibit 11.3 - Tabulation of Operating Conditions
- Exhibit 11.4 - Proposed Contour Study
- Exhibit 11.5 - Map of Proposed Translator vs. Parent Station

Contour Overlap Requirements

- Exhibit 12.1 - Tabulation of Proposed Allocation
- Exhibit 12.2 - Contour Protections Toward Select Stations

TV Channel 6 Protection Requirements (none required)

Unattended Operation Requirements (See Discussion)

Multiple Translator Requirements (See Discussion)

RF Radiation Study Requirement (See Discussion)

(Exhibit numbering is in response to FCC Online Form 349, Section III-A)

Discussion

This firm has been retained to prepare the required engineering report in support of a Minor Change Application for FM translator W269AQ, Chisholm, MN, File No. BLFT-19870318TG. The facility serves as a translator for non-commercial FM station KBHW, International Falls, MN. KBHW operates on Channel 258C1, 99.5 MHz. The proposed translator will operate on Channel 267D with 27 watts at a max HAAT of 84 meters.

It has been determined the translator may be used in the area without interference to any existing FM broadcast station or translator. Allocation details are found in **Exhibit 12.1**. **Exhibit 11.5** of this report is a map showing the relationship of the primary station protected contour to the protected contour of the translator station. The translator site is outside the primary contour, and the 1 mV/m (60 dBu) contour of the translator extends beyond the primary station 1 mV/m contour.

The proposed translator is located within 320 kilometers of the border between the United States of America and Canada. This proposal meets the requirements of 47 C.F.R. §74.1235(d)(3).

The translator will employ a two bay circularly polarized antenna. The antenna will be mounted on a tower to be constructed. The FAA TOWAIR program has been consulted and FCC Antenna Structure Registration is not required. A 7.5 minute topographical map of the transmitter site has been included as **Exhibit 11.1**. Data concerning the site was supplied by the applicant and the site owner, and is believed correct.

The proposed facility meets the requirements of the Rules for operation without a licensed operator in attendance. The transmitter site may be reached promptly at all hours and in all seasons. The transmitter will be equipped with proper control and interface circuits which will place the translator in a non-radiating condition in the event the proper incoming signal is absent. The transmitter and controls will be placed in a locked area to prevent unauthorized tampering with the equipment. A person or persons will be assigned to observe the signals of the station each day, and to take corrective action if required. The equipment proposed for operation is listed in the type-approved list of the Commission.

Prompt suspension of the translator operation will be made, in the event of equipment failure that could cause operation outside the specifications of the Rules. The data contained in this report is responsive to the Rules of the Commission, and provides information for FCC Form 349.

Discussion (continued)

RADIATION PROTECTION: The FM broadcast facility proposed in this application is within the limits as set forth in the FCC Form 349 Worksheet #2 (RF Exposure Compliance), issued March, 2001. As this facility complies with Worksheet #2, no RF study need be supplied. The facility will remain properly marked with signs, and entry will continue to be restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed.

In the event work would be required in proximity to the antenna such that the person or persons working in the area would be potentially exposed to fields in excess of the guidelines set forth in OET Bulletin No. 65 (Edition 97-01), the transmitter power will be reduced or the station will cease operation during the critical period.

DISTANCES TO CONTOURS: The following tabulation of the distances to the proposed service contours results from calculations performed in accordance with §73.313(d) and §73.333 Figure 1.

Munn-Reese, Inc. - Coldwater, MI 49036						
N. Lat. = 47 28 57 W. Lng. = 92 53 56						
HAAT and Distance to Contour - FCC Method - 30 Arc Sec.						
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5
000	439.0	62.0	0.0270	-15.69	1.000	5.86
030	446.2	54.8	0.0270	-15.69	1.000	5.53
060	499.8	1.2	0.0270	-15.69	1.000	4.02
090	442.1	58.9	0.0270	-15.69	1.000	5.73
120	419.9	81.1	0.0270	-15.69	1.000	6.67
150	416.7	84.3	0.0270	-15.69	1.000	6.80
180	424.5	76.5	0.0270	-15.69	1.000	6.47
210	454.9	46.1	0.0270	-15.69	1.000	5.05
240	474.2	26.8	0.0270	-15.69	1.000	4.02
270	461.5	39.5	0.0270	-15.69	1.000	4.63
300	442.6	58.4	0.0270	-15.69	1.000	5.70
330	436.3	64.7	0.0270	-15.69	1.000	5.96
Ave El= 446.49 M HAAT= 54.51 M AMSL= 501 M						