

Exhibit 15-0-3

Tabulation of Distance to WMAL Daytime Allocation Contours

WMAL	630 kHz	Lic	DA2U	BL850515AC		20060522
DC	WASHINGTON			5.000 kW	4 Towers	15 Augmentations
N. Lat:	39 00 55	W. Lon:	77 08 30			12 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.
All distances are in kilometers (US metric curves)
All radiations are in mV/m at one kilometer

'M*' bearing is supplemented by measurements.
'+-' 10 deg. variance from measured bearing.

Bearing	Radiation	Distance to Contour
-----	-----	-----
0.0M*	564.0	30.49
5.0+	615.1	31.86
10.0-	649.7	33.42
15.0M*	661.1	33.66
20.0+	640.4	33.18
25.0+	592.5	31.92
30.0	536.6	26.15
35.0	487.2	24.91
40.0	442.4	23.73
45.0	402.2	22.59
45.4-	399.9	24.38
50.0-	389.2	24.03
55.0-	405.4	24.55
55.4M*	407.5	24.62
60.0+	438.6	25.60
65.0+	483.6	26.93
65.4+	487.5	27.04
70.0	533.0	26.57
75.0	581.8	29.86
80.0	627.6	32.57
85.0	670.4	34.85
90.0	716.3	36.96
94.0-	760.4	45.24
95.0-	771.9	45.59
100.0-	828.0	47.20
104.0M*	867.6	48.30
105.0+	876.5	48.55
110.0+	914.5	49.57
114.0+	940.0	50.23
115.0	946.2	45.01
120.0	978.3	45.92
125.0	1011.3	46.77
130.0	1034.9	47.32
130.5-	1036.5	52.66
135.0-	1044.3	52.85
140.0-	1035.9	52.64

WMAL	630 kHz	Lic	DA2U	BL850515AC		20060522
DC	WASHINGTON			5.000 kW	4 Towers	15 Augmentations
N. Lat:	39 00 55	W. Lon:	77 08 30			12 Measured Cond

140.5M*	1034.0	52.60
145.0+	1015.4	52.14
150.0+	988.3	51.46
150.5+	984.7	51.37
155.0	940.1	47.84
160.0	857.5	45.65
165.0	746.4	39.00
168.0-	673.8	39.66
170.0-	626.5	37.83
175.0-	533.1	33.11
178.0M*	510.4	32.24
180.0+	511.3	32.28
180.5+	513.6	32.37
185.0-	568.8	34.09
188.0-	632.8	35.40
190.0-	683.0	35.70
190.5M*	696.2	35.76
195.0+	819.6	38.09
200.0+	949.4	40.38
200.5+	960.9	40.57
205.0	1049.5	36.00
210.0	1119.4	37.09
215.0-	1158.6	36.19
220.0-	1169.4	36.35
225.0M*	1155.7	36.15
230.0+	1117.7	35.58
235.0+	1060.6	34.70
240.0	990.3	35.05
245.0	912.7	33.75
250.0	832.5	32.33
255.0	747.4	30.72
260.0	663.0	29.00
261.3-	644.2	34.49
265.0-	600.1	33.52
270.0-	556.6	32.51
271.3M*	546.8	32.28
275.0+	524.9	31.75
280.0+	511.4	31.42
281.3+	509.5	31.37
285.0	503.8	25.34
290.0-	495.6	25.13
295.0-	491.7	25.03
300.0M*	493.7	25.08

Exhibit 15-O-3 (cont.)
 Tabulation of Distance to WMAL Daytime Allocation Contours

WMAL	630 kHz	Lic	DA2U	BL850515AC	20060522
DC	WASHINGTON			5.000 kW 4 Towers	15 Augmentations
N. Lat:	39 00 55	W. Lon:	77 08 30		12 Measured Cond

Bearing	Radiation	Distance to Contour 5.000
-----	-----	-----
302.6+	489.7	24.98
305.0+	483.3	24.81
310.0-	465.5	23.10
312.6M*	456.9	22.88
315.0+	450.4	22.72
320.0+	425.5	22.07
322.6+	405.7	21.53
325.0-	385.2	26.42
330.0-	345.3	24.88
335.0M*	328.1	24.18
340.0+	340.0	24.66
345.0+	383.6	26.36
350.0-	445.2	26.98
355.0-	507.5	28.89