

EXHIBIT #16

R.F. EMISSION COMPLIANCE STATEMENT

K207DL
Channel 207 – 0.205 kW V
Twin Falls, Idaho

June 2003

The proposed Scala FMV vertically polarized antenna will be energized such that it produces 0.205 kW effective radiated power from a center of radiation of 33 meters above ground. Based on the formulas expressed in the OET Bulletin, No. 65, August 1997, "Evaluating Compliance with F.C.C. Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", published by the Federal Communication Commission's Office of Science and Engineering, the proposed facility is predicted to produce a worst-case maximum R.F. non-ionization radiation level at a position six feet above the tower base (head level - based on the C.O.R. of 33 meters above ground minus 2 meters) of 7.127 microwatts per square centimeter. This figure is without regard for the antenna's vertical elevation field value toward the nadir, which will cause a reduction in the predicted "worst case" calculations. 7.127 microwatts per square centimeter is 0.71 percent of the maximum standard value for the frequency in use for this controlled area. The tower is surrounded by an 8' tall chain link fence, which is locked at all times and posted with warnings and contact telephone number.

Since the predicted level of emissions is less than 1% of maximum, no further calculations were deemed necessary.

The applicant will protect workers on the tower by either reducing ERP or terminating transmission.

Consequently, it appears that the proposed FM station will be in full compliance with the Commission's human exposure to radiofrequency electromagnetic field rules and regulations.