



Low Power FM (LPFM) Channel Finder Results

More search options at [LPFM Channel Finder Search](#)

[AM QUERY](#)[FM QUERY](#)[TV QUERY](#)[TV STATION PROFILES & PUBLIC INSPECTION FILES](#)[CDBS SEARCH](#)[MEDIA BUREAU](#)

Sun Aug 25 17:11:13 2013

EXCLUDES intermediate frequency (I.F.) spacings
INCLUDES second-adjacent channel spacings

Input options:

Latitude, Longitude: 34° 34' 7", 118 44' 26"

Google Map: [5.6 km radius \(approximate 60 dBu service contour coverage\)](#)



CONDITIONAL. The requested latitude and longitude meet the PROPOSED LPFM spacing requirements for one or more intermediate frequency (I.F.) channels.

These proposed spacing rules are not yet in effect.

Channels Available for LPFM LP100 Stations [Channels 201 to 300, [corresponding to 88.1 to 107.9 MHz](#)]

Channel 248 ---- 97.5 MHz
Channel 272 ---- 102.3 MHz

This analysis does not determine whether an LPFM station at this location and channel might receive interference within its 60 dBu LPFM service contour from FM broadcast stations already operating or authorized in the band from fully spaced locations. LPFM stations must accept all such interference.

Because the FM database constantly changes, there is no guarantee that channels represented as "available" will be technically acceptable at the time of application filing.

Available Channels Interference Analysis

This section considers the acceptable LPFM-use channels listed above, and determines which of these channels will be less likely to suffer interference from existing or authorized stations. This analysis only considers spacing, and assumes that the interfering stations are operating with the [reference facilities for the FM station's class](#). While helpful, the results shown below should not take the place of a thorough analysis of all options by a broadcast consulting engineer.

If interference is possible, the following table will contain:

- Call Sign of the interfering station
- Channel of that station
- Channel relationships: Same channel OR First-adjacent channel OR Second-adjacent channel
- Actual separation (in km)
- Minimum Separation for no interference within the 60 dBu contour

(based on reference facilities and flat terrain)

Channel 248				
KYGA	248	Same channel (cochannel)	111.8 km actual	143.0 km for no interference
Channel 272				
K272DI	272	Same channel (cochannel)	38.4 km actual	67.0 km for no interference
KJLH	272	Same channel (cochannel)	72.4 km actual	92.0 km for no interference

A simple test for potential interference is to tune a radio to the channel or frequency under consideration, while at the proposed transmitter site. If a station can be heard, you should expect that coverage from an LPFM station may be diminished. Interference to the LPFM station could occur at some future date should the listed FM station increase its facilities to the maximums permitted for the station's class.

AM Stations Within 3.2 km

Use this button to check for AM stations within 3.2 km [2 miles] of the coordinates specified above. If a *nondirectional* AM station appears within **0.8** km of these coordinates, or a *directional* AM station appears within **3.2** km, the LPFM applicant is responsible for measures to protect the AM station from changes in its operation caused by the LPFM antenna-supporting tower structure. See [47 CFR 73.1692](#). LPFM applicants should be aware that remediation may be costly if it becomes necessary to mitigate the impact on the AM station.

AM Stations within 3.2 km

'No records found' indicates that the coordinates are not within 3.2 km of an AM station.

Airports Within 8 km (5 Miles)

The tool below allows you to check for airports within 8 km of the proposed station's coordinates. If you get a FAIL message, or if your proposed tower or supporting structure will be greater than 200 feet (61 meters) at ANY location, then you MUST obtain clearance from the FAA using [FAA Form 7460-1](#), and the FAA-approved structure must be registered with the FCC via the [Antenna Structure Registration \(ASR\)](#) system.

The [FAA's Form 7460-1](#) and FCC antenna structure registration both require coordinates in the NAD83 coordinate system. To convert from NAD27 coordinates (used for broadcast station analyses) to NAD83 coordinates, you may use the [National Geodetic Survey's](#) conversion program at: <http://www.ngs.noaa.gov/cgi-bin/nadcon.prl>.

Convert 34° 34' 7", 118° 44' 26" to NAD83

Once you have obtained the converted coordinates, copy them down and enter them into the FCC's Wireless Telecommunications Bureau's

[TOWAIR Query](#)

If the proposed structure does not pass the TOWAIR test, you will need to request FAA clearance and register the antenna structure with the FCC once clearance is obtained from the FAA.

New LPFM Channel Finder Analysis?

NAD 27 Coordinates (degrees, minutes, seconds latitude and longitude)

FM Station Latitude

FM Station Longitude

34 34 7 118 44 26

- ☒ Results only
☐ Show List of Stations Considered

Special search options:

Second adjacent channels: An LPFM application must satisfy minimum distance separation requirements to stations operating on and applications proposing operations on second-adjacent channels. The *Local Community Radio Act* authorizes the Commission to waive the second-adjacent channel protection requirement and the Commission has under consideration proposed waiver standards.

☒ Include (more restrictive) ☐ Exclude

Second-adjacent channel distance separation requirements to authorized stations and pending applications

Intermediate Frequency (I.F.) channels: An LPFM application must satisfy minimum distance separation requirements to stations operating on and applications proposing operations on intermediate frequency (IF) channels. The Commission has under consideration a proposal to eliminate this requirement for LPFM applications proposing operations at less than 100 watts effective radiated power.

☒ Include (more restrictive) ☐ Exclude

I.F. channel distance separation requirements to authorized stations and pending applications

Submit the Data

Clear the Form



- Federal Communications Commission
- 445 12th Street SW, Washington, DC 20554
- Phone: 1-888-225-5322
- TTY: 1-888-835-5322
- Fax: 1-866-418-0232
- E-mail: fccinfo@fcc.gov

Get Email Updates

Email: *

Zip Code: *

Sign Up

- [Privacy Policy](#)
- [Moderation Policy](#)

[Join the Discussion](#)

- [Website Policies & Notices](#)
 - [Required Browser & Plug-ins](#)
 - [FOIA](#)
 - [No Fear Act Data](#)
- [FCC Digital Strategy](#)
 - [Open Government Directive](#)
 - [Plain Writing Act](#)
 - [2009 Recovery and Reinvestment Act](#)
 - [RSS](#)
- [File a Public Comment](#)
 - [Report a Consumer Complaint](#)
 - [Contact the FCC](#)

The FCC	Our Work	Tools & Data	Business & Licensing	Bureaus & Offices
<ul style="list-style-type: none">• What We Do• Blog• Events• FCC Encyclopedia• Guides• Leadership• Advisory Committees• Jobs & Internships• Contact Us• Help • MyFCC	<ul style="list-style-type: none">• Consumers• Public Safety• Broadband• Spectrum• Connecting America• Media & Marketplace• International• Enforcement	<ul style="list-style-type: none">• Tools• Developers• Maps• Data• Reports• Working Papers	<ul style="list-style-type: none">• Rulemaking• Online Filing• Fees• Forms• Commission Documents• FOIA• Ex Parte• Mergers• Small Business• Contracting with the FCC	<ul style="list-style-type: none">• Consumer & Governmental Affairs• Enforcement• International• Media• Public Safety & Homeland Security• Wireless Telecommunications• Wireline Competition• Administrative Law Judges• Communications Business Opportunities• Engineering Technology• General Counsel• Inspector General• Legislative Affairs• Managing Director• Media Relations• Secretary• Strategic Planning & Policy Analysis• Workplace Diversity