



**ERI**® **ELECTRONICS RESEARCH, INC.**

7777 Gardner Road • Chandler, Indiana 47610 • (812) 925-6000 • Fax: (812) 925-4030 • Home Page: www.ERInc.com

## Report of Inter-Modulation Product Measurements

For

**Two Station Pass Band Star Combiner**  
WXRK 92.3 MHZ / WCBS 101.1 MHZ

**Combined Broadcast Facility**  
New York, New York

**JOB # 03922**

November 20, 2001

**Received**

JAN 22 2002

CBS Communication Services

5  
7  
1943

## Contents

- Report of Findings for Inter-Modulation Product Measurements
- Exhibit A – Schematic Drawings and Specifications for Filter/Combiner/Antenna System
  - A-1 Schematic of Pass Band Star Combiner
  - A-2 Combiner System Specification Sheet
  - A-3 ERI LPX-4AC-SP Installation Drawing
  - A-4 Antenna Vertical Plane Relative Field Plots
- Exhibit B – Inter-Modulation Product Measurement Equipment Layout

## Introduction

This report of findings provides evidence to show that the two-station combined facility for the operation of WXRK and WCBS is in compliance with the FCC Rules and Regulations as required by the Code of Federal Regulations (CFR) Title 47 Section 73.317 paragraph (b), (c), and (d). In brief, the collection of measurements presented in this report shows that all possible second order inter-modulation (IM) products generated by this combined system are less than the maximum allowable level as required by section 73.317(d). Thomas B. Silliman of Electronics Research, Inc. performed the measurements summarized herein on October 13, 2001.

IM products can potentially violate section 73.317 paragraph (d) requirements and are commonly generated from radio stations operating into multiplexed facilities and at congested antenna broadcast sites when inadequate transmitter to transmitter isolation is provided. The ERI installed filter/combiner system is designed to provide adequate isolation to ensure that interfering signals and any resulting intermodulation products are sufficiently attenuated to satisfy the section 73.317 paragraph (d) requirement. A Potomac Instruments FIM-71 with a bandpass filter is used to verify compliance with paragraph (d).

Measurements to verify compliance with section 73.317 (d) were made on the Pass Band Star combiner system installed by ERI at the WXRK/WCBS auxiliary transmission site. Schematic diagrams and specification sheets for the combiner system are included in Exhibit A of this report.

The combined system serves as the auxiliary transmitter site for both WXRK and WCBS.

## Pass Band Star Combiner System

Stations WXRK and WCBS were operating at licensed power for the duration of compliance measurements. Measurements were made to determine the level of second order IM products (of the type  $2F_1 - F_2$ ) for the two-station Pass Band Star combiner system combining WXRK (92.3 MHz) and WCBS (101.1 MHz). The combiner system is illustrated in the attached Exhibit A on page A-1.

The inter-modulation products were measured with both system transmitters operating at licensed TPO on the filter/combiner system. Directional couplers were placed at key locations throughout the combiner system to monitor and maintain the combiner performance. All couplers furnished with the system are factory calibrated and capable of delivering accurate and repeatable RF measurements. For the purposes of the measurements for these findings, the coupler located at the system output to the antenna was used. The RF directional coupler installed in the 3-1/8" line section to the antenna output allows forward and reflected readings of the antenna output signal levels. This type of directional coupler used for measurements is factory calibrated with a typical directivity of about 35 dB and a forward signal sample typically attenuated by around 55 dB.

The forward port of the output directional coupler was used for sampling all outgoing carrier levels and IM products. The sampled signal was fed by shielded cable through a band pass filter into a Potomac Instruments FIM-71 field strength meter. Various attenuation pads were used at connection locations to the band pass filter and/or the FIM-71 to ensure adequate signal levels for measurement without overloading the measurement equipment. The selective tuning of the FIM-71 and of the band pass filter was accomplished using a Wavetek Model 3000 signal generator. The measurement setup is illustrated in the attached Exhibit B.

The relative output signal levels for the system carriers are measured first to establish reference levels for other measurements. These levels will be used as a basis for comparing the IM product levels. The resulting signal levels for these measurements are listed in Table 1. The Adjusted Level shown in the last column of the table will be used as the reference level for possible IM products of each carrier.

**Table 1. Carrier Reference Levels – Pass Band Star Combiner System**

Carrier Frequency (MHz)	Pad One (dB)	Bandpass Filter Loss (dB)	Pad Two (dB)	Full Scale Range (dB $\mu$ )	Scale Reading (dB)	Adjusted Level (dB $\mu$ )
101.1	---	—	—	120	-1.51	118.49
92.3	---	—	—	140	-18.42	121.58

Second-order products due to mixing of system second harmonics with system fundamentals are calculated and listed in Table 2.

**Table 2. Second Order Products for New York, New York  
WXRK/WCBS Pass Band Star Combiner System**

Carrier Frequency (MHz)	Interfering Frequency (MHz)	
	92.3	101.1
92.3	–	83.5
101.1	109.9	–

The IM product measurements using the measurement scheme as previously described were recorded and are listed in Table 3 with the signal level referenced to carrier calculated in the last column. Refer to the figure in Exhibit B for a layout of the measurement equipment. All product levels met requirements.

Additionally, I observed using the forward sample port on the filter system output directional coupler that both WXRK and WCBS met the requirements for section 73.317 paragraph (b) and (c) of the FCC Rules.

Table IM Measurements for Pass Band Star Combiner System

Product Frequency (MHz)	Carrier Frequency (MHz)	Interfering Frequency (MHz)	Pad One (dB)	Filter Loss (dB)	Pad Two (dB)	Full Scale Range (dB $\mu$ )	Scale Reading (dB)	Adjusted Level (dB $\mu$ )	Level Referenced to Carrier (dB)
83.5	92.3	101.1	---	9.5	---	20	$\pm 0$	29.5	89
109.9	101.1	92.3	---	8.0	---	20	<-20	<8	<110
184.6	92.3	---	---	0.6	---	20	<-20	<6	<121
202.2	101.1	---	---	0.6	---	20	<-20	<6	<118

## Conclusions

Based upon the observations and measurements recorded in this document, I, Thomas B. Silliman, find the Pass Band Star Combiner system for the operation of the WXRK auxiliary transmitter and the WCBS auxiliary transmitter to be in proper working order. Furthermore, based on the measured data, it is my opinion there are no inter-modulation products being generated in excess of 80 dB below station carrier levels by the stations operating on the installed system. Based on this recorded data and my observations, I conclude that WXRK and WCBS are in compliance with the requirements of Sections 73.317 paragraph (b), (c), and (d) of the FCC Rules and Regulations.

Respectfully submitted by Electronics Research, Inc.

AFFIDAVIT

WARRICK COUNTY        )  
                                  ) SS:  
STATE OF INDIANA     )

THOMAS B. SILLIMAN, being duly sworn upon his oath deposes and says:

That his qualifications are a matter of record with the Federal Communications Commission;

That he is a registered professional engineer in Indiana, Maryland and Minnesota and is the President of Electronics Research, Inc.;

That this corporation has been retained by Radio Station WXRK, to prepare this engineering statement; and

That he has either prepared or directly observed the preparation of all technical information contained in this engineering statement and that the facts stated in this engineering statement are true of his knowledge except as such statements as are herein stated to be on information and belief and as to such statements he believes them to be true.

Thomas B. Silliman  
Thomas B. Silliman


Subscribed and sworn to before me this 29th day of August, 2001

Cindy D. Tomes  
Notary Public

My Commission Expires: 11-06-04  
I Reside in WARRICK County.

Cindy D. Tomes  
Printed Name

(Seal)




ASSEMBLY SYSTEM BY MATING CORRESPONDING NUMBERS AND LETTERS.

OUTPUT TO ANTENNA

2) CONNECTIONS ARE DESIGNATED BY BANK LOCATION AND CONNECTION NUMBER. EX. A.1 IS BANK "A", CONNECTION NO. 1.

BANKS ARE COLOR-CODED FOR EASE OF INSTALLATION.



**ELECTRONICS RESEARCH, INC.**

Established 1943

7777 GARDNER RD.  
 CHANDLER, IN. 47610-9637  
 PHONE: (812) 925-8000  
 FAX: (812) 925-4026

This document/drawing contains information considered confidential by Electronics Research, Inc. (ERI). This information is disclosed on a confidential basis and only authorized for use in the installation, operation, and maintenance of ERI tower and antenna equipment, as appropriate. Reproduction, transmission or disclosure to others, or unauthorized use, without the express written consent of ERI, is strictly prohibited. UNAUTHORIZED DUPLICATION, REPRODUCTION, OR DISCLOSURE OF THIS INFORMATION IS A VIOLATION OF FEDERAL LAW.

NO	REVISION	APP'D	DATE
1	REVISED PER ROOM DIMENSIONS		9/2/01 SMI
2			
3			
4			
5			
6			

NAME TUNING DETAIL	
STATION: WLTV - NEW YORK, N.Y.	
FREQUENCY: 92.3/101.1 MHz. PROJECT NO: 03922/2	
PATH G:\DRAFTING\ALL PROJECT\03922	
FILE: I\1 - 2 DRAWN R.A.H. FACTOR NIS	
DATE: 9/14/01	APP'D: [Signature]
MODEL: 960F06-000-T13	DWG. NO. IM-2

• COPYRIGHT 2001 ERI, ELECTRONICS RESEARCH INC.

**Pass Band Star Combiner System Specification Sheet**  
**WXRK/WCBS**  
**NEW YORK, NEW YORK**

*General Specifications*



Multiplexer Type .....Pass Band Star Combiner  
 Number Of Combining Modules Used ..... One, Type 960 Star  
 Injected Port to Injected Port Isolation (typical)..... 55 dB  
 Output Connector..... 3-1/8" 50Ω EIA (Flanged)  
 Output Power .....20 kW

Heat Removal (All Multiplexer Components) ..... Natural Convection  
 Physical Arrangement..... All Components Floor Standing

*Injected Port Specifications*

Frequency Assignments ..... 101.1 and 92.3 MHz  
 Power Rating, Each Injected Port (Maximum)..... 10 kW  
 Connector ..... 3-1/8" 50 Ohm EIA (Flanged)  
 VSWR.....Less than 1.06:1 @ +/-150 kHz<sup>(1)</sup>  
 Group Delay (typical) ..... Less than 50 nsec Overall Variation, Carrier @ +/-150 kHz  
 Insertion Loss (Measured):  
     101.1 MHz      -0.236 dB @ +/- 100 kHz  
     92.3 MHz      -0.210 dB @ +/- 100 kHz

(1) When Terminated in 50 Ohm Resistive Load.



Center 101.100 MHz		Span 1.000 MHz	
1:MKr (MHz)	dB	2:MKr (MHz)	dB
1: 100.9000	-30.993	1: 100.9000	-0.270
2> 101.1000	-39.297	2> 101.1000	-0.236
3: 101.3000	-30.828	3: 101.3000	-0.282

- Match
- Insertion Loss
- Group Delay
- BROAD Port Match
- Isolation +/- 800 KHz
- Port to Port Isolation
- To Injected MHz
- To Broad
- To Dump
- TERMINATION
- Load
- Cable
- Antennas
- Other

Match

Insertion Loss

Group Delay

BROAD Port Match

Isolation +/- 800 KHz

*Port to Port Isolation*

To Injected MHz

To Broad

To Dump

TERMINATION

Load


Cable

Antenna

Other

2: Transmission Log Mag 10.0 dB/ Ref 0.00 dB


09-20-2001 08:27:55



10 MHz

1: Mkr (MHz)	dB	2: Mkr (MHz)	dB
1:	100.3000	-14.314	
2:	101.1000	-0.240	
3:	101.9000	-14.244	

09-20-2001 08:26:59 Delay



1: Mkr (MHz)	dB	2: Mkr (MHz)	s
1:		100.9000	771n
2:		101.1000	683n
3:		101.3000	761n

Match

Insertion Loss

Group Delay

BROAD Port Match

Isolation +/- 800 KHz.

Port to Port Isolation

T Injected MHz

To Broad

To Dump



TERMINATION

Load

Cable

Antenna

Other




Center 92.300 MHz Span 1.000 MHz

1: Mkr (MHz)		dB	2: Mkr (MHz)		dB
1:	92.1000	-32.126	1:	92.1000	-0.255
2>	92.3000	-38.326	2>	92.3000	-0.210
3:	92.5000	-31.919	3:	92.5000	-0.273

- Match
- Insertion Loss
- Group Delay
- BROAD Port Match
- Isolation +/- 800 KHz
- Port to Port Isolation
- To Injected \_\_\_\_\_ MHz
- To Broad
- To Dump
- TERMINATION
- Load
- Cable
- Antennas
- Other

▷1

▷2: Transmission Log Mag 10.0 dB/ Ref 0.00 dB C



1: Mkr (MHz)	dB	2: Mkr (MHz)	dB
		1: 91.5000	-14.692
		2: 92.3000	-0.209
		3: 93.1000	-15.367

Match

Insertion Loss

Group Delay

BROAD Port Match

Isolation +/- 800 KHz

*Port to Port Isolation*

To Injected \_\_\_ MHz

To Broad

To Dump

TERMINATION

Load

Cable

Antenna

Other



# Inter-Modulation Product Measurement Equipment Layout

## Exhibit B

