

RF CERTIFICATION AND STATEMENT

The proposed antenna system will be energized such that it produces 0.250 KW ERP, from the center of radiation of 87 meters above ground. The applicant will employ a four (4) bay ERI FM-10A-4-HW $\frac{1}{2} \lambda$ antenna system based on the formulas expressed in OET bulletin No. 65, August 1997, "Evaluating Compliance with F.C.C. Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields" published by the Federal Communications Commission's Office of Engineering and applying a combination of the element and array pattern as defined in E.P.A. study PB85-245868 ("**Engineering Assessment of the Potential Impact of the Federal Radiation Protection Guidance on the AM, FM and TV Broadcast Services**"). The highest calculated power density can be found at a distance of 81.19 meters from the tower. At this location the value is 0.0362 Microwatts per square centimeter. Since the tower site is fenced with a locked gate, (inaccessible to the public) this value amounts to 0.0036 percent of the maximum for a "controlled" environment. In an uncontrolled environment, this amounts to 0.0181 percent of maximum. This proposal is in full compliance with all applicable FCC rules. These calculations were performed using the V-Soft Communications RFHaz3 program.

The proposed antenna system will be co-located on the same supporting structure as AM station WKAV. The Station operates with 1.0 Kw non-directional fulltime. Also co-located on the structure are stations W231AD and WXTJ-LP CP.

Pursuant to section 1.1307 (b) of the Commission's rules, the power density contribution of a co-located or nearby broadcast facility are not required to be calculated as the proposed translators density is less than five (5) percent.

Should work be required on the supporting structure where exposure would be greater than the maximum allowed, the applicant would lower power or cease operation until the work is completed.

Regarding compliance with the nationwide programmatic agreement and NHPA Section 106 for tower co-location, the applicant has been informed by the FCC staff that compliance with the agreement is not required when: 1) the supporting structure was constructed prior to March 16, 2001; and 2) no new tower construction is proposed; and 3) the tower is not being substantially altered. Specifically, compliance is NOT necessary where an antenna and feed line are being attached to an existing structure. ***The proposed will NOT modify or change the existing structure.***

Clyde Scott
EME Communications.