



Exhibit #29

Environmental Impact Statement
Height Increase
Champlin Broadcasting, Inc.
KQBL (FM) Channel #245C
Enid, OK

This proposed modification application does not involve any of the environmental probations listed in Section 1.1311 of the Commission's Rules. Construction will not be a major environmental action.

The proposed KQBL (FM) antenna will be energized such that it produces 100 kW ERP circularly polarized from a center of radiation 426 meters above ground. KQBL (FM) will utilize an ERI model SHPX-6AC6 6 bay antenna.

By using the formulas expressed in OST Bulletin, No.65, October 1985, "Evaluating Compliance with F.C.C. Specified Guidelines for Human Exposure to Radio Frequency Radiation", published by the Federal Communications Commission's Office of Science and Technology, and then by applying a combination of the element and array pattern as identified in E.P.A. study PB85-245868 ("Engineering Assessment of the Potential Impact of the Federal Radiation Protection Guidance on the AM, FM and TV Broadcast Services") using an ERI circularly polarized antenna, it can be shown that the proposed antenna generates a maximum of 1.103 microwatts per square centimeter at a distance of 15 meters from the tower base, and 6 feet above the ground. This value amounts to .5516 percent of the maximum.

Access to the tower will be restricted with a fence and a locked gate. Signs will be posted warning of the radiation hazard. Company procedures have already been established to protect workers who must climb the tower. The transmitting power of the station will be reduced, or completely turned off to insure that these workers will not be exposed to excessive radiation levels.



Respectfully Submitted,

William H. Nolan

William H. Nolan
Managing Member
Broadcast Technical Associates, LLC