

EXHIBIT A


ENGINEERING STATEMENT

The engineering data contained herein have been prepared on behalf of TRINITY BROADCASTING NETWORK, licensee of television translator K51IO, Channel 51 in Bullhead City, Arizona, in support of this amendment to its pending digital flashcut application for Construction Permit (BDFCDTT-20070709ADE) to now specify a reduction in effective radiated power and a directional antenna.

It is proposed to utilize the licensed MCI directional antenna at the authorized height on the side of the existing 18-meter communications tower. Exhibit B is a map upon which the revised service contours are plotted. It is important to note that the newly proposed 51 dBu contour encompasses a significant portion of the Grade A contour that obtains from the licensed analog K51IO facility. Operating parameters for the proposed facility are tabulated in Exhibit C. An interference study is provided in Exhibit D, and a power density calculation follows as Exhibit E.

Because no change in the overall height or location of the existing tower is proposed, the FAA has not been notified of this application. Due to the diminutive height of the tower and its proximity to the nearest airport runway, FCC antenna structure registration is not required. This conclusion is supported by the Commission's TOWAIR Program.

I declare under penalty of perjury that the foregoing statements and the attached exhibits, which were prepared by me or under my immediate supervision, are true and correct to the best of my knowledge and belief.


KEVIN T. FISHER

November 5, 2007

CONTOUR POPULATION

51 DBU : 56,442

41 DBU : 65,287

SMITH and FISHER




EXHIBIT C

PROPOSED OPERATING PARAMETERS

PROPOSED K51IO-D
CHANNEL 51 – BULLHEAD CITY, ARIZONA
[AMENDMENT TO BDFCDTT-20070709ADE]

Transmitter Power Output:	9 watts
Transmission Line Efficiency:	91.3%
Antenna Power Gain – Toward Horizon:	59.5
Antenna Power Gain – Main Lobe:	59.5
Effective Radiated Power – Toward Horizon:	0.5 kw
Effective Radiated Power – Main Lobe:	0.5 kw
Transmitter Make and Model:	Type-accepted
Rated Output	10 watts
Transmission Line Make and Model:	Andrew LDF7-50A
Size and Type:	1-5/8" foam heliax
Length:	60 feet
Antenna Make and Model:	MCI 955514
Orientation	160 ° T
Beam Tilt	none
Radiation Center Above Ground:	12.2 meters
Radiation Center Above Mean Sea Level:	1,455 meters

EXHIBIT D-1

LONGLEY-RICE INTERFERENCE STUDIES
PROPOSED K51IO-D
CHANNEL 51 – BULLHEAD CITY, ARIZONA
[AMENDMENT TO BDFCDTT-20070709ADE]

We conducted detailed interference studies using the Longley-Rice methodology contained in the Commission's *OET Bulletin No. 69*, with respect to all facilities of concern. The software utilizes a 1-square kilometer cell size, calculates signal strength at 0.1 kilometer increments along each radial studied, and employs the 1990 U.S. Census to count population within cells. In addition, the program does not attribute interference to the proposed facility in cells within the protected contour of the station under study where interference from another source (other than proposed K51IO-D) already is predicted to exist (also known as "masking"). The results of these studies are provided in Exhibit D-2. They conclude that the facility proposed herein causes no significant new interference to any of the potentially affected stations.

As a result, it is believed that the proposed K51IO-D facility complies with the requirements of Sections 74.709, 74.793(e), 74.793(f), 74.793(g), 74.793(h), 74.794(b) and 73.1030 of the Commission's Rules.

INTERFERENCE SUMMARY

PROPOSED K51IO-D
CHANNEL 51 – BULLHEAD CITY, ARIZONA
[AMENDMENT TO BDFCDTT-20070709ADE]

<u>Call Sign</u>	<u>Status</u>	<u>City, State</u>	<u>Ch.</u>	<u>Longley-Rice Service Population</u>	<u>Unmasked Interference From Proposed Facility</u>	<u>%</u>
------------------	---------------	--------------------	------------	--	---	----------

[NO STATIONS AFFECTED]

EXHIBIT E

POWER DENSITY CALCULATION

PROPOSED K51IO-D
CHANNEL 51 – BULLHEAD CITY, ARIZONA
[AMENDMENT TO BDFCDTT-20070709ADE]

Since the FCC considers the possible biological effects of RF transmissions in its environmental determinations, we have studied the matter with respect to this Bullhead City facility. Employing the methods set forth in *OET Bulletin No. 65* and considering a main-lobe effective radiated power of 0.5 kw, an antenna radiation center 12 meters above ground, and the vertical pattern of the MCI antenna, maximum power density two meters above ground of 0.00015 mw/cm^2 is calculated to occur 27 meters south-southeast from the base of the tower. Since this is less than 0.1 percent of the 0.46 mw/cm^2 reference for uncontrolled environments (areas without public access) surrounding a facility operating on Channel 51 (692-698 MHz), this proposal may be considered a minor environmental action with respect to public exposure to nonionizing electromagnetic radiation.

Further, the station owner will take whatever precautionary steps are necessary, such as reducing power or leaving the air temporarily, to ensure that workers operating in the vicinity of the antenna are not exposed to excessive nonionizing radiation.