

**DELAWDER COMMUNICATIONS, INC.**

P.O. Box 1095  
Ashburn, Virginia 20146-1095  
(703) 299-9222

**ENGINEERING REPORT**

---

**WZFL(FM), Islamorada, FL, Channel 228C2 FM Application**

**EXHIBIT 35 - ENVIRONMENTAL STATEMENT**

The proposed antenna is being side-mounted at an existing communications tower. Therefore, pursuant to 47 CFR Section 1.1306, Note 1, this proposal is categorically excluded from the provisions of 47 CFR Section 1.1307(a). (47 CFR Section 1.1307(a)(4) is not applicable to this proposal.)

A Systems With Reliability, LP ("SWR") FMEH Plus 5 bay (horizontally polarized only, 0.9 wavelength spacing) antenna is proposed. This FM station proposal specifies an ERP that is less than or equal to 26 kilowatts (peak). Assuming: (a) a maximum ERP of 26 kilowatts; (b) a relative field of less than 0.18 in the critical downward angles; and (c) a distance of at least 100 meters from the lowest antenna element to 2 meters above ground level, the maximum power density is calculated as follows:

$$S = 33.4 (F)(F)(ERP) / [(R)(R)]$$

Where, S equals power density in uW/cm<sup>2</sup>  
F equals the relative field factor  
ERP equals the effective radiate power in watts  
R equals the distance in meters

$$= 33.4 (0.18)(0.18)(26,000) / [(100)(100)]$$

$$= 2.8 \text{ uW/cm}^2$$

2.8 uW/cm<sup>2</sup> represents less than 5% of the uncontrolled power density limit (200 uW/cm<sup>2</sup> for FM) and this facility is categorically excluded from RFR determination.

The electromagnetic radiation from this proposed operation will not produce a value in excess of the radiation standard. The electromagnetic radiation from the proposed operation will not combine with other facilities on or near the structure to produce a significant change in value. If this is a structure that may support various other operations, the applicant will cooperate with the other operators in establishing a plan for work done on the structure in close proximity to the existing antenna.