

Calvary Chapel of Twin Falls, Inc.

Paso Robles, CA K287BU Channel Change
 Calvary Chapel Of Twin Falls, Inc.
 CH# 255D - 98.9 MHz, Pwr= 0.01 kW DA, HAAT= 0.0 M, COR= 440 M
 Average Protected F(50-50)= 3.15 km
 Standard Directional

DISPLAY DATES
 DATA 12-13-16
 SEARCH 12-13-16

REFERENCE
 35 37 35.0 N.
 120 42 43.0 W.

CH CITY	CALL	TYPE STATE	ANT	AZI <--	DIST FILE #	LAT LNG	PWR(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
253D San Luis Obispo	K253BR	LIC DC_ CA		170.2 350.2	30.02 BLFT20151119AAR	35 21 37.0 120 39 20.0	0.250 758	1.1 758	24.6 Dimes Media Corporation	26.9	5.3
255B Dinuba	KSOF	LIC _CX CA		54.2 235.3	194.56 BLH20140630AED	36 38 11.8 118 56 33.6	19.000 250	173.9 1591	96.8 Capstar Tx, LIc	12.7	59.8
256B Santa Maria	KXFM	LIC _CN CA		148.9 329.2	92.85 BLH19910429KE	34 54 37.0 120 11 08.0	2.300 581	74.2 1016	63.0 Point Ten LIc	15.2	27.7
258B Greenfield	KL0K-FM	LIC _CN CA		330.7 150.3	107.00 BLH19920723KB	36 27 51.0 121 17 52.0	30.000 195	7.8 527	80.9 Entravision Holdings, LIc	93.7	24.9
254A Greenfield	KSGZ	CP NCX CA		330.5 150.2	106.58 BPH20161012AAM	36 27 34.2 121 17 54.8	2.500 89	56.3 418	38.3 Lazer Licenses, LIc	45.1	66.0

Terrain database is NGDC 30 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
 In & Out distances between contours are shown at closest points. Reference zone= East Zone 2A, Co to 3rd adjacent.
 All separation margins (if shown) include rounding.
 Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)