

Calvary Chapel of Twin Falls, Inc.

Argenta, NV K203DP Minor Change  
Calvary Chapel Of Twin Falls, Inc.  
Average Protected F(50-50)= 10.11 km  
Omni-directional

REFERENCE  
40 33 31.0 N.  
116 41 49.0 W.

CH# 203D - 88.5 MHz, Pwr= 0.013 kW, HAAT= 261.8 M, COR= 1903 M

DISPLAY DATES  
DATA 07-22-15  
SEARCH 07-28-15

CH CITY	CALL	TYPE STATE	ANT STATE	AZI <--	DIST FILE #	LAT LNG	PWR(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
203D Argenta	K203DP	LI	D_V_	327.4 147.3	20.43 BLFT20061101ACR	40 42 48.0 116 49 40.0	0.010 591	51.1 2153	13.9 Calvary Chapel Of Twin Fal	-41.9*	-31.3*
06 D Elko	K06MK-D	LI	D_N	70.5 251.2	89.08 BLDTV20111123AAA	40 49 16.0 115 42 04.0	0.100 428	13.2 2001	18.5	31.7R	57.4M
06 D Elko	K06MK-D	LI	D_N	70.5 251.2	89.08 BLDTV20111123AAA	40 49 16.0 115 42 04.0	0.100 428	13.2 2001	18.5	31.7R	57.4M
06 D Elko	K06HT-D	LI	D_N	132.5 313.7	210.78 BLDTV20111216ABM	39 15 53.0 114 53 35.0	0.053 505	13.2 2396	18.5	142.5R	68.3M
06 D Elko	K06HT-D	LI	D_N	132.5 313.7	210.78 BLDTV20111216ABM	39 15 53.0 114 53 35.0	0.053 505	13.2 2396	18.5	142.5R	68.3M
06 D Manhattan	K06KQ-D	LI	D_N	188.1 7.9	226.59 BLDTV20110531AQP	38 32 16.0 117 03 57.0	0.020 378	0.3 2235	63.2	142.5R	84.1M
06 D Manhattan	K06KQ-D	LI	D_N	188.1 7.9	226.59 BLDTV20110531AQP	38 32 16.0 117 03 57.0	0.020 378	12.6 2235	0.4	142.5R	84.1M
06 D Ryndon	K06NY-D	LI	D_Y	63.3 244.0	102.04 BLDTV20111219ABC	40 57 54.0 115 36 47.0	0.062 24	12.6 1586	0.4	13.0R	89.0M
06 D Ryndon	K06NY-D	LI	D_Y	63.3 244.0	102.04 BLDTV20111219ABC	40 57 54.0 115 36 47.0	0.062 24	12.6 1586	0.4	13.0R	89.0M
06 D Reno	1330491	CP	_N	248.7 66.7	285.79 BNPDVL20090825AOE	39 35 03.0 119 47 52.0	0.300 367	12.6 1725	0.4	142.5R	143.3M
06 D Reno	1330491	CP	_N	248.7 66.7	285.79 BNPDVL20090825AOE	39 35 03.0 119 47 52.0	0.300 367	12.6 1725	0.4	142.5R	143.3M
06 D Nampa	1330983	CP	D_N	7.5 187.8	355.48 BNPDVL20090825BZD	43 43 49.0 116 07 19.0	0.300 644	12.6 1620	0.4	142.5R	213.0M
06 D Panaca	K06DM-D	LI	D_N	150.1 331.5	394.60 BLDTV20130123ADQ	37 27 34.0 114 27 57.0	0.060 892	12.6 2284	0.4	142.5R	252.1M

Terrain database is USGS 03 SEC, R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM  
Contour distances are on direct line to and from reference station. Reference zone= , Co to 3rd adjacent.  
All separation margins (if shown) include rounding. Call signs with strikeout need not be protected.  
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, \_= Omni), Polarization (C,H,V,E), Beamtilt (Y,N,X)  
\*\*\*affixed to 'IN' or 'OUT' values = site inside restricted contour.