

ENGINEERING REPORT

FM Translator Minor Construction Permit Application

for

**K287BA – Marshalltown, IA
(formerly K284AW)**

Pending License BLFT-20090408AFF

April, 2009

COPYRIGHT 2009

MUNN-REESE, INC.
Broadcast Engineering Consultants
Coldwater, MI 49036

TABLE OF CONTENTS

Discussion of Report

FM Booster/Fill-in Translator Requirements (See Discussion)

Interference Requirements

Exhibit 12.1 - Copy of Existing Antenna Structure Registration

Exhibit 12.2 - Vertical Plan of Antenna System and Support Tower

Exhibit 12.3 - Present vs Proposed Service Contour Study

Exhibit 12.4 - Proposed vs Primary Station Service Contour Study

Contour Overlap Requirements

Exhibit 12.5 - Tabulation of Proposed Allocation

TV Channel 6 Protection Requirements (See Discussion)

Unattended Operation Requirements (See Discussion)

Multiple Translator Requirements (See Discussion)

RF Radiation Study Requirement

Exhibit 16.1 - RF Compliance Study

(Exhibit numbering is in response to FCC Online Form 349, Section III-A)

Discussion

This firm has been retained to prepare the required engineering report in support of a minor construction permit application for FM translator K287BA (formerly K284AW), Marshalltown, IA, pending License No. BLFT-20090408AFF. K287BA presently operates on 105.3 MHz with 5 watts of non-directional power with an antenna COR of 309 meters AMSL. A simple change in frequency is requested from the present operating site and height. Operation on CH290D with 5 watts ERP at a COR of 309 meters AMSL is requested. The translator will continue to rebroadcast FM station KNWS-FM, Waterloo, IA, Facility ID No. 49786.

The proposed site is existing Antenna Structure Registration Number 1023009. A copy of existing ASR 1023009 has been included in **Exhibit 12.1**. A copy of the vertical antenna system has been included in **Exhibit 12.2**. As this proposal will not increase the overall tower height, it is believed the FAA need not be notified.

It has been determined the translator may be used in the area without interference to any existing FM broadcast station or facility. General allocation details are found in **Exhibit 12.5**. It is believed sufficient clearance exists precluding the need for additional contour protection showings.

The translator site and proposed 60 dBu contour lie completely outside of the KNWS-FM 60 dBu contour. A map of the proposed service area in relation to the primary station service contour has been included in **Exhibit 12.4**.

Regarding protection of international concerns, the facility is and will remain more than 320 km of the common border between the United States and Canada or Mexico. As a result, no further international showings are required.

The proposed operating parameters have been changed from the licensed values, however the proposed service contour serves a portion of the present service area as seen in **Exhibit 12.3**.

RADIATION PROTECTION: The Commission requires an engineering study regarding compliance with the guidelines for human protection from radiofrequency radiation. This report section is in response to that provision of the Rules.

The current Federal Communications Commission guidelines for RF radiation protection are set forth in OET Bulletin No. 65 (Edition 97-01), and the accompanying Supplement A, (Edition 97-01).

The FM Broadcast facility proposed in this application will not produce human exposure to radiofrequency radiation in excess of the applicable safety standards specified in §1.1310 of the Commission's rules. **Exhibit 16.1** provides the details of the study that was made to demonstrate compliance. The facility is properly marked with signs, and entry is restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed.

Discussion (continued)

In the event work would be required in proximity to the antenna such that the person or persons working in the area would be potentially exposed to fields in excess of the guidelines set forth in OET Bulletin No. 65 (Edition 97-01), the transmitter power will be reduced or the station will cease operation during the critical period.

DISTANCES TO CONTOURS: The following tabulation of the distances to the proposed service contours results from calculations performed in accordance with §73.313(d) and §73.333 Figure 1 utilizing the NGDC 30 second terrain database.

N. Lat. = 420121.0 W. Lng. = 925957.0 HAAT and Distance to Contour V-Soft 3-16 km, 131 pts Method - NGDC 30 SEC						
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5
000	284.0	25.0	0.0050	-23.01	1.000	2.68
030	283.1	25.9	0.0050	-23.01	1.000	2.68
060	278.2	30.8	0.0050	-23.01	1.000	2.71
090	277.6	31.4	0.0050	-23.01	1.000	2.73
120	285.0	24.0	0.0050	-23.01	1.000	2.68
150	295.8	13.2	0.0050	-23.01	1.000	2.68
180	310.3	-1.3	0.0050	-23.01	1.000	2.68
210	305.7	3.3	0.0050	-23.01	1.000	2.68
240	311.4	-2.4	0.0050	-23.01	1.000	2.68
270	306.2	2.8	0.0050	-23.01	1.000	2.68
300	306.7	2.3	0.0050	-23.01	1.000	2.68
330	292.8	16.2	0.0050	-23.01	1.000	2.68
Ave El= 294.74 M HAAT= 14.26 M AMSL= 309 M						