

MINOR CHANGE APPLICATION
CUMULUS LICENSING LLC
WTOD AM RADIO STATION
has: 1560 kHz - 5.0 kW - DAD
req: 1560 kHz - 0.002/4.3 kW - DA2
TOLEDO, OHIO
February 2008

EXHIBIT #1F

Proposed Facility Daytime Horizontal Pattern Tabulation

Lat: 41-37-34 N Lng: 083-38-03 W
Power: 4.3 Kw Theo RMS: 599.03 mV/m @ 1km @ 4.3 kW

#	Field Ratio	Phase (deg)	Spacing (deg)	Orient (deg)	Height (deg)	Ref Switch	TL Switch	A (deg)	B (deg)	C (deg)	D (deg)
1	1.000	0.0	0.0	0.0	92.5	0	0	0.0	0.0	0.0	0.0
2	0.600	15.0	180.0	90.0	92.5	0	0	0.0	0.0	0.0	0.0

Standard Horizontal Plane Pattern

Azimuth (Deg)	Field (mV/m @1km)	Azimuth (Deg)	Field (mV/m @1km)	Azimuth (Deg)	Field (mV/m @1km)
0.0	994.89	120.0	263.18	240.0	411.02
5.0	969.47	125.0	291.98	245.0	366.52
10.0	927.60	130.0	339.26	250.0	332.40
15.0	871.11	135.0	402.25	255.0	308.23
20.0	802.56	140.0	476.72	260.0	292.76
25.0	725.11	145.0	558.18	265.0	284.36
30.0	642.35	150.0	642.35	270.0	281.73
35.0	558.18	155.0	725.11	275.0	284.36
40.0	476.72	160.0	802.56	280.0	292.76
45.0	402.25	165.0	871.11	285.0	308.23
50.0	339.26	170.0	927.60	290.0	332.40
55.0	291.98	175.0	969.47	295.0	366.52
60.0	263.18	180.0	994.89	300.0	411.02
65.0	252.11	185.0	1002.91	305.0	465.32
70.0	254.05	190.0	993.49	310.0	527.91
75.0	262.57	195.0	967.49	315.0	596.59
80.0	272.16	200.0	926.62	320.0	668.64
85.0	279.18	205.0	873.25	325.0	740.97
90.0	281.73	210.0	810.29	330.0	810.29
95.0	279.18	215.0	740.97	335.0	873.25
100.0	272.16	220.0	668.64	340.0	926.62
105.0	262.57	225.0	596.59	345.0	967.49
110.0	254.05	230.0	527.91	350.0	993.49
115.0	252.11	235.0	465.32	355.0	1002.91

MINOR CHANGE APPLICATION
CUMULUS LICENSING LLC
WTOD AM RADIO STATION
has: 1560 kHz - 5.0 kW - DAD
req: 1560 kHz - 0.002/4.3 kW - DA2
TOLEDO, OHIO
February 2008

EXHIBIT #1G

Proposed Facility Daytime Service Contour Tabulation

North Latitude: 41° 37' 34"
West Longitude: 83° 38' 03"

Azimuth	Radiation (mV/m at one km)	Distances to Contours in Kilometers :				
		Contour levels in mV/m.				
		1000.000	25.000	5.000	2.000	.500
0.0	994.89	0.88	13.33	28.60	42.24	75.98
5.0	969.47	0.86	13.14	28.28	41.78	75.16
10.0	927.60	0.82	12.83	27.74	41.01	73.77
15.0	871.11	0.78	12.40	26.99	39.94	71.84
20.0	802.56	0.72	11.86	26.03	38.58	69.39
25.0	725.11	0.66	11.20	24.89	36.96	66.47
30.0	642.35	0.59	10.45	23.58	35.11	63.14
35.0	558.18	0.51	9.63	22.12	33.07	59.48
40.0	476.72	0.44	8.76	20.57	30.91	55.63
45.0	402.25	0.38	7.88	18.99	28.73	51.77
50.0	339.26	0.32	7.07	17.49	26.67	48.16
55.0	291.98	0.28	6.40	16.24	24.96	45.20
60.0	263.18	0.25	5.97	15.41	23.83	43.26
65.0	252.11	0.24	5.80	15.08	23.37	42.49
70.0	254.05	0.24	5.83	15.13	23.46	42.62
75.0	262.57	0.25	5.96	15.39	23.81	43.22
80.0	272.16	0.26	6.11	15.68	24.19	43.88
85.0	279.18	0.27	6.21	15.88	24.49	44.37
90.0	281.73	0.27	6.25	15.95	24.57	44.59
95.0	279.18	0.27	6.21	16.30	24.24	44.05
100.0	272.16	0.26	6.11	16.82	23.66	43.59
105.0	262.57	0.25	5.96	17.00	23.69	43.52
110.0	254.05	0.24	5.83	17.07	23.62	43.46
115.0	252.11	0.24	5.80	17.14	23.66	43.53
120.0	263.18	0.25	5.97	17.70	24.40	44.26
125.0	291.98	0.28	6.40	18.97	26.10	46.92
130.0	339.26	0.32	7.07	20.83	28.61	49.90
135.0	402.25	0.38	7.88	23.02	31.57	52.65
140.0	476.72	0.44	8.76	25.30	34.65	55.65
145.0	558.18	0.51	9.63	27.49	37.61	58.54
150.0	642.35	0.59	10.45	29.45	40.30	61.07
155.0	725.11	0.66	11.20	31.13	42.64	63.08
160.0	802.56	0.72	11.86	32.46	44.55	64.46
165.0	871.11	0.78	12.40	33.39	45.96	65.10
170.0	927.60	0.82	12.83	33.88	46.83	65.94
175.0	969.47	0.86	13.14	32.89	45.12	64.92

See Exhibit #2E2 for ground conductivity tabulation

MINOR CHANGE APPLICATION
CUMULUS LICENSING, LLC
WTOD AM RADIO STATION
has: 1560 kHz - 5.0 kW - DAD
req: 1560 kHz - 0.002/4.3 kW - DA2
TOLEDO, OHIO
February 2008

EXHIBIT #1G (continued)

Proposed Facility Daytime Service Contour Tabulation

North Latitude: 41° 37' 34"
West Longitude: 83° 38' 03"

Azimuth	Radiation (mV/m at one km)	Distances to Contours in Kilometers :				
		Contour levels in mV/m.				
		1000.000	25.000	5.000	2.000	.500
180.0	994.89	0.88	13.33	28.60	46.90	91.11
185.0	1002.91	0.89	13.38	28.70	42.39	76.24
190.0	993.49	0.88	13.32	28.58	42.22	75.94
195.0	967.49	0.86	13.13	28.25	41.75	75.09
200.0	926.62	0.82	12.83	27.73	40.99	73.74
205.0	873.25	0.78	12.42	27.02	39.98	71.91
210.0	810.29	0.73	11.92	26.14	38.74	69.67
215.0	740.97	0.67	11.34	25.13	37.30	67.08
220.0	668.64	0.61	10.70	24.00	35.71	64.22
225.0	596.59	0.55	10.02	22.80	34.02	61.19
230.0	527.91	0.49	9.32	21.56	32.29	58.09
235.0	465.32	0.43	8.63	20.34	30.59	55.06
240.0	411.02	0.38	7.99	19.18	29.00	52.24
245.0	366.52	0.34	7.43	18.16	27.59	49.77
250.0	332.40	0.31	6.98	17.31	26.43	47.75
255.0	308.23	0.29	6.64	16.68	25.57	46.25
260.0	292.76	0.28	6.42	16.26	24.99	45.25
265.0	284.36	0.27	6.29	16.02	24.67	44.70
270.0	281.73	0.27	6.25	15.95	24.57	44.53
275.0	284.36	0.27	6.29	16.02	24.67	44.70
280.0	292.76	0.28	6.42	16.26	24.99	45.25
285.0	308.23	0.29	6.64	16.68	25.57	46.25
290.0	332.40	0.31	6.98	17.31	26.43	47.75
295.0	366.52	0.34	7.43	18.16	27.59	49.77
300.0	411.02	0.38	7.99	19.18	29.00	52.24
305.0	465.32	0.43	8.63	20.34	30.59	55.06
310.0	527.91	0.49	9.32	21.56	32.29	58.09
315.0	596.59	0.55	10.02	22.80	34.02	61.19
320.0	668.64	0.61	10.70	24.00	35.71	64.22
325.0	740.97	0.67	11.34	25.13	37.30	67.08
330.0	810.29	0.73	11.92	26.14	38.74	69.67
335.0	873.25	0.78	12.42	27.02	39.98	71.91
340.0	926.62	0.82	12.83	27.73	40.99	73.74
345.0	967.49	0.86	13.13	28.25	41.75	75.09
350.0	993.49	0.88	13.32	28.58	42.22	75.94
355.0	1002.91	0.89	13.38	28.70	42.39	76.24

See Exhibit #2E2 for ground conductivity tabulation

MINOR CHANGE APPLICATION
CUMULUS LICENSING LLC
WTOD AM RADIO STATION
has: 1560 kHz - 5.0 kW - DAD
req: 1560 kHz - 0.002/4.3 kW - DA2
TOLEDO, OHIO
February 2008

EXHIBIT #1H

Licensed Facility Daytime Service Contour Tabulation

North Latitude: 41° 36' 59"
West Longitude: 83° 37' 22"

Azimuth	Radiation (mV/m at one km)	Distances to Contours in Kilometers :			
		Contour levels in mV/m.			
		1000.000	5.000	2.000	.500
0.0	1030.71	0.91	29.04	42.88	77.12
5.0	998.82	0.88	28.64	42.31	76.11
10.0	950.33	0.84	28.03	41.43	74.53
15.0	887.37	0.79	27.21	40.25	72.40
20.0	812.77	0.73	26.18	38.79	69.76
25.0	730.02	0.66	24.96	37.06	66.66
30.0	643.04	0.59	23.59	35.12	63.16
35.0	556.15	0.51	22.08	33.02	59.39
40.0	473.93	0.44	20.51	30.84	55.49
45.0	401.30	0.38	18.96	28.70	51.71
50.0	343.25	0.32	17.59	26.81	48.40
55.0	304.04	0.29	16.57	25.42	45.98
60.0	285.08	0.27	16.04	24.70	44.75
65.0	283.31	0.27	15.99	24.63	44.63
70.0	292.32	0.28	16.25	24.97	45.23
75.0	305.46	0.29	16.61	25.47	46.07
80.0	317.77	0.30	16.94	26.29	47.67
85.0	326.20	0.31	17.18	27.09	49.24
90.0	329.18	0.31	17.66	28.31	50.24
95.0	326.06	0.31	17.47	28.08	50.94
100.0	317.20	0.30	17.78	28.28	50.32
105.0	304.20	0.29	17.74	28.05	50.45
110.0	290.16	0.28	17.40	27.51	50.29
115.0	280.18	0.27	17.06	26.02	50.45
120.0	281.16	0.27	17.14	26.12	50.58
125.0	299.80	0.28	17.94	26.19	50.26
130.0	339.23	0.32	21.48	35.27	65.55
135.0	397.86	0.37	23.54	38.04	69.99
140.0	471.22	0.44	25.82	41.11	74.97
145.0	554.15	0.51	28.08	44.17	80.01
150.0	641.67	0.59	30.17	47.02	84.77
155.0	729.16	0.66	32.00	49.55	89.07
160.0	812.30	0.73	33.51	51.67	92.76
165.0	887.16	0.79	34.63	53.31	95.74
170.0	950.28	0.84	35.32	54.43	97.91
175.0	998.82	0.88	35.52	54.94	99.21

See Exhibit #2F2 for ground conductivity tabulation

MINOR CHANGE APPLICATION
CUMULUS LICENSING LLC
WTOD AM RADIO STATION
has: 1560 kHz - 5.0 kW - DAD
req: 1560 kHz - 0.002/4.3 kW - DA2
TOLEDO, OHIO
February 2008

EXHIBIT #1H (continued)

Licensed Facility Daytime Service Contour Tabulation

North Latitude: 41° 36' 59"
West Longitude: 83° 37' 22"

Azimuth	Radiation (mV/m at one km)	Distances to Contours in Kilometers :			
		Contour levels in mV/m.			
		1000.000	5.000	2.000	.500
180.0	1030.71	0.91	31.99	51.61	96.39
185.0	1044.77	0.92	29.21	43.13	77.56
190.0	1040.77	0.92	29.16	43.06	77.44
195.0	1019.46	0.90	28.90	42.68	76.76
200.0	982.43	0.87	28.44	42.02	75.58
205.0	932.03	0.83	27.80	41.10	73.92
210.0	871.19	0.78	26.99	39.94	71.84
215.0	803.17	0.72	26.04	38.59	69.41
220.0	731.39	0.66	24.98	37.09	66.71
225.0	659.23	0.60	23.85	35.50	63.83
230.0	589.85	0.54	22.68	33.86	60.89
235.0	526.03	0.49	21.53	32.24	58.00
240.0	470.02	0.44	20.43	30.73	55.30
245.0	423.37	0.39	19.45	29.37	52.90
250.0	386.77	0.36	18.63	28.24	50.91
255.0	360.05	0.34	18.00	27.38	49.39
260.0	342.32	0.32	17.57	26.78	48.35
265.0	332.36	0.31	17.31	26.43	47.75
270.0	329.18	0.31	17.23	26.32	47.55
275.0	332.36	0.31	17.31	26.43	47.75
280.0	342.32	0.32	17.57	26.78	48.35
285.0	360.05	0.34	18.00	27.38	49.39
290.0	386.77	0.36	18.63	28.24	50.91
295.0	423.37	0.39	19.45	29.37	52.90
300.0	470.02	0.44	20.43	30.73	55.30
305.0	526.03	0.49	21.53	32.24	58.00
310.0	589.85	0.54	22.68	33.86	60.89
315.0	659.23	0.60	23.85	35.50	63.83
320.0	731.39	0.66	24.98	37.09	66.71
325.0	803.17	0.72	26.04	38.59	69.41
330.0	871.19	0.78	26.99	39.94	71.84
335.0	932.03	0.83	27.80	41.10	73.92
340.0	982.43	0.87	28.44	42.02	75.58
345.0	1019.46	0.90	28.90	42.68	76.76
350.0	1040.77	0.92	29.16	43.06	77.44
355.0	1044.77	0.92	29.21	43.13	77.56

See Exhibit #2F2 for ground conductivity tabulation