

Page 1 of 3

Exhibit 15-G-3 (cont.)  
Tabulation of Distance to WCAO Daytime Allocation Contours

WCAO	600 kHz	Lic	DA1U	BL890825AF	20060522
MD BALTIMORE				5.000 kW 4 Towers	3 Augmentations
N. Lat: 39 25 47	W. Lon: 76 45 42				9 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
-----	-----	-----	-----
165.0-	1348.0	413.56	566.43
170.0M*	1178.7	172.99	223.03
175.0+	996.4	155.54	205.53
180.0+	809.6	132.98	181.10
185.0	626.2	107.29	155.62
190.0	454.0	90.19	128.45
195.0	305.1	70.40	100.23
197.0-	255.0	61.59	96.45
200.0-	193.5	49.95	75.02
205.0-	138.4	43.03	58.36
207.0M*	134.0	42.41	57.55
210.0+	139.9	43.24	58.63
215.0+	159.9	45.91	62.10
217.0+	166.8	46.78	63.25
220.0	174.5	47.72	64.48
225.0	180.4	48.43	65.40
230.0	176.1	47.91	64.73
235.0	157.5	45.61	61.71
240.0	129.2	41.72	56.66
242.0-	116.6	39.82	54.18
245.0-	98.2	36.78	50.26
250.0-	76.9	32.78	45.12
252.0M*	75.0	32.39	44.61
255.0+	80.4	33.49	46.03
260.0+	103.3	37.66	51.40
262.0+	113.9	39.40	53.63
265.0	128.8	41.66	56.58
270.0	147.4	44.26	59.96
275.0	154.7	45.24	61.23
280.0	149.9	44.60	60.40
281.0-	147.5	38.56	54.26
285.0-	135.3	36.87	52.06
290.0-	122.7	35.03	49.67
291.0M*	122.3	34.96	49.59
295.0+	133.1	36.55	51.65
300.0+	175.4	42.10	58.89
301.0+	186.8	43.45	60.66
305.0	237.8	54.65	73.58
310.0	306.1	67.29	88.25
315.0	370.4	74.48	97.13
320.0-	423.5	71.41	95.33
325.0-	460.4	74.44	99.19
330.0M*	478.1	76.29	101.42

Exhibit 15-G-3 (cont.)  
 Tabulation of Distance to WCAO Daytime Allocation Contours

WCAO	600 kHz	Lic	DA1U	BL890825AF	20060522
MD	BALTIMORE			5.000 kW    4 Towers	3 Augmentations
N. Lat:	39 25 47	W. Lon:	76 45 42		9 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
-----	-----	-----	-----
335.0+	475.8	76.99	102.07
340.0+	454.7	76.68	101.31
345.0	417.5	87.05	110.83
350.0	368.5	85.80	108.40
355.0	312.4	81.96	105.30