

WSOM	600 kHz	Lic	DA2U	BL000410CH	20060522
OH SALEM				1.000 kW 2 Towers	0 Augmentations
N. Lat: 40 49 47	W. Lon: 80 55 49				0 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.
All distances are in kilometers (US metric curves)
All radiations are in mV/m at one kilometer

Bearing	Radiation	Distance to Contours	
		0.500	0.250
0.0	356.2	140.54	189.41
5.0	406.7	148.20	199.21
10.0	450.3	151.33	201.04
15.0	484.0	152.41	203.87
20.0	505.5	149.88	200.79
25.0	513.1	149.35	193.03
30.0	506.0	149.99	184.55
35.0	484.1	149.69	183.73
40.0	448.6	148.52	181.71
45.0	401.2	141.98	169.03
50.0	344.6	127.87	149.87
55.0	282.2	115.26	135.54
60.0	218.1	102.71	121.00
65.0	157.7	90.74	106.85
70.0	111.5	79.74	97.33
75.0	97.4	72.59	92.92
80.0	119.8	75.47	97.17
85.0	157.4	80.96	104.59
90.0	196.0	85.99	111.32
95.0	230.5	90.01	116.69
100.0	259.3	93.07	120.78
105.0	281.7	95.28	123.75
110.0	298.0	96.72	125.72
115.0	308.1	97.48	126.80
120.0	312.2	97.64	127.08
125.0	310.4	97.16	126.55
130.0	302.7	96.04	125.19
135.0	289.0	94.21	122.92
140.0	269.0	91.56	119.61
145.0	242.7	87.96	115.09
150.0	210.4	83.19	109.10
155.0	173.2	77.07	101.42
160.0	134.2	69.62	92.09
165.0	103.0	62.65	83.34
170.0	100.9	62.59	83.16
175.0	136.7	71.70	94.30

Exhibit 15-R-2 (cont.)

WSOM	600 kHz	Lic	DA2U	BL000410CH	20060522
OH SALEM				1.000 kW	2 Towers
N. Lat: 40 49 47	W. Lon: 80 55 49				0 Augmentations
					0 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
180.0	193.1	83.19	108.40
185.0	256.5	93.96	121.58
190.0	320.2	103.60	133.29
195.0	379.5	112.37	143.72
200.0	430.9	120.58	152.19
205.0	471.5	128.82	160.80
210.0	499.0	138.28	170.17
215.0	512.1	149.39	180.42
220.0	510.3	162.84	193.21
225.0	494.2	160.77	209.28
230.0	465.1	156.92	204.71
235.0	425.2	151.27	198.05
240.0	377.0	143.97	189.38
245.0	323.7	134.97	178.74
250.0	268.4	124.42	166.17
255.0	214.5	112.41	151.82
260.0	165.5	99.49	136.26
265.0	126.2	86.92	121.04
270.0	102.2	77.85	109.97
275.0	97.3	75.80	107.44
280.0	106.4	79.50	111.99
285.0	120.4	84.85	118.54
290.0	133.5	89.42	124.11
295.0	142.5	92.42	127.73
300.0	146.4	93.68	129.24
305.0	144.7	93.14	128.59
310.0	137.6	90.82	125.81
315.0	126.0	86.85	120.95
320.0	111.8	81.65	114.60
325.0	99.7	76.83	108.72
330.0	98.0	76.13	107.85
335.0	114.4	82.63	115.83
340.0	148.3	94.29	129.98
345.0	194.0	107.32	145.71
350.0	246.5	119.76	162.13
355.0	301.7	130.93	176.86