

# **Modification of BPFT-20160425ACD** **Scott Communications, Inc.**

REFERENCE 32 19 33.0 N. 88 41 14.0 W.		CH# 261D - 100.1 MHz, Pwr= 0.25 kW DA, HAAT= 0.0 M, COR= 257 M Average Protected F(50-50)= 7.1 km Standard Directional						DISPLAY DATES DATA 04-27-17 SEARCH 04-27-17			
CH CITY	CALL	TYPE	ANT STATE	AZI. <--	DIST FILE #	LAT. LNG.	Pwr(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap In km)	*OUT*
261D Livingston	W261CSI	CP	C AL	0.0 0.0	0.00 BPFT20160425ACD	32 19 33.0 88 41 14.0	0.250	49.7 257	14.9 Scott Communications, Inc.	-64.4	-63.9
261D Livingston	W261CSI	LIC	C AL	0.0 0.0	0.00 BLFT20160205AFC	32 19 33.0 88 41 14.0	0.250	49.7 257	14.9 Scott Communications, Inc.	-64.4	-63.9
262C0 Laurel	WNSL	LIC	CX MS	205.6 25.3	98.19 BMLH20060918AHV	31 31 37.0 89 08 07.0	100.000 324	107.6 394	74.1 Cc Licenses, Lic	-23.2*	3.4
259D Meridian	W259BP	LIC	DC MS	197.8 17.8	1.61 BLFT20160915AAP	32 18 43.0 88 41 33.0	0.250	1.1 319	18.8 Mississippi Broadcasters,	-12.9*	-18.2*
263D Meridian	W263CF	LIC	C MS	292.9 112.9	0.39 BLFT20160407ABQ	32 19 38.0 88 41 28.0	0.010	0.2 265	6.5 Max One Communications, Inc	-6.3*	-6.3*
261C2 Selma	WDXX	LIC	NCX AL	87.4 268.3	164.24 BLH20130301AGT	32 22 54.0 86 56 37.0	50.000 150	139.9 199	54.2 Broadsouth Communications,	12.1	68.3

Terrain database is USGS 03 SEC, R= 73.215 qualifying spacings or FCC minimum spacings in KM, M= Margin in KM  
Contour distances are on direct line to and from reference station. Reference Zone= East Zone, Co to 3rd adjacent.  
All separation margins (if shown) include rounding. Call signs with exclamation marks need not be protected.  
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, \_= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)  
"-"affixed to 'IN' or 'OUT' values = site inside restricted contour.

Clearance to second-adjacent W259BP and W263CF will be derived through the use of Section 74.1204(d).

**Bromo Communications, Inc.**