

EXHIBIT A

ENGINEERING STATEMENT

The engineering data contained herein have been prepared on behalf of TRI-STATE CHRISTIAN TV, INC., licensee of Class A LPTV station WDYR-CA, Channel 33 in Dyersburg, Tennessee, in support of this Application for Construction Permit to specify digital operation on Channel 18 from the licensed WDYR-CA site. This proposal is being submitted in response to the Commission's assignment of Channel 33 to WPGD-DT in Hendersonville, Tennessee. The site of WDYR-CD is located 239 kilometers from that of WPGD-DT, thereby placing this Class A television station in a displacement situation.

It is proposed to mount a standard ERI omnidirectional antenna at the 147-meter level of an existing 152-meter communications tower. Exhibit B is a map upon which the predicted service contours are plotted. It is important to note that the newly proposed 51 dBu contour encompasses the station's city of license. Operating parameters for the proposed facility are tabulated in Exhibit C. An interference study is provided in Exhibit D, and a power density calculation follows as Exhibit E.

Because no change in the overall height or location of the existing tower is proposed, the FAA has not been notified of this application. The FCC issued Antenna Structure Registration Number 1059207 to this tower.

I declare under penalty of perjury that the foregoing statements and the attached exhibits, which were prepared by me or under my immediate supervision, are true and correct to the best of my knowledge and belief.


KYLE T. FISHER

March 18, 2010

41 dBu : 243,971

SMITHANDFISHER


41 DBU

51 DBU.

WDYR-LD-D.C

Jackson

EXHIBIT B



km

km

PROPOSED OPERATING PARAMETERS

PROPOSED WDYR-CD
CHANNEL 18 – DYERSBURG, TENNESSEE

Transmitter Power Output:	1.9 kw
Transmission Line Efficiency:	57.2%
Antenna Power Gain – Toward Horizon:	14.06
Antenna Power Gain – Main Lobe:	14.06
Effective Radiated Power – Toward Horizon:	15.0 kw
Effective Radiated Power – Main Lobe:	15.0 kw
Transmitter Make and Model:	Type-accepted
Rated Output	2.0 kw
Transmission Line Make and Model:	Andrew HJ7-50A
Size and Type:	1-5/8" air heliax
Length:	510 feet*
Antenna Make and Model:	ERI AL8
Orientation	omnidirectional
Beam Tilt	1.75 degrees
Radiation Center Above Ground:	147 meters
Radiation Center Above Mean Sea Level:	257 meters

*estimated

EXHIBIT D-1

LONGLEY-RICE INTERFERENCE STUDIES
PROPOSED WDYR-CD
CHANNEL 18 – DYERSBURG, TENNESSEE

We conducted detailed interference studies using the Longley-Rice methodology contained in the Commission's *OET Bulletin No. 69*, with respect to all facilities of concern. The software utilizes a 1-square kilometer cell size, calculates signal strength at 0.1 kilometer increments along each radial studied, and employs the 2000 U.S. Census to count population within cells. In addition, the program does not attribute interference to the proposed facility in cells within the protected contour of the station under study where interference from another source (other than proposed WDYR-CD) already is predicted to exist (also known as "masking"). The results of these studies are provided in Exhibit D-2. They conclude that the facility proposed herein causes no significant new interference to any of the potentially affected stations.

As a result, it is believed that the proposed WDYR-CD facility complies with the requirements of Sections 74.709, 74.793(e), 74.793(f), 74.793(g), 74.793(h), 74.794(b) and 73.1030 of the Commission's Rules.

INTERFERENCE SUMMARY

PROPOSED WDYR-CD
CHANNEL 18 – DYERSBURG, TENNESSEE

<u>Call Sign</u>	<u>Status</u>	<u>City, State</u>	<u>Ch.</u>	<u>Longley-Rice Service Population</u>	<u>Unmasked Interference From Proposed Facility</u>	<u>%</u>
W18BL-D BDFCDTA-20090824AKM	CP	Adamsville, TN	18	68,412	60	0.1

POWER DENSITY CALCULATION
PROPOSED WDYR-CD
CHANNEL 18 – DYERSBURG, TENNESSEE

Since the FCC considers the possible biological effects of RF transmissions in its environmental determinations, we have studied the matter with respect to this Dyersburg facility. Employing the methods set forth in *OET Bulletin No. 65* and considering a main-lobe effective radiated power of 15.0 kw, an antenna radiation center 147 meters above ground, and the vertical pattern of the ERI antenna, maximum power density two meters above ground of 0.00022 mw/cm^2 is calculated to occur 131 meters from the base of the tower. Since this is less than 0.1 percent of the 0.33 mw/cm^2 reference for uncontrolled environments (areas with public access) surrounding a facility operating on Channel 18 (494-500 MHz), this proposal may be excluded from consideration with respect to public exposure to nonionizing electromagnetic radiation.

Further, the station owner will take whatever precautionary steps are necessary, such as reducing power or leaving the air temporarily, to ensure that workers operating in the vicinity of the antenna are not exposed to excessive nonionizing radiation.