

TECHNICAL EXHIBIT  
CONCERNING HUMAN EXPOSURE TO RF ELECTROMAGNETIC ENERGY  
PREPARED FOR  
STATION WTJR-DT  
QUINCY, ILLINOIS  
CH 32 1000 KW (MAX-DA) 308 M


Technical Statement

The proposed facilities were evaluated in terms of potential radio frequency (RF) energy exposure at ground level to workers and the general public. The radiation center for the proposed DTV antenna is located 268 meters above ground level. The maximum DTV ERP is 1000 kW (horizontal polarization). A conservative vertical plane relative field value of 0.1 (for angles below 60 degrees downward) was presumed for the antenna's downward radiation (see Figure 2). The calculated power density at a point 2 meters above ground level is  $0.0047 \text{ mW/cm}^2$ . This is 1.2% of the FCC's recommended limit of  $0.39 \text{ mW/cm}^2$  for channel 32 for an "uncontrolled" environment. Therefore, based on the responsibility threshold of 5%, the proposal will comply with the RF emission rules.

Access to the transmitting site will be restricted and appropriately marked with RFR warning signs. As this is a multi-user site, an agreement will be in effect with the other stations in the event that workers or other authorized personnel enter the restricted area or climb the tower, appropriate measures will be taken to assure worker safety with respect to radio frequency radiation exposure. Such measures include reducing the average exposure by spreading out the work over a longer period of time, wearing "accepted" RFR protective clothing and/or RFR exposure.

Finally, it is noted that this technical exhibit only addresses the potential for radio frequency electromagnetic field exposure. All other aspects of the

environmental processing analysis will be or already has been provided to the FCC by the tower owner as part of the tower registration process.



Jerome J. Manarchuck

du Treil, Lundin & Rackley, Inc.  
201 Fletcher Avenue  
Sarasota, Florida 34237-6019  
(941) 329-6000  
[JERRY@DLR.COM](mailto:JERRY@DLR.COM)

September 19, 2008

ELEVATION PATTERN

Type:	ATW25H2H		Channel:	32
Directivity:	Numeric	dBd	Location:	
Main Lobe:	25.00	13.98	Beam Tilt:	-0.50
Horizontal:	21.07	13.24	Polarization:	Horizontal

Relative Field



Preliminary, subject to final design and review.

## TABULATED DATA FOR ELEVATION PATTERN

Type: ATW25H2H  
PolarizationHorizontal

ANGLEFIELD	dB	ANGLEFIELD	dB	ANGLEFIELD	dB	ANGLEFIELD	dB	ANGLEFIELD	dB
5.00	0.144	-16.80	-6.75	0.108	-19.33	-27.00	0.028	-30.90	-50.50
4.75	0.148	-16.59	-7.00	0.105	-19.58	-27.50	0.024	-32.58	-51.00
4.50	0.135	-17.39	-7.25	0.116	-18.71	-28.00	0.034	-29.50	-51.50
4.25	0.108	-19.33	-7.50	0.130	-17.75	-28.50	0.041	-27.85	-52.00
4.00	0.076	-22.38	-7.75	0.139	-17.14	-29.00	0.036	-28.75	-52.50
3.75	0.071	-22.97	-8.00	0.138	-17.23	-29.50	0.025	-32.04	-53.00
3.50	0.112	-19.05	-8.25	0.127	-17.92	-30.00	0.022	-33.15	-53.50
3.25	0.165	-15.65	-8.50	0.109	-19.25	-30.50	0.032	-29.90	-54.00
3.00	0.213	-13.43	-8.75	0.090	-20.92	-31.00	0.039	-28.18	-54.50
2.75	0.244	-12.25	-9.00	0.078	-22.16	-31.50	0.035	-29.12	-55.00
2.50	0.251	-12.02	-9.25	0.079	-22.05	-32.00	0.024	-32.40	-55.50
2.25	0.230	-12.77	-9.50	0.089	-20.96	-32.50	0.021	-33.76	-56.00
2.00	0.184	-14.68	-9.75	0.101	-19.91	-33.00	0.030	-30.46	-56.50
1.75	0.136	-17.33	-10.00	0.107	-19.37	-33.50	0.037	-28.64	-57.00
1.50	0.154	-16.28	-10.50	0.097	-20.26	-34.00	0.035	-29.24	-57.50
1.25	0.257	-11.80	-11.00	0.069	-23.29	-34.50	0.025	-32.04	-58.00
1.00	0.399	-7.98	-11.50	0.064	-23.94	-35.00	0.018	-34.89	-58.50
0.75	0.550	-5.19	-12.00	0.083	-21.67	-35.50	0.026	-31.70	-59.00
0.50	0.695	-3.17	-12.50	0.086	-21.31	-36.00	0.035	-29.24	-59.50
0.25	0.821	-1.71	-13.00	0.067	-23.54	-36.50	0.036	-29.00	-60.00
0.00	0.918	-0.74	-13.50	0.049	-26.20	-37.00	0.027	-31.37	-60.50
-0.25	0.980	-0.18	-14.00	0.061	-24.29	-37.50	0.018	-35.14	-61.00
-0.50	1.000	0.00	-14.50	0.073	-22.67	-38.00	0.020	-33.98	-61.50
-0.75	0.981	-0.17	-15.00	0.066	-23.68	-38.50	0.030	-30.31	-62.00
-1.00	0.923	-0.70	-15.50	0.045	-26.84	-39.00	0.035	-29.12	-62.50
-1.25	0.835	-1.57	-16.00	0.044	-27.13	-39.50	0.032	-30.03	-63.00
-1.50	0.726	-2.78	-16.50	0.059	-24.58	-40.00	0.021	-33.35	-63.50
-1.75	0.610	-4.29	-17.00	0.061	-24.29	-40.50	0.015	-36.19	-64.00
-2.00	0.504	-5.96	-17.50	0.047	-26.56	-41.00	0.024	-32.40	-64.50
-2.25	0.420	-7.54	-18.00	0.034	-29.37	-41.50	0.033	-29.76	-65.00
-2.50	0.375	-8.53	-18.50	0.044	-27.03	-42.00	0.035	-29.12	-65.50
-2.75	0.359	-8.90	-19.00	0.056	-25.11	-42.50	0.029	-30.75	-66.00
-3.00	0.358	-8.92	-19.50	0.051	-25.93	-43.00	0.019	-34.42	-66.50
-3.25	0.354	-9.02	-20.00	0.035	-29.24	-43.50	0.015	-36.19	-67.00
-3.50	0.336	-9.47	-20.50	0.032	-29.90	-44.00	0.024	-32.40	-67.50
-3.75	0.303	-10.37	-21.00	0.045	-26.94	-44.50	0.033	-29.76	-68.00
-4.00	0.259	-11.75	-21.50	0.050	-26.11	-45.00	0.035	-29.24	-68.50
-4.25	0.212	-13.47	-22.00	0.041	-27.85	-45.50	0.029	-30.60	-69.00
-4.50	0.176	-15.07	-22.50	0.028	-31.21	-46.00	0.020	-33.98	-69.50
-4.75	0.163	-15.76	-23.00	0.033	-29.76	-46.50	0.014	-36.77	-70.00
-5.00	0.171	-15.34	-23.50	0.044	-27.13	-47.00	0.022	-33.15	-70.50
-5.25	0.186	-14.61	-24.00	0.044	-27.03	-47.50	0.032	-30.03	-71.00
-5.50	0.196	-14.15	-24.50	0.033	-29.76	-48.00	0.036	-29.00	-71.50
-5.75	0.194	-14.24	-25.00	0.025	-32.22	-48.50	0.033	-29.76	-72.00
-6.00	0.179	-14.94	-25.50	0.034	-29.37	-49.00	0.024	-32.40	-72.50
-6.25	0.155	-16.19	-26.00	0.042	-27.43	-49.50	0.014	-36.77	-73.00
-6.50	0.128	-17.86	-26.50	0.040	-27.96	-50.00	0.016	-35.92	-73.50

*Preliminary, subject to final design and review.*