

Robert Moore

Csn International

REFERENCE CH# 255D - 98.9 MHz, Pwr= 0.062 kw, HAAT= 163.3 M, COR= 493.5 M
 41 15 26.0 N. Average Protected F(50-50)= 11.73 km
 95 57 51.0 W. Omni-directional

DISPLAY DATES
 DATA 07-03-17
 SEARCH 07-17-17

CH CITY	CALL	TYPE ANT STATE	AZI <--	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*OUT* (Overlap in km)
253C0	KQKQ-FM	LIC _CX	316.5	7.62	41 18 25.0	100.000	10.8	75.7	-68.6*
Council Bluffs		IA	136.5	BLH20021211AAA	96 01 37.0	336	680	Nrg License Sub, Llc	
255D	K255CJ	LIC _V_	92.3	2.30	41 15 23.0	0.003	10.9	3.4	-42.0*
Briggs		NE	272.3	BLFT20170517AAQ	95 56 12.0		400	Csn International	
258D	K258DC	LIC DC_	165.4	3.71	41 13 29.6	0.250	0.2	5.9	-2.8*
Omaha		NE	345.4	BLFT20170306AIV	95 57 10.6		461	Nrg License Sub, Llc	
256C1	KMA-FM	LIC ZCX	119.3	102.53	40 48 04.0	100.000	105.5	72.7	10.6
Clarinda		IA	300.0	BLH20100303ACL	94 54 06.0	299	647	kma Broadcasting, L.p.	
255D	K255CS	CP _C_	221.0	80.27	40 42 39.0	0.115	42.1	12.5	28.8
Lincoln		NE	40.6	BNPFT20131021AFT	96 35 22.0	139	537	Csn International	

Terrain database is FCC NGDC 30 Sec , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
 In & Out distances between contours are shown at closest points. Reference zone= west Zone, Co to 3rd adjacent.
 All separation margins (if shown) include rounding.
 Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
 Incoming contour overlap is ignored.
 "*"affixed to 'IN' or 'OUT' values = site inside restricted contour.