

## Exhibit-34A

### FMOver Analysis Of Proposed Minor Mod KOOZ vs. KSLG-FM

07-10-2013

Terrain Data: FCC NGDC 30 Sec

FMOver Analysis

KOOZ

KSLG-FM BPH20130528AGJ

(^ Max Class Parameters)

Channel = 231C2

Channel = 231C1

Max ERP = 50 kW

Max ERP = 4.1 kW

RCAMSL = 381.86 M, 150M HAAT

RCAMSL = 739.1 M

N. Lat. 42 57 32.0

N. Lat. 40 30 03.0

W. Lng. 124 16 23.0

W. Lng. 124 17 06.0

Protected

Interfering

60 dBu

40 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
120.0	050.0000	0102.1	045.1	008.9	004.1000	0640.2	253.9	17.09	
121.0	050.0000	0090.9	043.1	008.4	004.1000	0640.7	253.9	17.09	
122.0	050.0000	0083.0	041.6	008.0	004.1000	0641.0	253.8	17.11	
123.0	050.0000	0075.0	039.9	007.6	004.1000	0641.4	253.9	17.11	
124.0	050.0000	0065.8	037.8	007.2	004.1000	0642.0	254.2	17.07	
125.0	050.0000	0056.2	035.5	006.6	004.1000	0642.6	254.7	17.00	
126.0	050.0000	0047.6	032.7	006.0	004.1000	0642.6	255.5	16.87	
127.0	050.0000	0041.4	030.5	005.6	004.1000	0642.2	256.2	16.76	
128.0	050.0000	0036.1	028.6	005.2	004.1000	0641.7	256.7	16.66	
129.0	050.0000	0030.1	026.6	004.7	004.1000	0641.1	257.5	16.53	
130.0	050.0000	0022.9	026.5	004.7	004.1000	0641.0	257.1	16.59	
131.0	050.0000	0013.3	026.5	004.6	004.1000	0641.0	256.7	16.65	
132.0	050.0000	0000.2	026.5	004.5	004.1000	0640.9	256.4	16.71	
133.0	050.0000	-0015.4	026.5	004.5	004.1000	0640.8	256.0	16.77	
134.0	050.0000	-0030.2	026.5	004.4	004.1000	0640.7	255.6	16.83	
135.0	050.0000	-0037.6	026.5	004.3	004.1000	0640.6	255.3	16.88	
136.0	050.0000	-0037.1	026.5	004.3	004.1000	0640.5	254.9	16.93	
137.0	050.0000	-0031.1	026.5	004.2	004.1000	0640.5	254.6	16.99	
138.0	050.0000	-0022.2	026.5	004.1	004.1000	0640.4	254.3	17.04	
139.0	050.0000	-0011.0	026.5	004.1	004.1000	0640.3	253.9	17.09	
140.0	050.0000	0002.2	026.5	004.0	004.1000	0640.2	253.6	17.13	
141.0	050.0000	0017.2	026.5	003.9	004.1000	0640.1	253.3	17.18	
142.0	050.0000	0031.8	027.1	003.9	004.1000	0640.2	252.5	17.29	
143.0	050.0000	0043.9	031.4	004.5	004.1000	0640.8	249.0	17.81	
144.0	050.0000	0053.6	034.7	004.9	004.1000	0641.4	246.1	18.25	
145.0	050.0000	0062.6	037.1	005.1	004.1000	0641.7	243.9	18.59	
146.0	050.0000	0070.3	038.9	005.3	004.1000	0641.9	242.1	18.88	
147.0	050.0000	0076.2	040.2	005.3	004.1000	0642.0	240.7	19.13	
148.0	050.0000	0082.4	041.4	005.4	004.1000	0642.0	239.2	19.39	
149.0	050.0000	0090.6	043.0	005.5	004.1000	0642.2	237.5	19.69	
150.0	050.0000	0100.4	044.8	005.6	004.1000	0642.3	235.6	20.04	
151.0	050.0000	0109.0	046.3	005.6	004.1000	0642.3	233.9	20.33	
152.0	050.0000	0115.2	047.3	005.6	004.1000	0642.3	232.7	20.57	
153.0	050.0000	0118.5	047.8	005.5	004.1000	0642.2	231.8	20.72	
154.0	050.0000	0117.8	047.7	005.3	004.1000	0641.9	231.4	20.78	
155.0	050.0000	0114.4	047.1	005.1	004.1000	0641.6	231.5	20.77	
156.0	050.0000	0108.6	046.2	004.8	004.1000	0641.2	231.9	20.70	
157.0	050.0000	0099.1	044.6	004.4	004.1000	0640.8	232.9	20.50	
158.0	050.0000	0085.2	042.0	004.0	004.1000	0640.2	234.9	20.13	
159.0	050.0000	0069.9	038.8	003.5	004.1000	0639.7	237.5	19.66	
160.0	050.0000	0054.4	035.0	003.0	004.1000	0639.2	240.7	19.08	
161.0	050.0000	0039.6	029.8	002.5	004.1000	0638.7	245.3	18.34	
162.0	050.0000	0027.3	026.5	002.1	004.1000	0638.3	248.2	17.90	
163.0	050.0000	0018.2	026.5	002.0	004.1000	0638.2	248.1	17.92	
164.0	050.0000	0011.6	026.5	001.9	004.1000	0638.1	247.9	17.94	
165.0	050.0000	0004.2	026.5	001.8	004.1000	0638.0	247.8	17.96	
166.0	050.0000	-0005.0	026.5	001.7	004.1000	0638.0	247.6	17.98	
167.0	050.0000	-0014.5	026.5	001.6	004.1000	0638.0	247.5	17.99	

## Exhibit-20A

### FMOver Analysis Of Proposed Minor Mod KOOZ vs. KSLG-FM

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
168.0	050.0000	-0022.1	026.5	001.5	004.1000	0638.0	247.4	18.01	
169.0	050.0000	-0031.1	026.5	001.4	004.1000	0638.1	247.3	18.03	
170.0	050.0000	-0041.7	026.5	001.3	004.1000	0638.2	247.2	18.04	
171.0	050.0000	-0049.0	026.5	001.2	004.1000	0638.3	247.1	18.06	
172.0	050.0000	-0050.4	026.5	001.1	004.1000	0638.3	247.1	18.07	
173.0	050.0000	-0047.6	026.5	001.0	004.1000	0638.3	247.0	18.08	
174.0	050.0000	-0046.3	026.5	000.9	004.1000	0638.5	246.9	18.09	
175.0	050.0000	-0049.8	026.5	000.8	004.1000	0638.6	246.9	18.10	
176.0	050.0000	-0057.2	026.5	000.6	004.1000	0638.7	246.8	18.11	
177.0	050.0000	-0064.2	026.5	000.5	004.1000	0638.9	246.8	18.11	
178.0	050.0000	-0064.4	026.5	000.4	004.1000	0639.0	246.8	18.12	
179.0	050.0000	-0056.8	026.5	000.3	004.1000	0639.2	246.8	18.12	
180.0	050.0000	-0048.9	026.5	000.2	004.1000	0639.3	246.8	18.12	
181.0	050.0000	-0039.3	026.5	000.1	004.1000	0639.4	246.8	18.13	
182.0	050.0000	-0024.6	026.5	000.0	004.1000	0639.6	246.8	18.13	
183.0	050.0000	-0009.6	026.5	359.9	004.1000	0639.7	246.8	18.12	
184.0	050.0000	-0006.5	026.5	359.8	004.1000	0639.8	246.8	18.12	
185.0	050.0000	-0009.2	026.5	359.7	004.1000	0640.0	246.9	18.12	
186.0	050.0000	-0013.9	026.5	359.6	004.1000	0640.1	246.9	18.11	
187.0	050.0000	-0011.7	026.5	359.5	004.1000	0640.3	247.0	18.11	
188.0	050.0000	-0007.9	026.5	359.4	004.1000	0640.4	247.0	18.10	
189.0	050.0000	-0004.2	026.5	359.3	004.1000	0640.5	247.1	18.09	
190.0	050.0000	0000.4	026.5	359.2	004.1000	0640.7	247.2	18.08	
191.0	050.0000	0005.2	026.5	359.1	004.1000	0640.8	247.3	18.07	
192.0	050.0000	0014.6	026.5	359.0	004.1000	0640.9	247.4	18.05	
193.0	050.0000	0022.7	026.5	358.9	004.1000	0641.0	247.5	18.04	
194.0	050.0000	0022.0	026.5	358.8	004.1000	0641.2	247.6	18.02	
195.0	050.0000	0014.7	026.5	358.7	004.1000	0641.3	247.7	18.01	
196.0	050.0000	0004.5	026.5	358.6	004.1000	0641.4	247.9	17.99	
197.0	050.0000	-0005.1	026.5	358.5	004.1000	0641.5	248.0	17.97	
198.0	050.0000	-0013.0	026.5	358.4	004.1000	0641.7	248.2	17.95	
199.0	050.0000	-0020.1	026.5	358.3	004.1000	0641.8	248.3	17.93	
200.0	050.0000	-0026.7	026.5	358.2	004.1000	0641.9	248.5	17.90	
201.0	050.0000	-0030.2	026.5	358.1	004.1000	0642.0	248.7	17.88	
202.0	050.0000	-0029.2	026.5	358.0	004.1000	0642.1	248.8	17.85	
203.0	050.0000	-0025.7	026.5	357.9	004.1000	0642.3	249.0	17.83	
204.0	050.0000	-0019.7	026.5	357.8	004.1000	0642.4	249.2	17.80	
205.0	050.0000	-0012.8	026.5	357.7	004.1000	0642.5	249.4	17.77	
206.0	050.0000	-0005.9	026.5	357.6	004.1000	0642.6	249.7	17.74	
207.0	050.0000	-0000.3	026.5	357.5	004.1000	0642.7	249.9	17.71	
208.0	050.0000	0001.1	026.5	357.4	004.1000	0642.8	250.1	17.68	
209.0	050.0000	-0004.6	026.5	357.3	004.1000	0642.9	250.4	17.64	
210.0	050.0000	-0014.2	026.5	357.3	004.1000	0643.0	250.6	17.61	
211.0	050.0000	-0023.5	026.5	357.2	004.1000	0643.1	250.9	17.57	
212.0	050.0000	-0031.0	026.5	357.1	004.1000	0643.2	251.1	17.54	
213.0	050.0000	-0039.7	026.5	357.0	004.1000	0643.3	251.4	17.50	
214.0	050.0000	-0047.7	026.5	356.9	004.1000	0643.4	251.7	17.46	
215.0	050.0000	-0052.6	026.5	356.8	004.1000	0643.5	251.9	17.42	
216.0	050.0000	-0052.3	026.5	356.8	004.1000	0643.6	252.2	17.38	
217.0	050.0000	-0042.7	026.5	356.7	004.1000	0643.7	252.5	17.34	
218.0	050.0000	-0025.4	026.5	356.6	004.1000	0643.8	252.8	17.29	
219.0	050.0000	-0007.7	026.5	356.5	004.1000	0643.9	253.1	17.25	
220.0	050.0000	0005.1	026.5	356.4	004.1000	0644.0	253.5	17.20	
221.0	050.0000	0012.5	026.5	356.4	004.1000	0644.0	253.8	17.15	
222.0	050.0000	0016.9	026.5	356.3	004.1000	0644.1	254.1	17.10	
223.0	050.0000	0019.4	026.5	356.2	004.1000	0644.2	254.4	17.05	
224.0	050.0000	0020.1	026.5	356.2	004.1000	0644.3	254.8	17.00	
225.0	050.0000	0019.0	026.5	356.1	004.1000	0644.3	255.1	16.95	
226.0	050.0000	0015.9	026.5	356.0	004.1000	0644.4	255.5	16.90	
227.0	050.0000	0013.3	026.5	356.0	004.1000	0644.4	255.8	16.84	
228.0	050.0000	0012.1	026.5	355.9	004.1000	0644.5	256.2	16.78	
229.0	050.0000	0014.5	026.5	355.8	004.1000	0644.6	256.6	16.72	
230.0	050.0000	0022.2	026.5	355.8	004.1000	0644.6	257.0	16.66	
231.0	050.0000	0038.2	029.3	355.2	004.1000	0646.0	255.7	16.88	
232.0	050.0000	0060.7	036.7	353.8	004.1000	0650.6	252.2	17.47	
233.0	050.0000	0083.8	041.7	352.7	004.1000	0653.6	250.2	17.79	

## Exhibit-20A

### FMOver Analysis Of Proposed Minor Mod KOOZ vs. KSLG-FM

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
234.0	050.0000	0103.9	045.4	351.9	004.1000	0655.7	249.1	17.97	
235.0	050.0000	0120.6	048.1	351.3	004.1000	0657.1	248.6	18.06	
236.0	050.0000	0136.4	050.3	350.8	004.1000	0658.2	248.5	18.10	
237.0	050.0000	0150.9	052.3	350.3	004.1000	0659.0	248.5	18.11	
238.0	050.0000	0163.1	053.8	349.9	004.1000	0659.4	248.7	18.07	
239.0	050.0000	0172.7	054.9	349.6	004.1000	0659.6	249.3	18.00	

07-10-2013

Terrain Data: FCC NGDC 30 Sec

FMOver Analysis

KSLG-FM BPH20130528AGJ

KOOZ

(^ Max Class Parameters)

Channel = 231C1

Channel = 231C2

Max ERP = 4.1 kW

Max ERP = 3.5 kW

RCAMSL = 739.1 M

RCAMSL = 691 M, 150M

HAAT

N. Lat. 40 30 03.0

N. Lat. 42 57 32.0

W. Lng. 124 17 06.0

W. Lng. 124 16 23.0

Protected

Interfering

60 dBu

40 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
300.0	004.1000	0664.0	060.7	192.6	003.5000	0328.8	248.7	12.62	
301.0	004.1000	0667.2	060.8	192.6	003.5000	0328.5	247.7	12.78	
302.0	004.1000	0670.1	060.9	192.5	003.5000	0328.0	246.6	12.93	
303.0	004.1000	0672.5	061.0	192.4	003.5000	0327.4	245.6	13.09	
304.0	004.1000	0674.5	061.1	192.4	003.5000	0326.7	244.6	13.24	
305.0	004.1000	0675.7	061.1	192.3	003.5000	0326.0	243.6	13.40	
306.0	004.1000	0676.1	061.1	192.2	003.5000	0325.2	242.6	13.55	
307.0	004.1000	0675.8	061.1	192.1	003.5000	0324.2	241.6	13.70	
308.0	004.1000	0674.9	061.1	191.9	003.5000	0323.2	240.7	13.84	
309.0	004.1000	0673.5	061.0	191.8	003.5000	0322.1	239.7	13.98	
310.0	004.1000	0672.0	061.0	191.7	003.5000	0320.9	238.8	14.12	
311.0	004.1000	0670.5	060.9	191.5	003.5000	0319.5	237.9	14.25	
312.0	004.1000	0669.1	060.9	191.4	003.5000	0318.1	237.0	14.38	
313.0	004.1000	0668.3	060.9	191.3	003.5000	0316.7	236.1	14.51	
314.0	004.1000	0667.7	060.8	191.1	003.5000	0315.3	235.3	14.64	
315.0	004.1000	0667.4	060.8	191.0	003.5000	0314.1	234.4	14.77	
316.0	004.1000	0667.5	060.8	190.8	003.5000	0312.9	233.5	14.90	
317.0	004.1000	0667.2	060.8	190.7	003.5000	0311.9	232.6	15.03	
318.0	004.1000	0666.9	060.8	190.5	003.5000	0311.1	231.8	15.15	
319.0	004.1000	0666.5	060.8	190.3	003.5000	0310.5	231.0	15.28	
320.0	004.1000	0666.0	060.8	190.2	003.5000	0310.1	230.2	15.41	
321.0	004.1000	0665.4	060.8	190.0	003.5000	0309.4	229.4	15.54	
322.0	004.1000	0665.3	060.8	189.8	003.5000	0308.7	228.6	15.66	
323.0	004.1000	0665.7	060.8	189.6	003.5000	0307.9	227.8	15.77	
324.0	004.1000	0667.0	060.8	189.4	003.5000	0307.0	227.0	15.89	
325.0	004.1000	0668.5	060.9	189.3	003.5000	0306.1	226.2	16.01	
326.0	004.1000	0670.6	060.9	189.1	003.5000	0305.2	225.4	16.13	
327.0	004.1000	0672.1	061.0	188.9	003.5000	0304.4	224.7	16.24	
328.0	004.1000	0672.6	061.0	188.7	003.5000	0303.6	224.0	16.34	
329.0	004.1000	0672.1	061.0	188.5	003.5000	0302.9	223.3	16.44	
330.0	004.1000	0670.7	060.9	188.2	003.5000	0302.1	222.7	16.54	
331.0	004.1000	0668.4	060.9	188.0	003.5000	0301.3	222.1	16.62	
332.0	004.1000	0665.5	060.8	187.8	003.5000	0300.3	221.5	16.70	
333.0	004.1000	0662.4	060.7	187.5	003.5000	0299.3	221.0	16.77	

## Exhibit-20A

### FMOver Analysis Of Proposed Minor Mod KOOZ vs. KSLG-FM

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
334.0	004.1000	0659.0	060.5	187.3	003.5000	0298.3	220.5	16.83	
335.0	004.1000	0655.5	060.4	187.0	003.5000	0297.5	220.1	16.89	
336.0	004.1000	0652.0	060.3	186.8	003.5000	0296.8	219.6	16.96	
337.0	004.1000	0648.7	060.2	186.5	003.5000	0296.1	219.2	17.02	
338.0	004.1000	0646.0	060.1	186.2	003.5000	0295.4	218.8	17.07	
339.0	004.1000	0644.0	060.0	186.0	003.5000	0295.3	218.4	17.14	
340.0	004.1000	0643.5	060.0	185.7	003.5000	0296.0	217.9	17.23	
341.0	004.1000	0644.6	060.0	185.5	003.5000	0297.3	217.4	17.33	
342.0	004.1000	0647.0	060.1	185.2	003.5000	0298.7	216.9	17.44	
343.0	004.1000	0650.2	060.2	185.0	003.5000	0299.9	216.4	17.55	
344.0	004.1000	0653.7	060.4	184.7	003.5000	0300.9	215.9	17.65	
345.0	004.1000	0656.7	060.5	184.5	003.5000	0301.5	215.5	17.73	
346.0	004.1000	0658.5	060.5	184.2	003.5000	0302.1	215.1	17.81	
347.0	004.1000	0659.5	060.6	184.0	003.5000	0302.7	214.7	17.88	
348.0	004.1000	0660.0	060.6	183.7	003.5000	0302.8	214.4	17.93	
349.0	004.1000	0659.9	060.6	183.4	003.5000	0302.7	214.1	17.98	
350.0	004.1000	0659.3	060.6	183.1	003.5000	0301.1	213.9	17.99	
351.0	004.1000	0657.8	060.5	182.8	003.5000	0297.1	213.7	17.95	
352.0	004.1000	0655.4	060.4	182.6	003.5000	0292.9	213.6	17.89	
353.0	004.1000	0652.8	060.3	182.3	003.5000	0288.6	213.5	17.83	
354.0	004.1000	0650.0	060.2	182.0	003.5000	0284.2	213.5	17.77	
355.0	004.1000	0646.6	060.1	181.7	003.5000	0279.8	213.4	17.69	
356.0	004.1000	0644.4	060.0	181.4	003.5000	0275.6	213.4	17.63	
357.0	004.1000	0643.3	060.0	181.1	003.5000	0271.6	213.4	17.56	
358.0	004.1000	0642.1	060.0	180.8	003.5000	0267.4	213.3	17.49	
359.0	004.1000	0640.9	059.9	180.6	003.5000	0264.5	213.3	17.44	
000.0	004.1000	0639.6	059.9	180.3	003.5000	0262.3	213.4	17.40	
001.0	004.1000	0638.3	059.8	180.0	003.5000	0260.1	213.4	17.35	
002.0	004.1000	0638.2	059.8	179.7	003.5000	0257.9	213.5	17.31	
003.0	004.1000	0639.2	059.8	179.4	003.5000	0255.7	213.5	17.27	
004.0	004.1000	0640.2	059.9	179.1	003.5000	0253.4	213.5	17.22	
005.0	004.1000	0641.5	059.9	178.9	003.5000	0251.2	213.6	17.17	
006.0	004.1000	0642.6	060.0	178.6	003.5000	0248.9	213.7	17.12	
007.0	004.1000	0642.2	060.0	178.3	003.5000	0246.7	213.8	17.05	
008.0	004.1000	0641.1	059.9	178.0	003.5000	0244.7	214.0	16.98	
009.0	004.1000	0640.2	059.9	177.7	003.5000	0244.1	214.2	16.93	
010.0	004.1000	0639.5	059.9	177.5	003.5000	0244.1	214.5	16.90	
011.0	004.1000	0639.0	059.8	177.2	003.5000	0244.4	214.7	16.86	
012.0	004.1000	0639.1	059.8	176.9	003.5000	0245.4	215.0	16.84	
013.0	004.1000	0640.1	059.9	176.6	003.5000	0247.2	215.2	16.83	
014.0	004.1000	0641.7	059.9	176.4	003.5000	0249.2	215.5	16.83	
015.0	004.1000	0643.2	060.0	176.1	003.5000	0251.3	215.8	16.82	
016.0	004.1000	0644.6	060.0	175.8	003.5000	0253.5	216.1	16.81	
017.0	004.1000	0645.7	060.1	175.6	003.5000	0255.6	216.4	16.80	
018.0	004.1000	0646.3	060.1	175.3	003.5000	0257.4	216.8	16.77	
019.0	004.1000	0646.1	060.1	175.0	003.5000	0259.2	217.2	16.73	
020.0	004.1000	0645.5	060.1	174.8	003.5000	0260.7	217.7	16.69	
021.0	004.1000	0644.4	060.0	174.5	003.5000	0261.8	218.1	16.63	
022.0	004.1000	0642.6	060.0	174.3	003.5000	0262.5	218.7	16.55	
023.0	004.1000	0640.6	059.9	174.1	003.5000	0262.8	219.2	16.47	
024.0	004.1000	0638.9	059.8	173.8	003.5000	0262.8	219.8	16.38	
025.0	004.1000	0637.7	059.8	173.6	003.5000	0262.6	220.4	16.28	
026.0	004.1000	0636.9	059.8	173.4	003.5000	0262.3	221.0	16.18	
027.0	004.1000	0636.3	059.7	173.1	003.5000	0261.9	221.5	16.08	
028.0	004.1000	0635.3	059.7	172.9	003.5000	0261.4	222.2	15.97	
029.0	004.1000	0633.3	059.6	172.7	003.5000	0260.7	222.8	15.85	
030.0	004.1000	0630.8	059.6	172.5	003.5000	0260.0	223.5	15.72	
031.0	004.1000	0627.7	059.4	172.3	003.5000	0259.4	224.2	15.59	
032.0	004.1000	0625.0	059.3	172.1	003.5000	0259.0	225.0	15.46	
033.0	004.1000	0622.6	059.3	171.9	003.5000	0258.7	225.7	15.33	
034.0	004.1000	0621.6	059.2	171.7	003.5000	0258.6	226.4	15.20	
035.0	004.1000	0622.3	059.2	171.5	003.5000	0258.7	227.1	15.09	
036.0	004.1000	0624.4	059.3	171.3	003.5000	0259.0	227.8	14.98	
037.0	004.1000	0627.7	059.4	171.1	003.5000	0259.6	228.4	14.87	
038.0	004.1000	0630.6	059.5	170.9	003.5000	0260.5	229.1	14.77	
039.0	004.1000	0634.0	059.7	170.7	003.5000	0261.6	229.8	14.67	

## Exhibit-20A

### FMOver Analysis Of Proposed Minor Mod KOOZ vs. KSLG-FM

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
040.0	004.1000	0637.0	059.8	170.5	003.5000	0262.9	230.5	14.57	
041.0	004.1000	0639.3	059.9	170.3	003.5000	0264.4	231.2	14.47	
042.0	004.1000	0640.9	059.9	170.2	003.5000	0265.9	232.0	14.36	
043.0	004.1000	0641.1	059.9	170.0	003.5000	0267.4	232.8	14.25	
044.0	004.1000	0640.5	059.9	169.9	003.5000	0268.8	233.7	14.13	
045.0	004.1000	0637.9	059.8	169.7	003.5000	0270.1	234.6	13.99	
046.0	004.1000	0634.7	059.7	169.6	003.5000	0271.3	235.5	13.86	
047.0	004.1000	0631.6	059.6	169.5	003.5000	0272.6	236.5	13.72	
048.0	004.1000	0628.1	059.5	169.4	003.5000	0273.8	237.4	13.58	
049.0	004.1000	0625.2	059.4	169.3	003.5000	0275.1	238.3	13.44	
050.0	004.1000	0621.6	059.2	169.2	003.5000	0276.2	239.3	13.30	
051.0	004.1000	0617.4	059.1	169.1	003.5000	0277.2	240.3	13.15	
052.0	004.1000	0612.4	058.9	169.0	003.5000	0278.1	241.3	13.00	
053.0	004.1000	0606.2	058.7	168.9	003.5000	0278.8	242.3	12.84	
054.0	004.1000	0599.7	058.4	168.9	003.5000	0279.4	243.3	12.67	
055.0	004.1000	0593.8	058.2	168.8	003.5000	0279.9	244.3	12.51	
056.0	004.1000	0588.6	058.0	168.8	003.5000	0280.5	245.4	12.35	
057.0	004.1000	0584.4	057.8	168.7	003.5000	0281.0	246.4	12.19	
058.0	004.1000	0581.4	057.7	168.7	003.5000	0281.6	247.3	12.03	
059.0	004.1000	0579.5	057.6	168.6	003.5000	0282.3	248.3	11.87	