

Sterling, CO Minor Modification of CP

REFERENCE  
40 31 57.0 N.  
103 07 22.0 W.

CH# 201D - 88.1 MHz, Pwr= 0.075 kW, HAAT= 70.5 M, COR= 1376 M  
Average Protected F(50-50)= 8.01 km  
Omni-directional

DISPLAY DATES  
DATA 01-24-19  
SEARCH 01-28-19

CH CITY	CALL	TYPE STATE	ANT	AZI <--	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
201D Sterling	K201IP	CP _C_ CO		0.0 0.0	0.00 BMPFT20180813AAR	40 31 57.0 103 07 22.0	0.075		---Reference--- Calvary Chapel of Twin Fal		
201D Sterling	K201IP	LIC _V_ CO		85.8 265.8	6.35 BLFT20121105AKX	40 32 12.0 103 02 52.0	0.075 120		---Reference--- Calvary Chapel of Twin Fal		
202D Yuma	K202EK	LIC _C_ CO		148.8 329.0	50.58 BLFT20130603BED	40 08 35.0 102 48 51.0	0.113 117	15.2 1398	10.7 Community Radio For Northe	30.2	32.2

Terrain database is USGS 03 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM  
In & Out distances between contours are shown at closest points. Reference zone= West Zone, Co to 3rd adjacent.  
All separation margins (if shown) include rounding.  
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, \_= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)  
"\*"affixed to 'IN' or 'OUT' values = site inside restricted contour.