



Exhibit # 12A

Section 74.1204 Compliance with WXLO (FM)

Channel 282 -- 0.069 kW ERP -- 137 m AMSL

Concord, New Hampshire

Bromo Communications, Inc.

Atlanta, Georgia

September 2008

Exhibit # 12B
FMOver Showing with WXLO Fitchburg, MA
Channel 282 – 0.069 kW ERP – 137 m AMSL
Concord, New Hampshire

WXLO
Channel = 283B
Max ERP = 37 kW
RCAMSL = 404 M
N. Lat = 423027.0
W. Lng = 714937.0

W282AF BLFT19970421TE
Channel = 282D
Max ERP = 0.069 kW
RCAMSL = 137.1 M
N. Lat = 43 11 39
W. Lng = 71 33 17

Protected
54 dBu

Interfering
48 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
346.0	037.0000	0145.9	061.6	246.0	000.0690	-0008.0	040.5	26.8
347.0	037.0000	0140.9	060.8	244.7	000.0690	-0007.7	039.7	27.0
348.0	037.0000	0137.3	060.3	243.6	000.0690	-0006.8	038.8	27.3
349.0	037.0000	0136.0	060.2	242.9	000.0690	-0005.6	037.8	27.6
350.0	037.0000	0135.0	060.0	242.2	000.0690	-0003.9	036.8	28.0
351.0	037.0000	0134.0	059.9	241.5	000.0690	-0001.9	035.9	28.3
352.0	037.0000	0133.6	059.8	240.8	000.0690	-0001.9	034.9	28.6
353.0	037.0000	0134.0	059.9	240.2	000.0690	-0000.1	033.9	29.0
354.0	037.0000	0133.5	059.8	239.4	000.0690	0001.0	033.0	29.4
355.0	037.0000	0135.3	060.1	239.0	000.0690	0001.0	032.0	29.8
356.0	037.0000	0138.2	060.5	238.8	000.0690	0001.0	030.8	30.2
357.0	037.0000	0141.2	060.9	238.6	000.0690	0001.0	029.7	30.8
358.0	037.0000	0146.6	061.7	238.9	000.0690	0001.0	028.4	31.5
359.0	037.0000	0151.7	062.3	239.0	000.0690	0001.0	027.1	32.2
000.0	037.0000	0156.8	063.0	239.0	000.0690	0001.0	025.8	33.0
001.0	037.0000	0161.4	063.6	238.8	000.0690	0001.0	024.6	33.8
002.0	037.0000	0163.0	063.7	237.7	000.0690	0001.5	023.6	34.5
003.0	037.0000	0164.1	063.9	236.4	000.0690	0003.7	022.6	35.3
004.0	037.0000	0166.4	064.2	235.2	000.0690	0005.5	021.5	36.1
005.0	037.0000	0170.4	064.6	234.1	000.0690	0006.9	020.4	36.9
006.0	037.0000	0175.5	065.1	233.1	000.0690	0007.7	019.2	37.9
007.0	037.0000	0180.5	065.7	231.8	000.0690	0007.6	018.0	38.9
008.0	037.0000	0184.7	066.1	230.0	000.0690	0007.9	016.9	39.8
009.0	037.0000	0189.5	066.5	227.9	000.0690	0011.0	015.8	40.7
010.0	037.0000	0192.9	066.9	225.2	000.0690	0010.2	014.8	41.6
011.0	037.0000	0193.2	066.9	221.4	000.0690	-0004.2	014.2	42.4
012.0	037.0000	0191.5	066.7	216.8	000.0690	-0017.9	013.8	42.9
013.0	037.0000	0190.5	066.6	212.2	000.0690	-0029.1	013.4	43.3
014.0	037.0000	0193.3	066.9	207.6	000.0690	-0037.2	012.8	44.2
015.0	037.0000	0199.3	067.5	202.8	000.0690	-0034.5	012.0	45.3
016.0	037.0000	0207.1	068.2	197.3	000.0690	-0033.7	011.2	46.6
017.0	037.0000	0213.6	068.8	190.9	000.0690	-0039.6	010.6	47.6
018.0	037.0000	0216.9	069.1	184.2	000.0690	-0041.4	010.5	47.7
019.0	037.0000	0217.1	069.2	178.0	000.0690	-0040.7	010.9	47.1
020.0	037.0000	0216.5	069.1	172.5	000.0690	-0048.6	011.4	46.3
021.0	037.0000	0216.9	069.1	167.4	000.0690	-0043.0	012.0	45.3

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
022.0	037.0000	0218.7	069.3	162.4	000.0690	-0026.3	012.6	44.5
023.0	037.0000	0221.2	069.5	157.8	000.0690	-0006.0	013.3	43.6
024.0	037.0000	0223.9	069.8	153.6	000.0690	0015.4	014.0	42.6
025.0	037.0000	0226.8	070.0	149.8	000.0690	0020.0	014.8	41.6
026.0	037.0000	0229.4	070.3	146.6	000.0690	0022.7	015.7	40.8
027.0	037.0000	0231.6	070.5	143.9	000.0690	0026.2	016.7	40.0
028.0	037.0000	0233.8	070.7	141.6	000.0690	0030.4	017.7	39.2
029.0	037.0000	0236.2	070.9	139.5	000.0690	0034.3	018.8	39.3
030.0	037.0000	0238.2	071.0	137.9	000.0690	0036.4	019.9	38.9
031.0	037.0000	0239.5	071.2	136.6	000.0690	0036.8	021.1	38.1
032.0	037.0000	0240.1	071.2	135.6	000.0690	0037.3	022.3	37.2
033.0	037.0000	0240.2	071.2	134.9	000.0690	0037.9	023.5	36.5
034.0	037.0000	0240.4	071.2	134.3	000.0690	0038.4	024.7	35.7
035.0	037.0000	0240.9	071.3	133.7	000.0690	0038.4	025.9	34.9
036.0	037.0000	0241.9	071.4	133.2	000.0690	0039.3	027.1	34.3
037.0	037.0000	0243.2	071.5	132.7	000.0690	0039.3	028.4	33.6
038.0	037.0000	0244.4	071.6	132.2	000.0690	0040.7	029.6	33.2
039.0	037.0000	0245.4	071.7	131.9	000.0690	0040.7	030.8	32.6
040.0	037.0000	0246.2	071.7	131.7	000.0690	0040.7	032.1	32.0
041.0	037.0000	0246.9	071.8	131.6	000.0690	0040.7	033.3	31.5
042.0	037.0000	0247.7	071.9	131.4	000.0690	0042.0	034.6	31.3
043.0	037.0000	0248.7	071.9	131.3	000.0690	0042.0	035.8	30.8
044.0	037.0000	0250.0	072.0	131.2	000.0690	0042.0	037.1	30.3
045.0	037.0000	0251.8	072.2	131.1	000.0690	0042.0	038.4	29.9
046.0	037.0000	0254.2	072.4	131.0	000.0690	0042.0	039.6	29.4

At no point in the protected 54 dBu (50, 50) contour of WXLO (FM), does the proposed translator exceed the allowable interfering contour of 48 dBu (50, 10).