

Exhibit 15-L-3

WKHB	620 kHz	Lic	ND2U	BL010416BD	20060522
PA	IRWIN			5.500 kW 1 Tower	0 Augmentations
N. Lat:	40 17 20	W. Lon:	79 42 04		19 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.
All distances are in kilometers (US metric curves)
All radiations are in mV/m at one kilometer

'M*' bearing is supplemented by measurements.
'+-' 10 deg. variance from measured bearing.

Bearing	Radiation	Distance to Contours	
		0.500	0.250
0.0M*	706.9	62.82	87.42
5.0+	706.9	62.82	87.42
10.0-	706.9	75.46	104.57
15.0M*	706.9	75.46	104.57
20.0+	706.9	75.46	104.57
25.0+	706.9	75.46	104.57
30.0-	706.9	99.40	131.74
35.0M*	706.9	99.40	131.74
40.0+	706.9	99.40	131.74
45.0+	706.9	99.40	131.74
50.0-	706.9	75.46	101.82
55.0M*	706.9	75.46	101.82
60.0+	706.9	75.46	101.82
65.0+	706.9	75.46	101.82
70.0-	706.9	75.46	101.82
75.0M*	706.9	75.46	101.82
80.0+	706.9	75.46	101.82
85.0+	706.9	75.46	101.82
90.0-	706.9	75.46	101.82
95.0M*	706.9	75.46	101.82
100.0+	706.9	75.46	101.82
105.0+	706.9	75.46	101.82
110.0-	706.9	75.46	101.82
115.0M*	706.9	75.46	101.82
120.0+	706.9	75.46	101.82
125.0+	706.9	75.46	101.82
130.0-	706.9	75.46	104.17
135.0M*	706.9	75.46	104.17
140.0+	706.9	75.46	104.17
145.0+	706.9	75.46	104.17
150.0-	706.9	62.82	85.67
155.0M*	706.9	62.82	85.67
160.0+	706.9	62.82	85.67
165.0+	706.9	62.82	85.67
170.0-	706.9	75.46	101.82
175.0M*	706.9	75.46	101.82

Exhibit 15-L-3 (cont.)
 Tabulation of Distance to WKHB Daytime Allocation Contours

WKHB	620 kHz	Lic	ND2U	BL010416BD	20060522
PA IRWIN				5.500 kW 1 Tower	0 Augmentations
N. Lat: 40 17 20	W. Lon: 79 42 04				19 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
-----	-----	-----	-----
180.0+	706.9	75.46	101.82
185.0+	706.9	75.46	101.82
190.0-	706.9	87.05	116.42
195.0M*	706.9	87.05	116.42
200.0+	706.9	87.05	116.42
205.0+	706.9	87.05	116.42
210.0-	706.9	75.46	101.82
215.0M*	706.9	75.46	101.82
220.0+	706.9	75.46	101.82
225.0+	706.9	75.46	101.82
230.0-	706.9	62.82	85.67
235.0M*	706.9	62.82	85.67
240.0+	706.9	62.82	85.67
245.0+	706.9	62.82	85.67
250.0-	706.9	78.00	101.82
255.0M*	706.9	78.00	101.82
260.0+	706.9	78.00	101.82
265.0+	706.9	78.00	101.82
270.0-	706.9	80.00	101.82
275.0M*	706.9	80.00	101.82
280.0+	706.9	80.00	101.82
285.0+	706.9	80.00	101.82
290.0-	706.9	75.46	101.82
295.0M*	706.9	75.46	101.82
300.0+	706.9	75.46	101.82
305.0-	706.9	77.00	101.82
310.0M*	706.9	77.00	101.82
315.0+	706.9	77.00	101.82
317.5+	706.9	77.00	101.82
320.0-	706.9	87.05	116.42
325.0-	706.9	87.05	116.42
327.5M*	706.9	87.05	116.42
330.0+	706.9	87.05	116.42
335.0+	706.9	87.05	116.42
337.5+	706.9	87.05	116.42
340.0-	706.9	89.37	141.38
345.0-	706.9	89.37	138.22
347.5M*	706.9	89.37	131.71
350.0+	706.9	89.22	123.32
355.0-	706.9	62.82	87.44
357.5-	706.9	62.82	87.42