

EXHIBIT 31 DISTANCE TO CONTOUR AND HAAT DATA  
MAY 2010

Callsign : PROPOSED  
 Coordinates : 35-28-38.0 N, 117-41-58.0 W  
 Frequency (MHz): 98.50000  
 HAAT (m): 416.99 AMSL (m): 1375.00  
 Elevation (m): 1335.00 RC AGL (m): 40  
 ERP (w): 300  
 City/State : JOHANNESBURG, CA  
 Licensee : Mt. WILSON  
 Contour type : F(50,50)  
 Signal strength : 60.000 dBu

Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist
0	890	485	29.8	90	1024	351	25.4	180	932	443	28.4	270	1146	229	20.7
1	892	483	29.7	91	1043	332	24.7	181	913	462	29.0	271	1142	233	20.9
2	890	485	29.8	92	1060	315	24.1	182	904	471	29.3	272	1144	231	20.8
3	885	490	30.0	93	1074	301	23.6	183	899	476	29.5	273	1138	237	21.1
4	877	498	30.3	94	1083	292	23.2	184	889	486	29.8	274	1132	243	21.3
5	875	500	30.3	95	1087	288	23.1	185	880	495	30.1	275	1131	244	21.4
6	872	503	30.5	96	1082	293	23.3	186	874	501	30.4	276	1136	239	21.1
7	870	505	30.5	97	1080	295	23.4	187	865	510	30.7	277	1132	243	21.3
8	867	508	30.7	98	1080	295	23.4	188	858	517	31.0	278	1122	253	21.7
9	865	510	30.7	99	1083	292	23.2	189	851	524	31.3	279	1116	259	22.0
10	865	510	30.7	100	1080	295	23.4	190	843	532	31.6	280	1114	261	22.0
11	864	511	30.8	101	1080	295	23.4	191	835	540	31.9	281	1115	260	22.0
12	863	512	30.8	102	1089	286	23.0	192	828	547	32.2	282	1111	264	22.2
13	864	511	30.8	103	1095	280	22.8	193	823	552	32.3	283	1098	277	22.7
14	865	510	30.7	104	1088	287	23.1	194	815	560	32.6	284	1087	288	23.1
15	865	510	30.7	105	1089	286	23.0	195	811	564	32.8	285	1074	301	23.6
16	866	509	30.7	106	1092	283	22.9	196	807	568	32.9	286	1065	310	23.9
17	867	508	30.7	107	1094	281	22.8	197	802	573	33.0	287	1066	309	23.9
18	870	505	30.5	108	1091	284	22.9	198	798	577	33.2	288	1066	309	23.9
19	874	501	30.4	109	1082	293	23.3	199	795	580	33.3	289	1061	314	24.1
20	877	498	30.3	110	1075	300	23.6	200	791	584	33.4	290	1057	318	24.2
21	882	493	30.1	111	1067	308	23.9	201	788	587	33.5	291	1047	328	24.6
22	888	487	29.9	112	1069	306	23.8	202	786	589	33.5	292	1036	339	25.0
23	893	482	29.7	113	1068	307	23.8	203	784	591	33.6	293	1030	345	25.2
24	896	479	29.6	114	1065	310	23.9	204	781	594	33.7	294	1027	348	25.3
25	904	471	29.3	115	1062	313	24.0	205	779	596	33.8	295	1022	353	25.5
26	911	464	29.1	116	1061	314	24.1	206	777	598	33.8	296	1014	361	25.8
27	916	459	28.9	117	1056	319	24.3	207	775	600	33.9	297	1009	366	25.9
28	922	453	28.7	118	1050	325	24.5	208	774	601	33.9	298	1004	371	26.1
29	927	448	28.5	119	1053	322	24.4	209	774	601	33.9	299	998	377	26.3
30	931	444	28.4	120	1051	324	24.4	210	773	602	33.9	300	993	382	26.4
31	936	439	28.2	121	1046	329	24.6	211	772	603	34.0	301	987	388	26.6
32	938	437	28.2	122	1039	336	24.9	212	771	604	34.0	302	983	392	26.8
33	944	431	28.0	123	1030	345	25.2	213	770	605	34.0	303	973	402	27.1
34	950	425	27.8	124	1024	351	25.4	214	769	606	34.0	304	960	415	27.5
35	955	420	27.6	125	1012	363	25.8	215	768	607	34.1	305	947	428	27.9
36	963	412	27.4	126	1002	373	26.2	216	768	607	34.1	306	937	438	28.2
37	971	404	27.1	127	994	381	26.4	217	769	606	34.0	307	931	444	28.4
38	977	398	26.9	128	991	384	26.5	218	772	603	34.0	308	925	450	28.6
39	985	390	26.7	129	985	390	26.7	219	773	602	33.9	309	918	457	28.8
40	992	383	26.5	130	980	395	26.9	220	773	602	33.9	310	911	464	29.1
41	999	376	26.3	131	974	401	27.0	221	776	599	33.8	311	902	473	29.4
42	1004	371	26.1	132	974	401	27.0	222	778	597	33.8	312	895	480	29.6
43	1008	367	26.0	133	980	395	26.9	223	780	595	33.7	313	889	486	29.8
44	1010	365	25.9	134	984	391	26.7	224	782	593	33.7	314	883	492	30.0
45	1013	362	25.8	135	991	384	26.5	225	788	587	33.5	315	879	496	30.2
46	1016	359	25.7	136	999	376	26.3	226	796	579	33.2	316	876	499	30.3
47	1018	357	25.6	137	1006	369	26.0	227	806	569	32.9	317	875	500	30.3
48	1019	356	25.6	138	1016	359	25.7	228	814	561	32.7	318	876	499	30.3
49	1019	356	25.6	139	1025	350	25.4	229	822	553	32.4	319	876	499	30.3
50	1017	358	25.7	140	1029	346	25.2	230	834	541	31.9	320	879	496	30.2
51	1014	361	25.8	141	1029	346	25.2	231	852	523	31.2	321	878	497	30.2
52	1009	366	25.9	142	1024	351	25.4	232	872	503	30.5	322	874	501	30.4
53	1002	373	26.2	143	1017	358	25.7	233	898	477	29.5	323	866	509	30.7
54	995	380	26.4	144	1013	362	25.8	234	921	454	28.7	324	857	518	31.0
55	988	387	26.6	145	1007	368	26.0	235	944	431	28.0	325	850	525	31.3
56	980	395	26.9	146	1003	372	26.1	236	969	406	27.2	326	848	527	31.4
57	971	404	27.1	147	1003	372	26.1	237	996	379	26.4	327	847	528	31.4
58	965	410	27.3	148	1004	371	26.1	238	1024	351	25.4	328	845	530	31.5
59	955	420	27.6	149	1001	374	26.2	239	1050	325	24.5	329	845	530	31.5
60	948	427	27.8	150	1001	374	26.2	240	1074	301	23.6	330	844	531	31.6
61	940	435	28.1	151	1000	375	26.2	241	1102	273	22.5	331	843	532	31.6
62	933	442	28.3	152	1002	373	26.2	242	1127	248	21.5	332	844	531	31.6

EXHIBIT 31 PAGE 2 DISTANCE TO CONTOUR AND HAAT DATA  
MAY 2010

Callsign : PROPOSED  
Coordinates : 35-28-38.0 N, 117-41-58.0 W  
Frequency (MHz): 98.50000  
HAAT (m): 416.99 AMSL (m): 1375.00  
Elevation (m): 1335.00 RC AGL (m): 40  
ERP (w): 300  
City/State : JOHANNESBURG, CA  
Licensee : Mt. WILSON  
Contour type : F(50,50)  
Signal strength : 60.000 dBu

Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist
63	926	449	28.6	153	1001	374	26.2	243	1145	230	20.8	333	843	532	31.6
64	920	455	28.8	154	999	376	26.3	244	1157	218	20.2	334	844	531	31.6
65	914	461	28.9	155	1000	375	26.2	245	1163	212	19.9	335	844	531	31.6
66	910	465	29.1	156	1004	371	26.1	246	1166	209	19.8	336	844	531	31.6
67	908	467	29.2	157	1007	368	26.0	247	1159	216	20.1	337	846	529	31.5
68	904	471	29.3	158	1003	372	26.1	248	1149	226	20.6	338	849	526	31.4
69	902	473	29.4	159	1000	375	26.2	249	1139	236	21.0	339	851	524	31.3
70	899	476	29.5	160	999	376	26.3	250	1125	250	21.6	340	851	524	31.3
71	897	478	29.5	161	1001	374	26.2	251	1115	260	22.0	341	853	522	31.2
72	899	476	29.5	162	1003	372	26.1	252	1106	269	22.4	342	855	520	31.1
73	901	474	29.4	163	1003	372	26.1	253	1098	277	22.7	343	856	519	31.1
74	904	471	29.3	164	1007	368	26.0	254	1089	286	23.0	344	859	516	31.0
75	906	469	29.2	165	1011	364	25.9	255	1085	290	23.2	345	861	514	30.9
76	910	465	29.1	166	1015	360	25.7	256	1078	297	23.4	346	862	513	30.9
77	913	462	29.0	167	1013	362	25.8	257	1076	299	23.5	347	863	512	30.8
78	916	459	28.9	168	1013	362	25.8	258	1077	298	23.5	348	865	510	30.7
79	918	457	28.8	169	1006	369	26.0	259	1078	297	23.4	349	867	508	30.7
80	922	453	28.7	170	1006	369	26.0	260	1075	300	23.6	350	869	506	30.6
81	928	447	28.5	171	1005	370	26.1	261	1072	303	23.7	351	870	505	30.5
82	935	440	28.3	172	1006	369	26.0	262	1081	294	23.3	352	872	503	30.5
83	942	433	28.0	173	1000	375	26.2	263	1089	286	23.0	353	873	502	30.4
84	950	425	27.8	174	990	385	26.5	264	1104	271	22.4	354	876	499	30.3
85	958	417	27.5	175	978	397	26.9	265	1122	253	21.7	355	879	496	30.2
86	968	407	27.2	176	971	404	27.1	266	1130	245	21.4	356	881	494	30.1
87	981	394	26.8	177	961	414	27.4	267	1145	230	20.8	357	885	490	30.0
88	994	381	26.4	178	957	418	27.6	268	1158	217	20.2	358	888	487	29.9
89	1011	364	25.9	179	947	428	27.9	269	1157	218	20.2	359	890	485	29.8

EXHIBIT 31 PAGE 3 DISTANCE TO CONTOUR AND HAAT DATA  
MAY 2010

Callsign : PROPOSED  
Coordinates : 35-28-38.0 N, 117-41-58.0 W  
Frequency (MHz): 98.50000  
HAAT (m): 416.99 AMSL (m): 1375.00  
Elevation (m): 1335.00 RC AGL (m): 40  
ERP (w): 300  
City/State : JOHANNESBURG, CA  
Licensee : Mt. WILSON  
Contour type : F(50,10)  
Signal strength : 37.000 dBu

Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist
0	890	485	97.1	90	1024	351	84.0	180	932	443	93.1	270	1146	229	72.1
1	892	483	96.9	91	1043	332	82.2	181	913	462	95.0	271	1142	233	72.6
2	890	485	97.1	92	1060	315	80.5	182	904	471	95.8	272	1144	231	72.4
3	885	490	97.5	93	1074	301	79.1	183	899	476	96.3	273	1138	237	73.0
4	877	498	98.2	94	1083	292	78.3	184	889	486	97.2	274	1132	243	73.6
5	875	500	98.4	95	1087	288	77.9	185	880	495	98.0	275	1131	244	73.7
6	872	503	98.6	96	1082	293	78.4	186	874	501	98.5	276	1136	239	73.2
7	870	505	98.8	97	1080	295	78.5	187	865	510	99.2	277	1132	243	73.6
8	867	508	99.1	98	1080	295	78.5	188	858	517	99.8	278	1122	253	74.6
9	865	510	99.2	99	1083	292	78.3	189	851	524	100.4	279	1116	259	75.2
10	865	510	99.2	100	1080	295	78.5	190	843	532	101.1	280	1114	261	75.4
11	864	511	99.3	101	1080	295	78.5	191	835	540	101.8	281	1115	260	75.3
12	863	512	99.4	102	1089	286	77.7	192	828	547	102.4	282	1111	264	75.6
13	864	511	99.3	103	1095	280	77.2	193	823	552	102.8	283	1098	277	76.9
14	865	510	99.2	104	1088	287	77.8	194	815	560	103.5	284	1087	288	77.9
15	865	510	99.2	105	1089	286	77.7	195	811	564	103.8	285	1074	301	79.1
16	866	509	99.1	106	1092	283	77.4	196	807	568	104.1	286	1065	310	80.0
17	867	508	99.1	107	1094	281	77.2	197	802	573	104.5	287	1066	309	79.9
18	870	505	98.8	108	1091	284	77.5	198	798	577	104.8	288	1066	309	79.9
19	874	501	98.5	109	1082	293	78.4	199	795	580	105.0	289	1061	314	80.4
20	877	498	98.2	110	1075	300	79.0	200	791	584	105.3	290	1057	318	80.8
21	882	493	97.8	111	1067	308	79.8	201	788	587	105.5	291	1047	328	81.8
22	888	487	97.3	112	1069	306	79.6	202	786	589	105.6	292	1036	339	82.9
23	893	482	96.8	113	1068	307	79.7	203	784	591	105.8	293	1030	345	83.5
24	896	479	96.6	114	1065	310	80.0	204	781	594	106.0	294	1027	348	83.7
25	904	471	95.8	115	1062	313	80.3	205	779	596	106.1	295	1022	353	84.2
26	911	464	95.2	116	1061	314	80.4	206	777	598	106.2	296	1014	361	85.0
27	916	459	94.7	117	1056	319	80.9	207	775	600	106.3	297	1009	366	85.5
28	922	453	94.1	118	1050	325	81.5	208	774	601	106.4	298	1004	371	85.9
29	927	448	93.6	119	1053	322	81.2	209	774	601	106.4	299	998	377	86.5
30	931	444	93.2	120	1051	324	81.4	210	773	602	106.5	300	993	382	87.0
31	936	439	92.7	121	1046	329	81.9	211	772	603	106.5	301	987	388	87.6
32	938	437	92.5	122	1039	336	82.6	212	771	604	106.6	302	983	392	88.0
33	944	431	91.9	123	1030	345	83.5	213	770	605	106.6	303	973	402	88.9
34	950	425	91.3	124	1024	351	84.0	214	769	606	106.7	304	960	415	90.2
35	955	420	90.7	125	1012	363	85.2	215	768	607	106.8	305	947	428	91.6
36	963	412	89.9	126	1002	373	86.1	216	768	607	106.8	306	937	438	92.6
37	971	404	89.1	127	994	381	86.9	217	769	606	106.7	307	931	444	93.2
38	977	398	88.5	128	991	384	87.2	218	772	603	106.5	308	925	450	93.8
39	985	390	87.8	129	985	390	87.8	219	773	602	106.5	309	918	457	94.5
40	992	383	87.1	130	980	395	88.3	220	773	602	106.5	310	911	464	95.2
41	999	376	86.4	131	974	401	88.8	221	776	599	106.3	311	902	473	96.0
42	1004	371	85.9	132	974	401	88.8	222	778	597	106.2	312	895	480	96.7
43	1008	367	85.6	133	980	395	88.3	223	780	595	106.0	313	889	486	97.2
44	1010	365	85.4	134	984	391	87.9	224	782	593	105.9	314	883	492	97.7
45	1013	362	85.1	135	991	384	87.2	225	788	587	105.5	315	879	496	98.0
46	1016	359	84.8	136	999	376	86.4	226	796	579	105.0	316	876	499	98.3
47	1018	357	84.6	137	1006	369	85.8	227	806	569	104.2	317	875	500	98.4
48	1019	356	84.5	138	1016	359	84.8	228	814	561	103.6	318	876	499	98.3
49	1019	356	84.5	139	1025	350	83.9	229	822	553	102.9	319	876	499	98.3
50	1017	358	84.7	140	1029	346	83.5	230	834	541	101.9	320	879	496	98.0
51	1014	361	85.0	141	1029	346	83.5	231	852	523	100.3	321	878	497	98.1
52	1009	366	85.5	142	1024	351	84.0	232	872	503	98.6	322	874	501	98.5
53	1002	373	86.1	143	1017	358	84.7	233	898	477	96.4	323	866	509	99.1
54	995	380	86.8	144	1013	362	85.1	234	921	454	94.2	324	857	518	99.9
55	988	387	87.5	145	1007	368	85.7	235	944	431	91.9	325	850	525	100.5
56	980	395	88.3	146	1003	372	86.0	236	969	406	89.3	326	848	527	100.7
57	971	404	89.1	147	1003	372	86.0	237	996	379	86.7	327	847	528	100.8
58	965	410	89.7	148	1004	371	85.9	238	1024	351	84.0	328	845	530	100.9
59	955	420	90.7	149	1001	374	86.2	239	1050	325	81.5	329	845	530	100.9
60	948	427	91.5	150	1001	374	86.2	240	1074	301	79.1	330	844	531	101.0
61	940	435	92.3	151	1000	375	86.3	241	1102	273	76.5	331	843	532	101.1
62	933	442	93.0	152	1002	373	86.1	242	1127	248	74.1	332	844	531	101.0

EXHIBIT 31 PAGE 4 DISTANCE TO CONTOUR AND HAAT DATA  
MAY 2010

Callsign : PROPOSED  
Coordinates : 35-28-38.0 N, 117-41-58.0 W  
Frequency (MHz): 98.50000  
HAAT (m): 416.99 AMSL (m): 1375.00  
Elevation (m): 1335.00 RC AGL (m): 40  
ERP (w): 300  
City/State : JOHANNESBURG, CA  
Licensee : Mt. WILSON  
Contour type : F(50,10)  
Signal strength : 37.000 dBu

Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist
63	926	449	93.7	153	1001	374	86.2	243	1145	230	72.2	333	843	532	101.1
64	920	455	94.3	154	999	376	86.4	244	1157	218	70.9	334	844	531	101.0
65	914	461	94.9	155	1000	375	86.3	245	1163	212	70.2	335	844	531	101.0
66	910	465	95.3	156	1004	371	85.9	246	1166	209	69.9	336	844	531	101.0
67	908	467	95.5	157	1007	368	85.7	247	1159	216	70.7	337	846	529	100.9
68	904	471	95.8	158	1003	372	86.0	248	1149	226	71.8	338	849	526	100.6
69	902	473	96.0	159	1000	375	86.3	249	1139	236	72.9	339	851	524	100.4
70	899	476	96.3	160	999	376	86.4	250	1125	250	74.3	340	851	524	100.4
71	897	478	96.5	161	1001	374	86.2	251	1115	260	75.3	341	853	522	100.2
72	899	476	96.3	162	1003	372	86.0	252	1106	269	76.1	342	855	520	100.1
73	901	474	96.1	163	1003	372	86.0	253	1098	277	76.9	343	856	519	100.0
74	904	471	95.8	164	1007	368	85.7	254	1089	286	77.7	344	859	516	99.7
75	906	469	95.7	165	1011	364	85.3	255	1085	290	78.1	345	861	514	99.6
76	910	465	95.3	166	1015	360	84.9	256	1078	297	78.7	346	862	513	99.5
77	913	462	95.0	167	1013	362	85.1	257	1076	299	78.9	347	863	512	99.4
78	916	459	94.7	168	1013	362	85.1	258	1077	298	78.8	348	865	510	99.2
79	918	457	94.5	169	1006	369	85.8	259	1078	297	78.7	349	867	508	99.1
80	922	453	94.1	170	1006	369	85.8	260	1075	300	79.0	350	869	506	98.9
81	928	447	93.5	171	1005	370	85.9	261	1072	303	79.3	351	870	505	98.8
82	935	440	92.8	172	1006	369	85.8	262	1081	294	78.5	352	872	503	98.6
83	942	433	92.1	173	1000	375	86.3	263	1089	286	77.7	353	873	502	98.6
84	950	425	91.3	174	990	385	87.3	264	1104	271	76.3	354	876	499	98.3
85	958	417	90.4	175	978	397	88.5	265	1122	253	74.6	355	879	496	98.0
86	968	407	89.4	176	971	404	89.1	266	1130	245	73.8	356	881	494	97.9
87	981	394	88.2	177	961	414	90.1	267	1145	230	72.2	357	885	490	97.5
88	994	381	86.9	178	957	418	90.5	268	1158	217	70.8	358	888	487	97.3
89	1011	364	85.3	179	947	428	91.6	269	1157	218	70.9	359	890	485	97.1

EXHIBIT 31 PAGE 5 DISTANCE TO CONTOUR AND HAAT DATA  
MAY 2010

Callsign : KDFO215  
Coordinates : 35-30-53.0 N, 119-03-41.0 W  
Frequency (MHz): 98.50000  
HAAT (m): 100. AMSL (m): 307.00  
ERP (w): 25000  
City/State : DELANO, CA  
Licensee : CC LICENSES, LLC  
Contour type : F(50,50)  
Signal strength : 57.000 dBu

Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist
0	244	63	37.2	90	309	-2	26.5	180	160	147	51.8	270	148	159	53.3
1	244	63	37.2	91	292	15	26.5	181	157	150	52.2	271	148	159	53.3
2	244	63	37.2	92	304	3	26.5	182	154	153	52.6	272	148	159	53.3
3	246	61	36.7	93	309	-2	26.5	183	154	153	52.6	273	148	159	53.3
4	248	59	36.2	94	310	-3	26.5	184	154	153	52.6	274	151	156	53.0
5	248	59	36.2	95	333	-26	26.5	185	154	153	52.6	275	151	156	53.0
6	249	58	35.9	96	341	-34	26.5	186	154	153	52.6	276	152	155	52.8
7	252	55	35.1	97	345	-38	26.5	187	154	153	52.6	277	153	154	52.7
8	256	51	33.8	98	351	-44	26.5	188	154	153	52.6	278	154	153	52.6
9	259	48	32.8	99	355	-48	26.5	189	153	154	52.7	279	154	153	52.6
10	258	49	33.2	100	360	-53	26.5	190	152	155	52.8	280	154	153	52.6
11	260	47	32.5	101	364	-57	26.5	191	151	156	53.0	281	156	151	52.3
12	260	47	32.5	102	366	-59	26.5	192	151	156	53.0	282	156	151	52.3
13	259	48	32.8	103	368	-61	26.5	193	150	157	53.1	283	156	151	52.3
14	264	43	31.0	104	366	-59	26.5	194	149	158	53.2	284	157	150	52.2
15	267	40	29.9	105	355	-48	26.5	195	149	158	53.2	285	157	150	52.2
16	268	39	29.6	106	347	-40	26.5	196	148	159	53.3	286	158	149	52.0
17	272	35	28.2	107	341	-34	26.5	197	147	160	53.4	287	158	149	52.0
18	273	34	27.8	108	333	-26	26.5	198	146	161	53.6	288	158	149	52.0
19	280	27	26.5	109	329	-22	26.5	199	146	161	53.6	289	158	149	52.0
20	282	25	26.5	110	325	-18	26.5	200	146	161	53.6	290	158	149	52.0
21	281	26	26.5	111	318	-11	26.5	201	144	163	53.8	291	159	148	51.9
22	279	28	26.5	112	310	-3	26.5	202	143	164	53.9	292	159	148	51.9
23	282	25	26.5	113	305	2	26.5	203	143	164	53.9	293	161	146	51.6
24	282	25	26.5	114	300	7	26.5	204	143	164	53.9	294	161	146	51.6
25	287	20	26.5	115	299	8	26.5	205	142	165	54.0	295	161	146	51.6
26	291	16	26.5	116	297	10	26.5	206	140	167	54.3	296	159	148	51.9
27	294	13	26.5	117	292	15	26.5	207	138	169	54.5	297	161	146	51.6
28	292	15	26.5	118	284	23	26.5	208	137	170	54.6	298	161	146	51.6
29	293	14	26.5	119	285	22	26.5	209	137	170	54.6	299	161	146	51.6
30	297	10	26.5	120	274	33	27.5	210	136	171	54.7	300	161	146	51.6
31	301	6	26.5	121	278	29	26.5	211	135	172	54.8	301	162	145	51.5
32	305	2	26.5	122	277	30	26.5	212	135	172	54.8	302	163	144	51.4
33	307	0	26.5	123	277	30	26.5	213	133	174	55.0	303	162	145	51.5
34	310	-3	26.5	124	272	35	28.2	214	133	174	55.0	304	163	144	51.4
35	311	-4	26.5	125	275	32	27.2	215	132	175	55.1	305	163	144	51.4
36	315	-8	26.5	126	270	37	28.9	216	131	176	55.2	306	163	144	51.4
37	319	-12	26.5	127	269	38	29.2	217	132	175	55.1	307	165	142	51.1
38	320	-13	26.5	128	270	37	28.9	218	132	175	55.1	308	165	142	51.1
39	320	-13	26.5	129	272	35	28.2	219	130	177	55.3	309	166	141	50.9
40	322	-15	26.5	130	260	47	32.5	220	130	177	55.3	310	167	140	50.8
41	326	-19	26.5	131	261	46	32.2	221	129	178	55.4	311	167	140	50.8
42	325	-18	26.5	132	267	40	29.9	222	129	178	55.4	312	169	138	50.5
43	326	-19	26.5	133	261	46	32.2	223	128	179	55.5	313	168	139	50.7
44	327	-20	26.5	134	258	49	33.2	224	127	180	55.6	314	168	139	50.7
45	327	-20	26.5	135	253	54	34.8	225	128	179	55.5	315	170	137	50.4
46	329	-22	26.5	136	248	59	36.2	226	128	179	55.5	316	172	135	50.1
47	329	-22	26.5	137	247	60	36.4	227	128	179	55.5	317	172	135	50.1
48	336	-29	26.5	138	242	65	37.7	228	128	179	55.5	318	171	136	50.2
49	333	-26	26.5	139	241	66	37.9	229	129	178	55.4	319	173	134	50.0
50	328	-21	26.5	140	236	71	39.0	230	129	178	55.4	320	174	133	49.8
51	327	-20	26.5	141	233	74	39.7	231	130	177	55.3	321	175	132	49.7
52	327	-20	26.5	142	236	71	39.0	232	129	178	55.4	322	177	130	49.4
53	330	-23	26.5	143	235	72	39.2	233	128	179	55.5	323	177	130	49.4
54	331	-24	26.5	144	222	85	42.0	234	129	178	55.4	324	179	128	49.1
55	328	-21	26.5	145	221	86	42.2	235	130	177	55.3	325	180	127	49.0
56	328	-21	26.5	146	224	83	41.6	236	129	178	55.4	326	181	126	48.8
57	328	-21	26.5	147	221	86	42.2	237	131	176	55.2	327	182	125	48.7
58	322	-15	26.5	148	215	92	43.3	238	131	176	55.2	328	184	123	48.4
59	318	-11	26.5	149	214	93	43.5	239	131	176	55.2	329	185	122	48.3
60	318	-11	26.5	150	213	94	43.7	240	131	176	55.2	330	190	117	47.6
61	320	-13	26.5	151	208	99	44.6	241	130	177	55.3	331	190	117	47.6
62	320	-13	26.5	152	210	97	44.2	242	131	176	55.2	332	194	113	46.9

EXHIBIT 31 PAGE 6 DISTANCE TO CONTOUR AND HAAT DATA  
MAY 2010

Callsign : KDFO215  
Coordinates : 35-30-53.0 N, 119-03-41.0 W  
Frequency (MHz): 98.50000  
HAAT (m): 100. AMSL (m): 307.00  
ERP (w): 25000  
City/State : DELANO, CA  
Licensee : CC LICENSES, LLC  
Contour type : F(50,50)  
Signal strength : 57.000 dBu

Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist
63	321	-14	26.5	153	202	105	45.6	243	131	176	55.2	333	196	111	46.6
64	321	-14	26.5	154	200	107	46.0	244	132	175	55.1	334	197	110	46.5
65	315	-8	26.5	155	198	109	46.3	245	132	175	55.1	335	197	110	46.5
66	313	-6	26.5	156	195	112	46.8	246	132	175	55.1	336	198	109	46.3
67	313	-6	26.5	157	192	115	47.3	247	133	174	55.0	337	198	109	46.3
68	314	-7	26.5	158	191	116	47.4	248	133	174	55.0	338	199	108	46.1
69	314	-7	26.5	159	189	118	47.7	249	134	173	54.9	339	200	107	46.0
70	316	-9	26.5	160	188	119	47.8	250	134	173	54.9	340	202	105	45.6
71	312	-5	26.5	161	186	121	48.1	251	134	173	54.9	341	203	104	45.4
72	312	-5	26.5	162	184	123	48.4	252	134	173	54.9	342	206	101	44.9
73	311	-4	26.5	163	184	123	48.4	253	136	171	54.7	343	207	100	44.7
74	311	-4	26.5	164	182	125	48.7	254	137	170	54.6	344	211	96	44.0
75	312	-5	26.5	165	178	129	49.3	255	138	169	54.5	345	213	94	43.7
76	310	-3	26.5	166	178	129	49.3	256	139	168	54.4	346	218	89	42.7
77	313	-6	26.5	167	176	131	49.5	257	139	168	54.4	347	222	85	42.0
78	311	-4	26.5	168	176	131	49.5	258	139	168	54.4	348	226	81	41.1
79	314	-7	26.5	169	174	133	49.8	259	140	167	54.3	349	228	79	40.7
80	321	-14	26.5	170	173	134	50.0	260	141	166	54.1	350	228	79	40.7
81	318	-11	26.5	171	171	136	50.2	261	141	166	54.1	351	228	79	40.7
82	316	-9	26.5	172	169	138	50.5	262	141	166	54.1	352	228	79	40.7
83	320	-13	26.5	173	168	139	50.7	263	141	166	54.1	353	229	78	40.5
84	312	-5	26.5	174	171	136	50.2	264	141	166	54.1	354	229	78	40.5
85	313	-6	26.5	175	173	134	50.0	265	142	165	54.0	355	229	78	40.5
86	314	-7	26.5	176	173	134	50.0	266	143	164	53.9	356	232	75	39.9
87	313	-6	26.5	177	167	140	50.8	267	144	163	53.8	357	234	73	39.4
88	309	-2	26.5	178	160	147	51.8	268	144	163	53.8	358	234	73	39.4
89	309	-2	26.5	179	160	147	51.8	269	148	159	53.3	359	234	73	39.4

EXHIBIT 31 PAGE 7 DISTANCE TO CONTOUR AND HAAT DATA  
MAY 2010

Callsign : KDFO215  
Coordinates : 35-30-53.0 N, 119-03-41.0 W  
Frequency (MHz): 98.50000  
HAAT (m): 100. AMSL (m): 307.00  
ERP (w): 25000  
City/State : DELANO, CA  
Licensee : CC LICENSES, LLC  
Contour type : F(50,10)  
Signal strength : 40.000 dBu

Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist
0	244	63	107.0	90	309	-2	99.8	180	160	147	121.6	270	148	159	123.4
1	244	63	107.0	91	292	15	99.8	181	157	150	122.1	271	148	159	123.4
2	244	63	107.0	92	304	3	99.8	182	154	153	122.5	272	148	159	123.4
3	246	61	106.6	93	309	-2	99.8	183	154	153	122.5	273	148	159	123.4
4	248	59	106.2	94	310	-3	99.8	184	154	153	122.5	274	151	156	123.0
5	248	59	106.2	95	333	-26	99.8	185	154	153	122.5	275	151	156	123.0
6	249	58	106.0	96	341	-34	99.8	186	154	153	122.5	276	152	155	122.8
7	252	55	105.4	97	345	-38	99.8	187	154	153	122.5	277	153	154	122.7
8	256	51	104.5	98	351	-44	99.8	188	154	153	122.5	278	154	153	122.5
9	259	48	103.9	99	355	-48	99.8	189	153	154	122.7	279	154	153	122.5
10	258	49	104.1	100	360	-53	99.8	190	152	155	122.8	280	154	153	122.5
11	260	47	103.7	101	364	-57	99.8	191	151	156	123.0	281	156	151	122.2
12	260	47	103.7	102	366	-59	99.8	192	151	156	123.0	282	156	151	122.2
13	259	48	103.9	103	368	-61	99.8	193	150	157	123.1	283	156	151	122.2
14	264	43	102.7	104	366	-59	99.8	194	149	158	123.3	284	157	150	122.1
15	267	40	102.1	105	355	-48	99.8	195	149	158	123.3	285	157	150	122.1
16	268	39	101.8	106	347	-40	99.8	196	148	159	123.4	286	158	149	121.9
17	272	35	100.9	107	341	-34	99.8	197	147	160	123.6	287	158	149	121.9
18	273	34	100.7	108	333	-26	99.8	198	146	161	123.7	288	158	149	121.9
19	280	27	99.8	109	329	-22	99.8	199	146	161	123.7	289	158	149	121.9
20	282	25	99.8	110	325	-18	99.8	200	146	161	123.7	290	158	149	121.9
21	281	26	99.8	111	318	-11	99.8	201	144	163	124.0	291	159	148	121.8
22	279	28	99.8	112	310	-3	99.8	202	143	164	124.2	292	159	148	121.8
23	282	25	99.8	113	305	2	99.8	203	143	164	124.2	293	161	146	121.5
24	282	25	99.8	114	300	7	99.8	204	143	164	124.2	294	161	146	121.5
25	287	20	99.8	115	299	8	99.8	205	142	165	124.3	295	161	146	121.5
26	291	16	99.8	116	297	10	99.8	206	140	167	124.6	296	159	148	121.8
27	294	13	99.8	117	292	15	99.8	207	138	169	124.8	297	161	146	121.5
28	292	15	99.8	118	284	23	99.8	208	137	170	125.0	298	161	146	121.5
29	293	14	99.8	119	285	22	99.8	209	137	170	125.0	299	161	146	121.5
30	297	10	99.8	120	274	33	100.5	210	136	171	125.1	300	161	146	121.5
31	301	6	99.8	121	278	29	99.8	211	135	172	125.2	301	162	145	121.3
32	305	2	99.8	122	277	30	99.8	212	135	172	125.2	302	163	144	121.1
33	307	0	99.8	123	277	30	99.8	213	133	174	125.5	303	162	145	121.3
34	310	-3	99.8	124	272	35	100.9	214	133	174	125.5	304	163	144	121.1
35	311	-4	99.8	125	275	32	100.3	215	132	175	125.6	305	163	144	121.1
36	315	-8	99.8	126	270	37	101.4	216	131	176	125.8	306	163	144	121.1
37	319	-12	99.8	127	269	38	101.6	217	132	175	125.6	307	165	142	120.8
38	320	-13	99.8	128	270	37	101.4	218	132	175	125.6	308	165	142	120.8
39	320	-13	99.8	129	272	35	100.9	219	130	177	125.9	309	166	141	120.7
40	322	-15	99.8	130	260	47	103.7	220	130	177	125.9	310	167	140	120.5
41	326	-19	99.8	131	261	46	103.4	221	129	178	126.0	311	167	140	120.5
42	325	-18	99.8	132	267	40	102.1	222	129	178	126.0	312	169	138	120.2
43	326	-19	99.8	133	261	46	103.4	223	128	179	126.2	313	168	139	120.3
44	327	-20	99.8	134	258	49	104.1	224	127	180	126.3	314	168	139	120.3
45	327	-20	99.8	135	253	54	105.2	225	128	179	126.2	315	170	137	120.0
46	329	-22	99.8	136	248	59	106.2	226	128	179	126.2	316	172	135	119.7
47	329	-22	99.8	137	247	60	106.4	227	128	179	126.2	317	172	135	119.7
48	336	-29	99.8	138	242	65	107.4	228	128	179	126.2	318	171	136	119.9
49	333	-26	99.8	139	241	66	107.6	229	129	178	126.0	319	173	134	119.5
50	328	-21	99.8	140	236	71	108.5	230	129	178	126.0	320	174	133	119.4
51	327	-20	99.8	141	233	74	109.0	231	130	177	125.9	321	175	132	119.2
52	327	-20	99.8	142	236	71	108.5	232	129	178	126.0	322	177	130	118.9
53	330	-23	99.8	143	235	72	108.7	233	128	179	126.2	323	177	130	118.9
54	331	-24	99.8	144	222	85	111.0	234	129	178	126.0	324	179	128	118.6
55	328	-21	99.8	145	221	86	111.2	235	130	177	125.9	325	180	127	118.4
56	328	-21	99.8	146	224	83	110.6	236	129	178	126.0	326	181	126	118.2
57	328	-21	99.8	147	221	86	111.2	237	131	176	125.8	327	182	125	118.1
58	322	-15	99.8	148	215	92	112.3	238	131	176	125.8	328	184	123	117.8
59	318	-11	99.8	149	214	93	112.5	239	131	176	125.8	329	185	122	117.6
60	318	-11	99.8	150	213	94	112.7	240	131	176	125.8	330	190	117	116.8
61	320	-13	99.8	151	208	99	113.6	241	130	177	125.9	331	190	117	116.8
62	320	-13	99.8	152	210	97	113.2	242	131	176	125.8	332	194	113	116.1

EXHIBIT 31 PAGE 8 DISTANCE TO CONTOUR AND HAAT DATA  
MAY 2010

Callsign : KDF0215  
Coordinates : 35-30-53.0 N, 119-03-41.0 W  
Frequency (MHz): 98.50000  
HAAT (m): 100. AMSL (m): 307.00  
ERP (w): 25000  
City/State : DELANO, CA  
Licensee : CC LICENSES, LLC  
Contour type : F(50,10)  
Signal strength : 40.000 dBu

Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist	Brg	AT	HAAT	Dist
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----
63	321	-14	99.8	153	202	105	114.7	243	131	176	125.8	333	196	111	115.7
64	321	-14	99.8	154	200	107	115.0	244	132	175	125.6	334	197	110	115.6
65	315	-8	99.8	155	198	109	115.4	245	132	175	125.6	335	197	110	115.6
66	313	-6	99.8	156	195	112	115.9	246	132	175	125.6	336	198	109	115.4
67	313	-6	99.8	157	192	115	116.4	247	133	174	125.5	337	198	109	115.4
68	314	-7	99.8	158	191	116	116.6	248	133	174	125.5	338	199	108	115.2
69	314	-7	99.8	159	189	118	116.9	249	134	173	125.4	339	200	107	115.0
70	316	-9	99.8	160	188	119	117.1	250	134	173	125.4	340	202	105	114.7
71	312	-5	99.8	161	186	121	117.4	251	134	173	125.4	341	203	104	114.5
72	312	-5	99.8	162	184	123	117.8	252	134	173	125.4	342	206	101	114.0
73	311	-4	99.8	163	184	123	117.8	253	136	171	125.1	343	207	100	113.8
74	311	-4	99.8	164	182	125	118.1	254	137	170	125.0	344	211	96	113.0
75	312	-5	99.8	165	178	129	118.7	255	138	169	124.8	345	213	94	112.7
76	310	-3	99.8	166	178	129	118.7	256	139	168	124.7	346	218	89	111.8
77	313	-6	99.8	167	176	131	119.1	257	139	168	124.7	347	222	85	111.0
78	311	-4	99.8	168	176	131	119.1	258	139	168	124.7	348	226	81	110.3
79	314	-7	99.8	169	174	133	119.4	259	140	167	124.6	349	228	79	109.9
80	321	-14	99.8	170	173	134	119.5	260	141	166	124.4	350	228	79	109.9
81	318	-11	99.8	171	171	136	119.9	261	141	166	124.4	351	228	79	109.9
82	316	-9	99.8	172	169	138	120.2	262	141	166	124.4	352	228	79	109.9
83	320	-13	99.8	173	168	139	120.3	263	141	166	124.4	353	229	78	109.7
84	312	-5	99.8	174	171	136	119.9	264	141	166	124.4	354	229	78	109.7
85	313	-6	99.8	175	173	134	119.5	265	142	165	124.3	355	229	78	109.7
86	314	-7	99.8	176	173	134	119.5	266	143	164	124.2	356	232	75	109.2
87	313	-6	99.8	177	167	140	120.5	267	144	163	124.0	357	234	73	108.9
88	309	-2	99.8	178	160	147	121.6	268	144	163	124.0	358	234	73	108.9
89	309	-2	99.8	179	160	147	121.6	269	148	159	123.4	359	234	73	108.9