

# **ENGINEERING REPORT**

## **FM Translator “Long Form” Filing for Original Construction Permit Application**

**NEW253D – Waco, TX**  
File No. BNPFT-20030317ADW  
Facility ID No. 147224

Long-Form Filing pursuant to  
DA 13-283 (AUC-03-83-D)  
“Auction 83 Singleton”

COPYRIGHT 2013

**MUNN-REESE, INC.**  
Broadcast Engineering Consultants  
Coldwater, MI 49036

# **Table of Contents**

---

Discussion of Report

**FM Booster/Fill-in Translator Requirements** (See Discussion)

**Interference Requirements**

Exhibit 13.1 - Copy of Existing Antenna Structure Registration

Exhibit 13.2 - Vertical Plan of Existing Tower Structure

Exhibit 13.3 - Licensed vs Proposed Service Contour Study

Exhibit 13.4 - Proposed vs Primary Station Service Contour Study

**Contour Overlap Requirements**

Exhibit 13.5 - Tabulation of Proposed Allocation

**TV Channel 6 Protection Requirements** (See Discussion)

**Unattended Operation Requirements** (See Discussion)

**Multiple Translator Requirements** (See Discussion)

**RF Radiation Study Requirement**

Exhibit 17.1 - RF Compliance Study

(Exhibit numbering is in response to FCC Online Form 349, Section III-A)

## **Discussion**

---

This firm has been retained to prepare the required engineering report in support of a minor Construction Permit “Long Form” Filing for FM Translator Application BNPFT-20030317ADW (Facility ID No. 147224). The Original “Short-Form” Application specified operation on CH253D (98.5 MHz) with 0.075 kW of non-directional power at an antenna COR of 299 meters AMSL. Amended Operating Parameters will be requested in this “Long-Form” Filing. Operation on new minor change Channel CH256D (99.1 MHz) with a power of 75 watts ERP is requested from the same site location. A circularly polarized non-directional antenna will be utilized at the existing antenna COR height of 299 meters AMSL. The translator will rebroadcast primary station KYFP(FM) – Palestine, TX, CH206C1 (Facility ID No. 85164) as a regular (non-fill-in) non-commercial FM Translator.

Pursuant to Public Notice DA 13-283 (Report No. AUC-03-83-D) and its Attachment B, this “Long-Form” Filing proposes amended parameters more than 39 km from any Appendix A Market Grid. Therefore, the applicant is not required to submit supplemental LPFM Grid Test Showings. In addition, the amended site does not reside within any “out-of-grid” Top-50 Spectrum Limited Market Boundaries, therefore no supplemental Top-50 Transmitter Site Test Showings are required either.

The facility will be located at the proposed tower bearing Antenna Structure Registration Number 1205092. A copy of the existing ASR has been included in **Exhibit 13.1**. The vertical antenna system has been plotted in **Exhibit 13.2**. As this proposal will not increase the overall tower height, it is believed the FAA need not be notified.

It has been determined the translator may be used in the area without given interference to any existing FM broadcast station or facility. General allocation details are found in **Exhibit 13.5**. It is believed sufficient clearance exists precluding the need for additional contour protection showings. The applicant would like to note the use of the USGS 03 second terrain database for all allocation, contour and HAAT calculations contained here-in.

The proposed 60 dBμ contour of the Translator lies wholly outside of the KYFP(FM) primary daytime 60 dBμ contour. A map of the proposed service contour in relation to the primary station service contour has been included in **Exhibit 13.4**. The Translator will rebroadcast KYFP(FM) directly off-air as a non-fill-in FM Translator.

The proposed operating parameters have been changed from the original “Short-Form” values, however the proposed service contour serves a portion of the present service area as seen in **Exhibit 13.3**.

**RADIATION PROTECTION:** The Commission requires an engineering study regarding compliance with the guidelines for human protection from radiofrequency radiation. This report section is in response to that provision of the Rules. The current Federal Communications Commission guidelines for RF radiation protection are set forth in OET Bulletin No. 65 (Edition 97-01), and the accompanying Supplement A, (Edition 97-01).

## Discussion (continued)

The FM Broadcast facility proposed in this application will not produce human exposure to radiofrequency radiation in excess of the applicable safety standards specified in §1.1307(b)(3) of the Commission's rules concerning RF contributors of less than 5%. **Exhibit 17.1** provides the details of the study that was made to demonstrate compliance. The facility is properly marked with signs, and entry is restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed.

***In the event work would be required in proximity to the antenna such that the person or persons working in the area would be potentially exposed to fields in excess of the guidelines set forth in OET Bulletin No. 65 (Edition 97-01), the transmitter power will be reduced or the station will cease operation during the critical period.***

**DISTANCES TO CONTOURS:** The following tabulation of the distances to the proposed service contours results from calculations performed in accordance with §73.313(d) and §73.333 Figure 1 utilizing the USGS 03 second terrain database.

N. Lat. = 313220 W. Lng. = 971057 HAAT and Distance to Contour, FCC, FM 2-10 Mi, 51 pts Method - USGS 03 SEC						
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5
000	132.0	167.0	0.2500	-6.02	1.000	16.95
030	139.1	159.9	0.2500	-6.02	1.000	16.52
060	130.6	168.4	0.2500	-6.02	1.000	17.02
<b>090</b>	<b>121.9</b>	<b>177.1</b>	<b>0.2500</b>	<b>-6.02</b>	<b>1.000</b>	<b>17.49</b>
120	132.8	166.2	0.2500	-6.02	1.000	16.90
150	154.3	144.7	0.2500	-6.02	1.000	15.55
180	184.8	114.2	0.2500	-6.02	1.000	13.73
210	208.9	90.1	0.2500	-6.02	1.000	12.24
240	157.6	141.4	0.2500	-6.02	1.000	15.34
270	163.3	135.7	0.2500	-6.02	1.000	14.99
300	151.5	147.5	0.2500	-6.02	1.000	15.74
330	154.5	144.5	0.2500	-6.02	1.000	15.54
Ave El= 152.61 M HAAT= 146.39 M AMSL= 299 M						