

Human exposure to excess levels of radiofrequency radiation

The proposed facility is to be built using a 1-bay circularly polarized full-wave spaced antenna.

According to OET 65, "Applicants and licensees should be able to calculate, based on considerations of frequency, power and antenna characteristics the distance from their transmitter where their signal produces an RF field equal to, or greater than, the 5% threshold limit. The applicant or licensee then shares responsibility for compliance in any accessible area or areas within this 5% "contour" where the appropriate limits are found to be exceeded."

As can be seen in Exhibit 17-A, the proposed facility's maximum contribution to RF on the site is $0.133 \mu\text{W}/\text{cm}^2$ at a distance of 90 meters from the tower, which is 0.1% of the uncontrolled (public) exposure limit.

Therefore, because the proposed facility will not cause an RF field that is equal to or greater than 5% of the $200 \mu\text{W}/\text{cm}^2$ limit for uncontrolled exposure at any point, the proposed facility complies with the requirements of OET 65.

EMF will fully cooperate with other site users to temporarily reduce power or cease broadcasting, as necessary, to protect workers and others having access to the site from excessive levels of RF Radiation.

Specific Antenna RF Power Density Calculator

Based on Equation 10 of OET-65
Exhibit 17-A / Detailed Report

ERP	0.14 kW	% of OET-65
Height above ground	100.0 meters	0.1% Uncontrolled
Height above head	98.0 meters	0.0% Controlled
Antenna Brand Jampro		
Antenna Model JLCP-1		

Horizontal distance from tower (meters)	Angle (°)	Distance (m)	Field	Power (W)	Power Density (uW/cm2)
0	90	98.0	0.01	1.4	0.000
10	84	98.5	0.18	25.2	0.016
20	78	100.0	0.32	44.8	0.048
30	73	102.5	0.32	44.8	0.046
40	68	105.8	0.45	63	0.085
50	63	110.0	0.45	63	0.078
60	59	114.9	0.6	84	0.127
70	54	120.4	0.6	84	0.116
80	51	126.5	0.6	84	0.105
90	47	133.1	0.71	99.4	0.133
100	44	140.0	0.71	99.4	0.120

