

TABULATION OF ALLOCATION CONTOURS

KQDD, Osceola, AR, Channel 297A

AZ (degs)	HAAT (m)	ERP (kW)	CONTOUR DISTANCES (km) 60.0 F(50,50) (dBu)
--------------	-------------	-------------	-----------------------------------------------

90.0	101	1.6000	21.0
100.0	102	1.6000	21.0
110.0	101	1.6000	21.0
120.0	101	1.6000	21.0
130.0	103	1.6000	21.1
140.0	104	1.6000	21.3
150.0	103	1.6000	21.2
160.0	105	1.6000	21.4
170.0	103	1.6000	21.2
180.0	106	1.6000	21.4
190.0	104	1.6000	21.3
200.0	102	1.6000	21.1
210.0	102	1.6000	21.1
220.0	102	1.6000	21.1
230.0	103	1.6000	21.1

AZ (degs)	HAAT (m)	ERP (kW)	CONTOUR DISTANCES (km) 54.0 F(50,10) (dBu)
--------------	-------------	-------------	-----------------------------------------------

.0	98	1.6000	30.7
10.0	99	1.6000	30.8
20.0	99	1.6000	30.8
30.0	99	1.6000	30.8
40.0	99	1.6000	30.8
50.0	98	1.6000	30.7
60.0	98	1.6000	30.7
300.0	104	1.6000	31.6
310.0	104	1.6000	31.6
320.0	103	1.6000	31.5
330.0	103	1.6000	31.4
340.0	103	1.6000	31.4
350.0	101	1.6000	31.1



TABULATION OF F(50,10) INTERFERENCE CONTOUR FROM PROPOSED FACILITY

AZ (degs)	HAAT (m)	ERP (kW)	CONTOUR DISTANCES (km) 54.0 (dBu)
.0	121	3.9000	42.4
10.0	121	3.9000	42.4
20.0	124	3.9000	42.7
30.0	124	3.9000	42.8
40.0	121	3.9000	42.3
50.0	116	3.9000	41.5
60.0	118	3.9000	41.8
70.0	120	3.9000	42.2
80.0	107	3.9000	40.0
90.0	104	3.9000	39.4
100.0	100	3.9000	38.7
110.0	103	3.9000	39.2
120.0	107	3.9000	39.9
130.0	122	3.9000	42.5
140.0	126	3.9000	43.2
150.0	126	3.9000	43.2
160.0	125	3.9000	43.0
170.0	126	3.9000	43.2
180.0	127	3.9000	43.4
190.0	127	3.9000	43.4
200.0	127	3.9000	43.3
210.0	128	3.9000	43.5
220.0	129	3.9000	43.6
230.0	128	3.9000	43.5
240.0	126	3.9000	43.2
250.0	129	3.9000	43.7
260.0	133	3.9000	44.2
270.0	137	3.9000	44.9
280.0	134	3.9000	44.5
290.0	129	3.9000	43.6
300.0	125	3.9000	43.0
310.0	126	3.9000	43.2
320.0	128	3.9000	43.4
330.0	128	3.9000	43.5
340.0	123	3.9000	42.7
350.0	123	3.9000	42.7



TABULATION OF F(50,50) SERVICE CONTOUR FROM PROPOSED FACILITY

AZ (deg/s)	HAAT (m)	ERP (kW)	CONTOUR DISTANCES (km) 60.0 (dBu)
.0	121	3.9000	28.2
10.0	121	3.9000	28.2
20.0	124	3.9000	28.4
30.0	124	3.9000	28.5
40.0	121	3.9000	28.1
50.0	116	3.9000	27.7
60.0	118	3.9000	27.8
70.0	120	3.9000	28.1
80.0	107	3.9000	26.7
90.0	104	3.9000	26.3
100.0	100	3.9000	25.9
110.0	103	3.9000	26.2
120.0	107	3.9000	26.7
130.0	122	3.9000	28.2
140.0	126	3.9000	28.7
150.0	126	3.9000	28.7
160.0	125	3.9000	28.5
170.0	126	3.9000	28.7
180.0	127	3.9000	28.8
190.0	127	3.9000	28.8
200.0	127	3.9000	28.8
210.0	128	3.9000	28.9
220.0	129	3.9000	28.9
230.0	128	3.9000	28.9
240.0	126	3.9000	28.7
250.0	129	3.9000	29.0
260.0	133	3.9000	29.3
270.0	137	3.9000	29.7
280.0	134	3.9000	29.5
290.0	129	3.9000	28.9
300.0	125	3.9000	28.6
310.0	126	3.9000	28.7
320.0	128	3.9000	28.8
330.0	128	3.9000	28.9
340.0	123	3.9000	28.4
350.0	123	3.9000	28.4



