

FCC Form 349

Exhibit 13

Brewton W262AR Allen Kirby site
Divine Word Communications

REFERENCE	CH# 262D - 100.3 MHz, Pwr= 0.25 kW, HAAT= 6.9 M, COR= 59 M	DISPLAY DATES
31 08 04.2 N.	Average Protected F(50-50)= 7.1 km	DATA 08-01-13
86 55 24.4 W.	Omni-directional	SEARCH 08-29-13

CH CITY	CALL	TYPE	ANT STATE	AZI. <--	DIST FILE #	LAT. LNG.	Pwr(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
262D Brewton	W262AR	LIC	C AL	255.7 75.7	10.21 BLFT20070419AAN	31 06 42.6 87 01 38.9	0.002 82	11.9 130	3.3 Divine Word Communications	-8.5*	-17.1
262A Niceville	WTKE-FM	LIC	NCX FL	160.3 340.4	85.45 BLH20110510ABG	30 24 38.0 86 37 22.0	3.000 143	80.8 148	27.0 R. Lee Hagan, Receiver For	-2.4	34.6
262A Brantley	WAOQ	RSV-A	AL	48.8 229.2	92.29	31 40 46.0 86 11 23.0	6.000 100	87.2 199	28.7 Alatron Corporation, Inc.	-2.0	39.8
262A Brantley	WAOQ	LIC	CN AL	46.2 226.5	92.24 BLH19990603KF	31 42 26.0 86 13 12.0	6.000 100	86.9 203	28.5 Alatron Corporation, Inc.	-1.8	39.1
262A Brantley	WAOQ	APP	ZCX AL	46.2 226.5	92.24 BPH20121219ACP	31 42 26.0 86 13 12.0	6.000 100	86.9 203	28.5 Alatron Corporation, Inc.	-1.8	39.1
264C Pensacola	WCOA-FM	LIC	C FL	230.1 49.7	90.07 BLH20050627AAV	30 36 45.0 87 38 43.0	100.000 521	12.7 553	87.8 Cumulus Licensing Llc	70.3	1.2
260C Mobile	WMXC	LIC	C AL	240.4 60.0	99.68 BMLH20130123AEM	30 41 20.0 87 49 49.0	100.000 535	12.8 569	88.3 Cc Licenses, Llc	79.8	10.3
262D Mobile	W262BL	CP	C AL	240.4 60.0	99.68 BPFT20120213ABP	30 41 20.0 87 49 49.0	0.250	76.4 431	25.5 Red Mountain Broadcasting,	16.2	50.4
262C0 Laurel	WNSL	LIC	CX MS	282.3 101.2	214.53 BMLH20060918AHV	31 31 37.0 89 08 07.0	100.000 324	175.8 394	74.8 Cc Licenses, Llc	31.6	116.0

Terrain database is FCC NGDC 30 Sec, R= 73.215 qualifying spacings or FCC minimum spacings in KM, M= Margin in KM
In & Out distances between contours are shown at closest points. Reference Zone= East Zone, Co to 3rd adjacent.
All separation margins (if shown) include rounding
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
***affixed to 'IN' or 'OUT' values = site inside protected contour.