

EXHIBIT 15.10

Tabulation of Proposed Nighttime Radiation Protecting WTIC (non-directional)

Station: WNWI proposed

Freq. kHz	Power (kW)	Pat-Mult (mV/m)	Theo-RMS (mV/m)	Standard RMS-mV/m	Pat-RSS (mV/m)	Q Factor
1080	0.65	519.63	231.39	243.78	761.23	19.0306

Twr No.	Field Ratio	Phase Deg.	Spacing Deg.	Orient Deg.	Twr Ref	TL/ Sec	Elec-Ht in Deg.	TL(B) Deg.	TL(C) Deg.	TL(D) Deg.
1	0.388	-155.0	0.0	0.0	0	0	77.4	0.0	0.0	0.0
2	1.000	0.0	70.0	170.0	1	0	77.4	0.0	0.0	0.0
3	0.943	154.5	70.0	170.0	1	0	77.4	0.0	0.0	0.0
4	0.326	-51.0	70.0	170.0	1	0	77.4	0.0	0.0	0.0

-----The Calculated Radiation Values-----

Standard Horizontal Plane Pattern

Azimuth Deg.	Field mV/m @ 1 km	Azimuth Deg.	Field mV/m @ 1 km	Azimuth Deg.	Field mV/m @ 1 km
0.0	537.33	5.0	518.63	10.0	492.98
15.0	460.96	20.0	423.32	25.0	381.07
30.0	335.39	35.0	287.67	40.0	239.46
45.0	192.39	50.0	148.09	55.0	108.13
60.0	73.94	65.0	46.89	70.0	28.66
75.0	21.01	80.0	20.96	85.0	22.01
90.0	21.74	95.0	20.69	100.0	20.18
105.0	20.89	110.0	22.34	115.0	23.48
120.0	23.62	125.0	22.75	130.0	21.65
135.0	21.76	140.0	24.33	145.0	29.20
150.0	35.20	155.0	41.10	160.0	45.95
165.0	49.12	170.0	50.21	175.0	49.12
180.0	45.95	185.0	41.10	190.0	35.20
195.0	29.20	200.0	24.33	205.0	21.76
210.0	21.65	215.0	22.75	220.0	23.62
225.0	23.48	230.0	22.34	235.0	20.89
240.0	20.18	245.0	20.69	250.0	21.74
255.0	22.01	260.0	20.96	265.0	21.01
270.0	28.66	275.0	46.89	280.0	73.94
285.0	108.13	290.0	148.09	295.0	192.39
300.0	239.46	305.0	287.67	310.0	335.39
315.0	381.07	320.0	423.32	325.0	460.96
330.0	492.98	335.0	518.63	340.0	537.33
345.0	548.70	350.0	552.51	355.0	548.70

**Complete Tabulations of Directional Polar Pattern for 0° to 60°
angles of radiation will be supplied upon request.**

MUNN-REESE, INC.

Broadcast Engineering Consultants
Coldwater, MI 49036