

ENGINEERING REPORT
LPFM (Low Power FM)
Original Construction Permit
Application

NEW267L1 – Monticello, MS
(101.3 MHz)

Form 318 – “New Station”
Filing Pursuant to
FCC Public Notice, DA 13-1385
(Released June 17, 2013)

November, 2013

COPYRIGHT 2013

Table of Contents

Discussion of Report

Tech Box Requirements

Exhibit 11.1 - Copy of USGS Topographic Map of Proposed Site

Exhibit 11.2 - Vertical Plan of Existing Tower Structure

Exhibit 11.3 - Proposed Service Contour Study

Interference Protection Requirements

Exhibit 11.4 - Proposed LPFM Spacings Study

Interference to Input Signal Requirements (See Discussion)

TV Channel 6 Protection Requirements (See Discussion)

RF Radiation Study Requirement

Exhibit 14.1 - RF Compliance Study

(Exhibit numbering is in response to FCC Online Form 349, Section III-A)

Discussion

This firm has been retained to prepare the required engineering report in support of an Original Construction Permit Application for a Form 318 "New Station" LPFM facility. This Filing is in response to FCC Public Notice DA 13-1385 (Released June 17, 2013) announcing the upcoming October 15 – October 29, 2013 Low Power Filing Window. Original operating parameters will be requested in this "New Station" Form 318 Filing. Operation on Channel CH267L1 (101.3 MHz) is requested with a power of 0.016 kW ERP at 73 meters HAAT. A circularly polarized non-directional antenna will be utilized at the antenna COR height of 156 meters AMSL. The new LPFM facility will serve the community of Monticello, MS.

The facility will be located on an existing unregistered 30.5 meter (100 foot) communications tower. A USGS Aerial Photo-Map of the existing tower has been included in **Exhibit 11.1**. The vertical antenna system has been plotted in **Exhibit 11.2**. FCC TOWAIR has been consulted and FAA Notification is not required. Furthermore, as this proposal will not increase the overall tower height, it is believed the FAA need not be notified.

It has been determined the proposed LPFM facility meets all §73.807(a) spacing requirements toward all other existing or proposed concerns. General allocation details are found in **Exhibit 11.4**. It is believed sufficient clearance exists precluding the need for additional allocation showings.

The proposed LPFM facility will be located more than 320 km from the common border between the United States and Canada and/or Mexico. Therefore, full protection is believed afforded all international concerns. Additional International compliance showings will be supplied upon request.

The proposed LPFM facility will remain in compliance with §73.827(a). There are no existing or proposed FM Translator or FM Booster facilities located within the worst case 10 km radius of the proposed LPFM site. A listing of the FM domestic concerns within the radius is as follows:

ID Stations Study at 31 35 54 N, 90 03 11 W, Search Distance = 10.1 km										
Call	Srv	City	ST	CH	Power	Coordinates	Dist	Azi	File Number	
none	---	-----	--	---	-----	-----	---	---	-----	

The applicant would like to note the use of the NGDC 30 second terrain database for all allocation, contour and HAAT calculations contained here-in.

The proposed 60 dBμ F(50:50) Service Contour has been noted in **Exhibit 11.3**.

Discussion (continued)

RADIATION PROTECTION: The Commission requires an engineering study regarding compliance with the guidelines for human protection from radiofrequency radiation. This report section is in response to that provision of the Rules. The current Federal Communications Commission guidelines for RF radiation protection are set forth in OET Bulletin No. 65 (Edition 97-01), and the accompanying Supplement A, (Edition 97-01).

The FM Broadcast facility proposed in this application will not produce human exposure to radiofrequency radiation in excess of the applicable safety standards specified in §1.1310 of the Commission's rules. ***Exhibit 14.1*** provides the details of the study that was made to demonstrate compliance. The facility is properly marked with signs, and entry is restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed.

In the event work would be required in proximity to the antenna such that the person or persons working in the area would be potentially exposed to fields in excess of the guidelines set forth in OET Bulletin No. 65 (Edition 97-01), the transmitter power will be reduced or the station will cease operation during the critical period.

DISTANCES TO CONTOURS: The following tabulation of the distances to the proposed service contours results from calculations performed in accordance with §73.813 & §73.313(d) and §73.333 Figure 1 utilizing the NGDC 30 second terrain database.

N. Lat. = 313554.0 W. Lng. = 900311.0						
HAAT and Distance to Contour,						
FCC, FM 2-10 Mi, 51 pts Method - NGDC 30 SEC						
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5
000	104.8	51.2	0.0160	-17.96	1.000	4.69
045	115.1	40.9	0.0160	-17.96	1.000	4.14
090	113.1	42.9	0.0160	-17.96	1.000	4.25
135	85.4	70.6	0.0160	-17.96	1.000	5.49
180	51.6	104.4	0.0160	-17.96	1.000	6.70
225	69.7	86.3	0.0160	-17.96	1.000	6.07
270	64.1	91.9	0.0160	-17.96	1.000	6.27
315	62.8	93.2	0.0160	-17.96	1.000	6.32
Ave El= 83.34 M HAAT= 72.66 M AMSL= 156.0						