

JAN 23 1986

UNITED STATES OF AMERICA
FEDERAL COMMUNICATIONS COMMISSION

File No.: BL-820715AC
FACID: 48513
Call Sign: KIRV

AM BROADCAST STATION LICENSE

Subject to the provisions of the Communications Act of 1934, as amended, subsequent Acts, Treaties, and Commission Rules made thereunder, and further subject to conditions set forth in this license,¹ the LICENSEE

NEW LIFE ENTERPRISES, INC.

is hereby authorized to use and operate the radio transmitting apparatus hereinafter described for the purpose of broadcasting for the term ending 3 a.m. Local Time DECEMBER 1, 1990 in accordance with the following:

1. Station location: Fresno, CA
2. Main Studio location:
(Listed only if not at transmitter site or not within boundaries of principal community)
3. Remote control location: 3636 N. 1st St.,
Fresno, Ca
4. Transmitter location: 2025 W. Church, Ave.,
Fresno, CA
North latitude : 36 ° 42 ' 42 "
West longitude: 119 ° 49 ' 59 "
5. Transmitter(s): Type Accepted. (See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.)
6. Antenna and ground system: See Page 2.
7. Obstruction marking and lighting specifications — FCC Form 715, paragraphs: 1, 3, 11 & 21.
8. Frequency (kHz.): 1510
9. Nominal power (kW): 10.0 Day
- Night
- Antenna input power (kW): 10.5 Day
- Night
☐ Non-directional antenna: current _____ amperes; resistance _____ ohms.
☒ Directional antenna : current 14.5 amperes; resistance 50.0 ohms.
☐ Non-directional antenna: current _____ amperes; resistance _____ ohms.
☐ Directional antenna : current _____ amperes; resistance _____ ohms.
10. Hours of operation: Specified in construction permit (BP -790124AF)
11. Conditions: - -

The Commission reserves the right during said license period of terminating this license or making effective any change, or modification of this license which may be necessary to comply with any decision of the Commission rendered as a result of any hearing held under the rules of the Commission prior to the commencement of this license period or any decision rendered as a result of any such hearing which has been designated but not held, prior to the commencement of this license period.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934, as amended. This license is subject to the right of use or control by the Government of the United States conferred by Section 606 of the Communications Act of 1934, as amended.

¹ This license consists of this page and pages



File NO.: BL 820715AF

Call Sign: KIRV

Date:

DA- D

1. DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

No. and Type of Elements: Two, vertical, cross section, guyed radiators
Theo. RMS: 623.9 mV/m; Std. RMS: 655.4 mV/m. Towers are insulated at 120'
level with pass/reject filter installed.

Height above Insulators: 185' (102.2°)

Overall Height: 190'

Spacing and Orientation: Tower #2 is 162.6' (90°) from tower #1 at a bearing
of 140° T.

Non-Directional Antenna: None authorized

Ground System consists of 120 radials 162' plus 120 radials 50' about
base of each tower. Radials are shortened and
bonded to copper strap midway between elements.

2. THEORETICAL SPECIFICATIONS

	N(#1)	SE(#2)
Phasing:	0°	-94.5°

Field Ratio:	1.0	0.77
--------------	-----	------

3. OPERATING SPECIFICATIONS

Phase Indication*:	0°	-78.3°
--------------------	----	--------

Antenna Base Current Ratio:	1.00	0.750
--------------------------------	------	-------

Antenna Monitor Sample Current Ratio:	1.00	0.772
--	------	-------

* As indicated by Delta Electronics DAM-1(3-218) antenna monitor.

EXEMPTIONS AS LISTED IN SECTION 73.68(b) OF THE RULES WILL APPLY DURING PROPER
OPERATION OF APPROVED SAMPLING SYSTEM.

Field measuring equipment shall be available at all times and the field intensity at each of the monitoring point shall be measured at least once every seven days and appropriate record kept of all measurements so made.

DESCRIPTION OF AND FIELD STRENGTH OF MONITORING POINTS:

Direction of 302° true North. Distance of 2.1 miles. From starting point at KIRV towers, proceed .04 miles north on Dirt Road to Church Avenue. Turn left (west) on Church, proceed 1.55 miles west to JCT. of church & Brawley, turn right (north) on Brawley 1.0 mi. North to JCT. of Brawley & Madison, turn left (west) .25 mi. on Madison Ave., turn right (north) on East Driveway, 7 White Fence Posts North, fence post is marked with 3 large-head nails in triangular shape six feet East of post. The field intensity measured at this point should not exceed 35.8 mV/m.

Direction of 320° true North. Distance of 2.7 miles. From point no. 1 return to JCT. of Madison & Brawley, turn left (north) on Barwley 1.0 mi. North to Nielson Ave., turn left (west) on Nielson .25 mi., with two stripes of gold paint. The field intensity measured at this point should not exceed 25 mV/m.

Direction of 338° true North. Distance of 2.63 miles. From point no. 2 return east to JCT. of Nielson & Brawley, turn left (north) on Barwley .35 mi. to Franklin, turn right (east) on Franklin to JCT. Franklin & Valentine, 36 yds. west on Franklin, which point is identified by number spray-painted with gold paint on Blacktop pavement. The field intensity measured at this point should not exceed 35.4 mV/m.