

ENGINEERING REPORT

FM Translator Minor Construction Permit Application

for

**K288GF.L – Clinton, MO
(Formerly K285EM)
Facility ID No. 36259**

Pending License File No.
BLFT-20110607AAS

June, 2011

COPYRIGHT 2011

MUNN-REESE, INC.
Broadcast Engineering Consultants
Coldwater, MI 49036

Table of Contents

Discussion of Report

FM Booster/Fill-in Translator Requirements (See Discussion)

Interference Requirements

Exhibit 13.1 - USGS Topographic Map of Proposed Site

Exhibit 13.2 - USGS Aerial Photograph of Proposed Site

Exhibit 13.3 - Vertical Plan of Proposed Tower Structure

Exhibit 13.4 - Licensed vs Proposed Service Contour Study

Exhibit 13.5 - Proposed vs Primary Station Service Contour Study

Contour Overlap Requirements

Exhibit 13.6 - Tabulation of Proposed Allocation

Exhibit 13.7 - Proposed Contour Protection Toward APP291D – Adrian, MO

TV Channel 6 Protection Requirements (See Discussion)

Unattended Operation Requirements (See Discussion)

Multiple Translator Requirements (See Discussion)

RF Radiation Study Requirement

Exhibit 17.1 - RF Compliance Study

(Exhibit numbering is in response to FCC Online Form 349, Section III-A)

Discussion

This firm has been retained to prepare the required engineering report in support of a minor construction permit application for FM translator K288GF.L (formerly K285EM), Clinton, MO, Pending License No. BLFT-20110607AAS. K288GF.L presently operates on 105.5 MHz with 0.250 kW of non-directional power with an antenna COR of 241 meters AMSL. An increase in COR height to 250 meters AMSL from a new site location is requested. Operation on CH290D, 105.9 MHz with 250 watts ERP is requested. The translator will continue to rebroadcast primary station of KLRQ(FM) – Clinton, MO, CH241C0, Facility ID No. 3429 as a Fill-In Translator.

The proposed facility will be relocated to a new tower location. A copy of the USGS Topographic Map for the site has been included in **Exhibit 13.1**. A copy of the USGS Aerial Photograph for the site has been included in **Exhibit 13.2**. A copy of the vertical antenna system has been included in **Exhibit 13.3**. TOWAIR has been consulted and the proposed tower does not require Antenna Structure Registration.

It has been determined the translator may be used in the area without interference to any existing FM broadcast station or facility. General allocation details are found in **Exhibit 13.6**. There is one facility, APP291D – Adrian, MO (BNPFT-20030317BSU) close enough to merit further protection studies. Therefore an FMCommander™, map and tabulation of contours toward APP291D has been included in **Exhibit 13.7**. It is believed sufficient clearance exists precluding the need for additional contour protection showings.

The translator site and proposed 60 dBu contour lie inside of the KLRQ(FM) 60 dBu service contour therefore qualifying this service as an FM Fill-In Translator. A map of the proposed service area in relation to the primary station 60 dBu service contour has been included in **Exhibit 13.5**.

Regarding protection of international concerns, the facility is and will remain more than 320 km of the common border between the United States and Canada or Mexico. As a result, it is believed no further international showings are required.

The proposed operating parameters have been changed from the licensed values, however the proposed service contour serves a portion of the present service area as seen in **Exhibit 13.4**.

The applicant would like to note the use of the USGS 03 second terrain database for all HAAT, allocation and contour showings used for this Form 349 Translator filing.

RADIATION PROTECTION: The Commission requires an engineering study regarding compliance with the guidelines for human protection from radiofrequency radiation. This report section is in response to that provision of the Rules. The current Federal Communications Commission guidelines for RF radiation protection are set forth in OET Bulletin No. 65 (Edition 97-01), and the accompanying Supplement A, (Edition 97-01).

Discussion (continued)

The FM Broadcast facility proposed in this application will not produce human exposure to radiofrequency radiation in excess of the applicable safety standards specified in §1.1310 of the Commission's rules. **Exhibit 17.1** provides the details of the study that was made to demonstrate compliance. The facility is properly marked with signs, and entry is restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed.

In the event work would be required in proximity to the antenna such that the person or persons working in the area would be potentially exposed to fields in excess of the guidelines set forth in OET Bulletin No. 65 (Edition 97-01), the transmitter power will be reduced or the station will cease operation during the critical period.

DISTANCES TO CONTOURS: The following tabulation of the distances to the proposed service contours results from calculations performed in accordance with §73.313(d) and §73.333 Figure 1 utilizing the USGS 03 second terrain database.

N. Lat. = 382502.0 W. Lng. = 940542.0 HAAT and Distance to Contour, FCC, FM 2-10 Mi, 51 pts Method - USGS 03 SEC						
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5
000	258.8	-8.8	0.2500	-6.02	1.000	7.09
030	248.5	1.5	0.2500	-6.02	1.000	7.09
060	237.4	12.6	0.2500	-6.02	1.000	7.09
090	235.9	14.1	0.2500	-6.02	1.000	7.09
120	256.9	-6.9	0.2500	-6.02	1.000	7.09
150	250.9	-0.9	0.2500	-6.02	1.000	7.09
180	255.7	-5.7	0.2500	-6.02	1.000	7.09
210	275.1	-25.1	0.2500	-6.02	1.000	7.09
240	267.7	-17.7	0.2500	-6.02	1.000	7.09
270	253.1	-3.1	0.2500	-6.02	1.000	7.09
300	241.3	8.7	0.2500	-6.02	1.000	7.09
330	252.8	-2.8	0.2500	-6.02	1.000	7.09
Ave El= 252.84 M HAAT= -2.84 M AMSL= 250						