

Exhibit 17

RF Radiation Guidelines Compliance

The facilities proposed in this application have been evaluated for potential human exposure to non-ionizing radiofrequency radiation. The guidelines set forth in OET bulletin no. 65 and the Commission's RF Worksheet #2 (AM) were consulted.

The proposed KAHS nighttime array will operate with a nighttime input power of .24 kW into a 3 tower array. For the purpose of this study, .24 kW has been assumed to be present in each tower. Each element in the array is 84.6 degrees in electrical length.

Table 2 specifies that at .25 wavelength on a frequency of 1360 kHz with an input power of 1 kW or less, the non-ionizing radiation will fall to safe levels at a distance of 1.0 meter or more.

Fences will be built around the base of each tower to achieve the level of protection specified in the above referenced guidelines. Access to the areas within the fences will be limited by means of locked gates. In addition, signs will be posted warning of the potential for exposure to excessive levels of non-ionizing RF radiation.

In the event maintenance personnel are required to work within the restricted areas, they will be advised to limit their work in the high RF field to specified periods of time appropriate for compliance with the guidelines set forth in OET Bulletin No. 65. If their work cannot be completed within the time specified, the power will be reduced or the station will be shut down until the work is completed.

There are no other RF sources at this site subject to the provisions of OET Bulletin No. 65.