

FEDERAL COMMUNICATIONS COMMISSION
445 TWELFTH STREET SW
WASHINGTON DC 20554

MEDIA BUREAU
AUDIO DIVISION
APPLICATION STATUS: (202) 418-2730
HOME PAGE: www.fcc.gov/mb/audio/

ENGINEER: CHARLES N. (NORM) MILLER
TELEPHONE: (202) 418-2767
FACSIMILE: (202) 418-1410
E-MAIL: charles.miller@fcc.gov

March 27, 2007

Andrew S. Kersting, Esq.
Dickstein Shapiro Morin & Oshinsky LLP
2101 L Street NW
Washington, DC 20037-1526

Re: KTCT(AM), San Mateo, California
Facility Identification Number : 51188
Susquehanna Radio Corporation
Special Temporary Authorization

Dear Counsel:

This is in reference to the request filed May 25, 2006, on behalf of Susquehanna Radio Corporation ("SRC"), licensee of Station KTCT(AM), San Mateo, California. SRC requests further extension of the special temporary authority ("STA") originally granted on June 15, 1999, and modified on February 11, 2004, to operate Station KTCT with its authorized daytime facilities during nighttime hours in order to overcome interference from a foreign station.¹

In support of its request for extension, SRC states that the STA was authorized to overcome interference to KTCT from an unauthorized operation of cochannel Station XED, Mexicali, Baja California, Mexico. SRC further states that the interference situation has not changed.

Accordingly, the request for extension of STA IS HEREBY GRANTED, subject to the following condition:

Operation with the facilities specified herein is subject to modification, suspension or termination without right to hearing, if found by the Commission to be necessary in order to conform to the provisions of the registration process of the ITU, or to bilateral or other multilateral agreements between the United States and any other country.

Station KTCT may continue to operate with increased power during nighttime hours in order to overcome interference from the non-compliant operation of Station XED. Operation pursuant to this authority shall be in accordance with the attached Directional Antenna Specifications. It will be necessary to reduce power or cease STA operation if complaints of interference are received. SRC must use whatever means are necessary to protect workers and the public from exposure to radio frequency radiation in excess of the Commission's exposure guidelines. See 47 CFR §

¹ KTCT is licensed for operation on 1050 kHz with 50 kilowatts daytime and 10 kilowatts nighttime, employing different directional antenna patterns during daytime and nighttime hours (DA-2-U).

1.1310.

This authority expires on **September 27, 2007**.

Sincerely,

A handwritten signature in cursive script, appearing to read "Charles N. Miller".

Charles N. Miller, Engineer
Audio Division
Media Bureau

Attachment: Directional Antenna Specifications

cc: Susquehanna Radio Corporation

SPECIAL TEMPORARY AUTHORITY

**SPECIFICATIONS FOR NIGHTTIME DIRECTIONAL OPERATION OF
KTCT (AM), San Mateo, CA**

Frequency: 1050 kHz **Nominal Power:** 50 kW **Antenna Input Power:** 52.6 kW

Common Point Current: 32.43 Amperes **Common Point Resistance:** 50 ohms

Transmitter site coordinates (NAD 1927): 37° 39' 02" N, 122° 09' 02" W

Description of Directional Antenna System:

Number and Type of Elements: Five (5) vertical, self-supporting, series-excited steel radiators. (Note: Tower #5 is not used in this pattern.)

Height above Insulators: 61.0 meters (76.9°)

Overall Height: 62.5 meters

Ground System: 120 radials 72 m in length except where intersecting radials are shortened and bonded, plus 120 radials 15.2 m in length, about the base of each tower.

Spacing and Orientation: With Tower #3 (WC) as a reference, Tower #1 (E) is spaced 180.0° (142.8 m) on a line bearing 80.8° ; Tower #2 (EC) is spaced 90.0° (71.4 m) on a line bearing 81.8°; Tower #4 (W) is spaced 90.5° (71.8 m) on a line bearing 253.3°; Tower #5 (N) is spaced 102.4° (81.2 m) on a line bearing 327.8°.

Theoretical RMS: 2327.6 mV/m at 1 km

Standard RMS: 2445.25 mV/m at 1 km

Q factor: 75.1 mV/m

SPECIAL TEMPORARY AUTHORITY

SPECIFICATIONS FOR NIGHTTIME DIRECTIONAL OPERATION OF KTCT (AM), San Mateo, CA

Tower:	#1(E)	#2 (EC)	#3 (WC)	#4(W)
---------------	--------------	----------------	----------------	--------------

Theoretical Parameters:

Field Ratio:	0.402	1.0	1.0	0.357
Phasing (degrees):	-95.2	126.6	0.0	-112.7

Operating Parameters*

Phase (degrees):	-91.4	125.2	0.0	-109.2
Current Ratio:	0.417	0.906	1.00	0.304

*As indicated by Potomac Instruments AM-1901 antenna Monitor.

Antenna sampling system approved under Section 73.68 (b) of the rules.

Descriptions Of And Field Intensities At Monitor Points:

Direction of 52.5° True North: North side of Grove Way, west end of Cherryland Park, 200' into park at northwest corner of basketball court. Distance from the transmitter site is 4.83 km. The field intensity at this point shall not exceed **36.0 mV/m**.

Direction of 122° True North: Northwest corner of the intersection of Pueblo springs Avenue and Pueblo Lake Avenue, at curb, next to fire hydrant. Distance from the transmitter site is 5.63 km. The field intensity at this point shall not exceed **25.6 mV/m**.