

Larry H. Will, P.E.

Broadcast Engineering

1055 Powderhorn Drive
Glen Mills, PA 19342-9504

PH (610) 399-1826
FAX (610) 399-0995
E-Mail lhwill@verizon.net

ATLANTIC COAST COMMUNICATIONS, INC

HOLMDEL, NEW JERSEY

LICENSEE OF W26CE CHANNEL 26

NEW YORK, NEW YORK

FCC Facility ID #47855

**FCC FILE Nos. BLTTL-20010927ABF
BSTA-20070821AEJ**

**APPLICATION FOR A CONSTRUCTION PERMIT TO FLASH CUT
W26CE ON CHANNEL 26**

ENGINEERING EXHIBIT 12

December 21, 2007

ATLANTIC COAST COMMUNICATIONS, INC

LICENSEE OF W26CE CHANNEL 26

**APPLICATION FOR A CONSTRUCTION PERMIT TO FLASH CUT W26CE
ON CHANNEL 26**

**FCC FILE Nos. BLTTL-20010927ABF
BSTA-20070821AEJ**

ENGINEERING EXHIBIT 12

ENVIRONMENTAL STATEMENT

There are no AM stations within 3.2 km of the W26CE site. The instant application is excluded under 1.1306. Using the procedures outlined in OET Bulletin 65, Edition 97-01 and specifically Appendix A, Table 1 and Equation 9, Page 21, I have evaluated the RFR energy from the antenna system of W26CE (CH 26) as follows:

W26CE is the only station at this general location required to be considered by 47 CFR 1.1307(b).

W26CE: W26CE is proposing operation on Channel 26 utilizing a digital ERP of 1.0 kilowatt with a directional antenna and horizontal polarization. The Channel 26 transmitting antenna is a high gain unit with an elevation power gain of 8x side mounted with a C/R 72.9 meters up the tower. With the resulting high elevation gain, the RFR energy at steep angles below the horizon is expected to be at least 10 dB below that of the main lobe. Utilizing Appendix A, Table 1 the maximum occupational/controlled exposure level at CH 26 is 1810 uW/cm². Using Equation 10, Page 21, the distance to the 1810 uW/cm² contour is 3.4 meters. For general public/uncontrolled environment the maximum exposure level is 362 uW/cm². Again using Equation 10, the distance to the 362 uW/cm² contour is 5.7 meters.

Since the base of the antenna is at least 76 meters above the ground, the height of the structure limits the possible excessive radiation values to at least 70.3 meters above the ground.

Again using Equation 10, the predicted RFR energy levels at 2 meters above ground is calculated at 0.6 uW/cm^2 or 0.2% of the FCC allowable for the general public/uncontrolled environment per FCC OET Bulletin 65.

Therefore the total level of the W26CE RFR source at all points on the ground is below that required for protection of both the employees and the general public as required by ANSI 95.1-1992 or FCC OET 65, Edition 97-01. The total RFR level is calculated not to not exceed 0.6 uW/cm^2 or 0.2% of the FCC allowable anywhere on the ground in the area of the tower. Neither workers nor the general public will be exposed to electromagnetic fields exceeding the maximum permissible exposure (MPE) levels set forth in Section 1.1310 of the FCC Rules.

Where radio frequency fields in excess of FCC guidelines are predicted to be encountered (very near the station's transmission antenna), signs and protective devices shall secure the area affected from the general public. With respect to direct employees of this licensee, OSHA RFR guidelines will be observed. Contractors and other outside workers potentially exposed to such areas shall be advised of the hazard by posted notices or other means. The station will reduce power or cease operation, if necessary, in order to protect workers on the tower.

With these procedures in place, we believe the proposed W26CE (Channel 26) operation at this new site will be in compliance with the RFR energy requirements of 47 CFR 1.1307(b).