

# Exhibit 15-V-3 Tabulation of Distance to WWNR Daytime Allocation Contours

WWNR        620 kHz   Lic        ND2U        BL020225CM        20060522  
WV BECKLEY        5.000 kW    1 Tower        0 Augmentations  
N. Lat: 37 45 18   W. Lon: 81 14 12        18 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.  
All distances are in kilometers (US metric curves)  
All radiations are in mV/m at one kilometer

'M\*' bearing is supplemented by measurements.  
'+-' 10 deg. variance from measured bearing.

Bearing	Radiation	Distance to Contours	
		0.500	0.250
0.0-	666.5	40.72	56.88
5.0M*	666.5	40.72	56.88
10.0+	666.5	40.72	56.88
15.0+	666.5	40.72	56.88
20.0-	666.5	40.72	56.88
25.0M*	666.5	40.72	56.88
30.0+	666.5	40.72	56.88
35.0+	666.5	40.72	56.88
40.0-	666.5	44.26	72.96
45.0M*	666.5	44.26	72.96
50.0+	666.5	44.26	72.96
55.0+	666.5	44.26	72.96
60.0-	666.5	40.72	56.88
65.0M*	666.5	40.72	56.88
70.0+	666.5	40.72	56.88
75.0+	666.5	40.72	56.88
80.0-	666.5	40.72	56.88
85.0M*	666.5	40.72	56.88
90.0+	666.5	40.72	56.88
95.0+	666.5	40.72	56.88
100.0-	666.5	40.72	56.88
105.0M*	666.5	40.72	56.88
110.0+	666.5	40.72	56.88
115.0+	666.5	40.72	56.88
120.0-	666.5	40.72	56.88
125.0M*	666.5	40.72	56.88
130.0+	666.5	40.72	56.88
135.0+	666.5	40.72	56.88
140.0-	666.5	40.72	56.88
145.0M*	666.5	40.72	56.88
150.0+	666.5	40.72	56.88
155.0+	666.5	40.72	56.88
160.0-	666.5	40.72	56.88
165.0M*	666.5	40.72	56.88
170.0+	666.5	40.72	56.88
175.0+	666.5	40.72	56.88

**Exhibit 15-V-3 (cont.)**  
**Tabulation of Distance to WWRN Daytime Allocation Contours**

WVNR	620 kHz	Lic	ND2U	BL020225CM	20060522
WV	BECKLEY			5.000 kW 1 Tower	0 Augmentations
N. Lat:	37 45 18	W. Lon:	81 14 12		18 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
180.0-	666.5	40.72	56.88
185.0M*	666.5	40.72	56.88
190.0+	666.5	40.72	56.88
195.0+	666.5	40.72	56.88
200.0-	666.5	40.72	56.88
205.0M*	666.5	40.72	56.88
210.0+	666.5	40.72	56.88
215.0+	666.5	40.72	56.88
220.0-	666.5	40.72	56.88
225.0M*	666.5	40.72	56.88
230.0+	666.5	40.72	56.88
235.0+	666.5	40.72	56.88
240.0-	666.5	40.72	56.88
245.0M*	666.5	40.72	56.88
250.0+	666.5	40.72	56.88
255.0+	666.5	40.72	56.88
260.0-	666.5	48.53	77.23
265.0M*	666.5	48.53	77.23
270.0+	666.5	48.53	77.23
275.0+	666.5	48.53	77.23
280.0-	666.5	44.29	72.99
285.0M*	666.5	44.29	72.99
290.0+	666.5	44.29	72.99
295.0+	666.5	44.29	72.99
300.0-	666.5	40.72	60.08
305.0M*	666.5	40.72	60.08
310.0+	666.5	40.72	60.08
315.0+	666.5	40.72	60.08
320.0-	666.5	40.72	56.88
325.0M*	666.5	40.72	56.88
330.0+	666.5	40.72	56.88
335.0+	666.5	40.72	56.88
340.0-	666.5	40.72	56.88
345.0M*	666.5	40.72	56.88
350.0+	666.5	40.72	56.88
355.0-	666.5	40.72	56.88