

## **EXHIBIT 13**

### **Waiver Request of Section 74.1204**

K220HA Kihei, HI 10 Watts ERP

Minor IF Change to 273

Calvary Chapel of Twin Falls, Inc.

August 2010

The proposed site is contained entirely inside the service contour of second-adjacent FM Station KLZY Paia, HI

The transmit antenna and coax will not be modified on this proposal.

### **KLZY**

The proposed site is contained entirely inside the service contour of third-adjacent KLZY, 275C2, 1.55kW, Paia, HI. KLZY is located on the same tower as the proposed, making the level of least arriving protected F(50,50) signal at the proposed transmitter site more than 100.0-dBu. Using the Undesired-to-Desired method for calculating proposed interference, the interfering contour is more than 140-dBu (free-space contour method employed). The interfering signal would extend less than 1 meter from the center of radiation, which will remain at 15 meters AGL. This interference contour does not touch the ground and because this is a remote communications site, there are no residences or businesses located within the contour. The only structures at this site house equipment associated with the communications and broadcast on this tower. Calvary Chapel of Twin Falls, Inc. respectfully requests a waiver of the FM translator contour overlap regulations with respect to second-adjacent KLZY Paia, HI

Calvary Chapel of Twin Falls, Inc.

Calvary Chapel Of Twin Falls, Inc.  
 Minor IF Change BLMFT-20070823AEP Kihel, HI  
 CH# 273D - 102.5 MHz, Pwr= 0.01 kW, HAAT= 0.0 M, COR= 1347 M  
 Average Protected F(50-50)= 3.15 km  
 Omni-directional

DISPLAY DATES  
 DATA 08-20-10  
 SEARCH 08-31-10

REFERENCE  
 20 39 36.0 N.  
 156 21 50.0 W.

CH CITY	CALL	TYPE STATE	ANT STATE	AZI <--	DIST FILE #	LAT LNG	PWR(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
275C2 Pai a	KLZY	LIC	DC_	0.0 0.0	0.0 BLH20080228ABV	20 39 36.0 156 21 50.0	1.550 696	2.4 1387	52.0 Chaparral Broadcasting, In	-17.4*<	-52.3*<
273D Wai mea	641397	APP	_C_	136.0 316.2	90.7 BNPFT20030317EKA	20 04 16.0 155 45 35.5	0.010	40.1 1044	11.6 Edgewater Broadcasting, In	33.2	14.0
272C3 Kaunakakai	KMKK-FM	LIC	_CX	301.5 121.2	100.8 BLH20070202AAZ	21 07 55.0 157 11 31.0	1.900 360	60.6 421	40.1 Ohana Broadcast Company LI	22.1	29.6
274C Wai pahu	ALLO	USE	___	293.9 113.3	202.0	21 23 12.0 158 08 48.0	100.000 600	136.1 726	91.4	47.8	79.3
274C Wai pahu	KDDB	LIC	DEN	294.8 114.1	198.0 BLH19881205KA	21 23 49.0 158 05 58.0	61.000 577	131.5 703	89.1 Ohana Broadcast Company LI	48.4	77.6

Terrain database is USGS 03 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM  
 Contour distances are on direct line to and from reference station. Reference zone = , Co to 3rd adjacent.  
 Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, \_= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)  
 "\*"affixed to 'IN' or 'OUT' values = site inside protected contour.

