

Exhibit #22

R.F. EMISSIONS COMPLIANCE STATEMENT

KPSC
Channel 203
Palm Springs, California

September 2002

The proposed two bay, half-wave spaced, circularly polarized antenna will be energized such that it produces 1.26 kW effective radiated power from a center of radiation of 32.8 meters above ground. Using the formulas expressed in the OET Bulletin, No. 65, August 1997, "Evaluating Compliance with F.C.C. Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", published by the Federal Communication Commission's Office of Science and Engineering, and then by applying a combination of the element and array pattern as defined in E.P.A. study PB85-245868 ("**Engineering Assessment of the Potential Impact of the Federal Radiation Protection Guidance on the AM, FM and TV Broadcast Services**") the predicted level of RF non-ionization emissions at a position of 2 meters above ground (head-height) for the proposed 2-bay, half-wave spaced ERI-LPX-2E-HW (Type #3) antenna is less than one microwatt per square centimeter.

The new transmitter will contribute less than 1% of the maximum allowable RF emission level. No further calculations were deemed necessary.

The applicant will protect workers on the tower by either reducing ERP or terminating transmission.

Consequently, it appears that the proposed FM station, when using the antenna listed above, will be in full compliance with the Commission's human exposure to radiofrequency electromagnetic field rules and regulations.