

EXHIBIT 12
Page #1, Waiver Request of Section 74.1204

K201DO, Farmington , NM 25 Watts ERP
Calvary Chapel of Twin Falls, Inc. 09/02

The proposed site is contained entirely inside the service contour of second-adjacent Station, KNMI, Farmington, NM

KNMI

The proposed site is contained entirely inside the service contour of second-adjacent Station KNMI, Channel 205, Class C2, 6.2 kW, Farmington, NM. As shown by the map on **page #2** of this waiver request, the level of the second -adjacent station KNMI arriving protected F(50,50) signal at the proposed transmitter site is 105-dBu. Using the Undesired-to-Desired method for calculating proposed interference (the basis of the FCC current contour overlap regulations and an acceptable method for the purposes of determining lack of interference for an FM Translator), the proposed interfering contour with respect to KNMI is 145-dBu (free-space contour method employed). This means that the 145-dBu interfering signal would extend 2 meters from the center of radiation, which already exists at 22 meters AGL. Since no population inhabits this interference area, Calvary Chapel of Twin Falls, Inc. respectfully requests a waiver of the FM translator contour overlap regulations with respect to second -adjacent channel station KNMI.

The Commission's implementation of the Revised FM Engineering Rules, released in a *Report and Order* November 1, 2000 found in the "1998 Biennial Regulatory Review" in MM Docket 98-93, have been applied.