

EXHIBIT 7  
(Page 1 of 1)

NONIONIZING RADIATION COMPLIANCE

Christian Faith Broadcast, Inc.  
Ashland, OH

The proposed W33BW facilities will fully comply with the current FCC Standard with regard to human exposure to nonionizing radiation. The proposed antenna will be a Jampro JA/LS-BC-12, twelve bay directional antenna which will be mounted at the 148.4 meter level on a proposed new tower that will stand 152.4 meters above ground level. The proposed facilities will operate with a maximum peak visual effective radiated power of 30.0 kilowatts and a maximum aural effective radiated power of 3.0 kilowatts. Equation (2), found on Page 30 of Supplement A to FCC OET Bulletin No. 65, details the calculation technique for determining the power density levels at the base of a TV broadcast tower. Assuming 100% downward radiation for the proposed W33BW facilities, this equation predicts that the maximum power density generated by the proposed W33BW facilities at two meters above ground level will be  $23.9 \mu\text{W}/\text{cm}^2$ . Since the permitted power density for uncontrolled exposure on Channel 33 is  $389.3 \mu\text{W}/\text{cm}^2$ , this constitutes 6.1% of the permitted level. Thus, the implementation of the proposed W33BW facilities will not subject members of the general public to power density levels that are in excess of the permitted level for uncontrolled exposure.

W33BW will also take appropriate steps to insure that workers that must climb this tower will not be exposed to power density levels that are in excess of the permitted level for controlled exposure. These steps will include the cessation of operation or a reduction in power, as appropriate, when work is necessary in areas on this tower where the power density levels will be in excess of the permitted level for controlled exposure.