

## **Exhibit 35**

### **No Significant Impact On the Environment Statement**

**The proposed WMYT facility will not have any significant impact on the environment based on an independent review of the Environmental Assessments filed by the owner of the tower support structure with the FCC Tower Registration Section, FileNumber A0780284, Report No. CWS-12-82, Issued September 5, 2012. TowerRegistration Number 1285012.**

### **Compliance with Occupational/Controlled and Population/Uncontrolled RF Exposure Limits**

**The proposed facility will be located on a support tower that will be providing antenna support for three other F.M. broadcasting antennas. In calculating the Maximum Exposure Limits (MPE), all proposed stations total ERP and antenna height was considered. The following is a list of the proposed facilities along with the antenna center of radiation above ground level (C/R-AGL) and the Effective Radiated Power (ERP):**

<b>WMYT – FM</b>	<b>100m</b>	<b>1.8 Kw ERP</b>
<b>WBNE – FM</b>	<b>149m</b>	<b>22.1 Kw ERP</b>
<b>WWQQ – FM</b>	<b>163m</b>	<b>18.0 Kw ERP</b>
<b>WKXB – FM</b>	<b>176m</b>	<b>28.0 Kw ERP</b>

**In our calculation all four stations are proposing the use of circular polarized antennas. The ERP for all stations were summed and the result was doubled to produce the “total” ERP for the site at 139.8 Kw. The C/R-AGL of the group was assumed to be the proposed, double element antenna for WMYT – FM located at 100 meters above ground level.**

**Consulting the FCC OET-65 appendix A, Table 6 – general population/uncontrolled exposure limits, the 150.0 Kw ERP and a two element antenna was used which showed a worse case of 124.2 meters and a best case of 59.6 meters below the antenna. In addition a calculation using the above parameters was performed using the FCC’s RF Exposure Model Calculator and found that a Max Power Density of 69.843 microwatts/cm squared at 66 meters from the base of the tower and 2 meters above ground level was predicted. This is well below the MPE of 200 microwatts/cm squared for general population/uncontrolled exposure limits. To additionally protect the public, a 65’ by 70’ chain length fence, 6’ tall with three strands of “razor wire” will be constructed around the tower to secure unauthorized access to any possible over limit exposure area.**

**Consulting the FCC OET-65 appendix A, Table 5 – occupational/controlled exposure limits, the 150 Kw ERP and a two element antenna was used which showed a worse case of 56.7 meters and a best case of 27.6 meters below the antenna. The MPE of 1000 microwatts/cm squared for occupational/controlled exposure will be maintained when service personnel are within the normal “over exposure area” on the tower by a collective reduction of power from each of the four**

**stations located on the tower or a “cease of operation” if safe levels can not be met with continued operation of transmitting equipment.**

**It is believed that protection of the general public and service personnel has been proven by calculations performed, FCC chart consultation and preventative efforts taken by the applicant. For these reasons the applicant certifies compliance with the maximum permissible radio frequency electromagnetic exposure limits for controlled and uncontrolled environments.**