

Light Of Life Ministries, Inc.

REFERENCE
43 45 28.0 N.
70 19 16.0 W.

CH# 263D - 100.5 MHz, Pwr= 0.01 kw, HAAT= 144.7 M, COR= 193 M
Average Protected F(50-50)= 6.97 km
Omni-directional

DISPLAY DATES
DATA 05-21-10
SEARCH 07-03-10

CH CITY	CALL	TYPE ANT STATE	AZI <--	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*OUT* (Overlap in km)
260B Auburn	WTHT	LIC _CN ME	5.3 185.3	21.7 BLH19980825KD	43 57 07.0 70 17 46.0	28.500 196	5.9 288	65.1 Nassau Broadcasting Iii, L	-43.8*<
265B1 South Portland	WYNZ	LIC ZCX ME	178.1 358.1	7.5 BLH20090916AAQ	43 41 26.0 70 19 05.0	25.000 93	2.9 126	33.2 Saga Communications Of New	-26.1*<
262B Portsmouth	WHEB	LIC _CN NH	204.9 24.6	86.3 BLH19910307KE	43 03 11.0 70 46 04.0	50.000 140	76.5 151	63.6 Capstar Tx Llc	8.3
264C3 Mexico	WTBM	LIC NCX ME	344.9 164.7	94.9 BLH20020611AAK	44 34 56.0 70 37 59.0	0.850 388	53.9 729	36.1 Mountain Valley Broadcasti	51.6

Terrain database is FCC NGDC 30 Sec , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
In & Out distances between contours are shown at closest points. Reference zone = 1, Co to 3rd adjacent.
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
Incoming contour overlap is ignored.
"*"affixed to 'IN' or 'OUT' values = site inside protected contour.