

***Directional Antenna System
for
KCMY, Gardnerville-Minden, Nevada***

December 7, 2005

Electronics Research Inc. is providing a custom fabricated antenna system that is specially designed to meet the FCC requirements and the general needs of radio station KCMY.

The antenna is the ERI model LP-2E-DA-HW configuration. The circular polarized system consists of two half-wavelength spaced bays using one driven circular polarized radiating element per bay and two horizontal parasitic elements per bay. The antenna was mounted on the North 310 degrees East tower leg with bracketry to provide an antenna orientation of North 280 degrees East. The antenna was tested on a 42" face tower, which is the structure the station plans to use to support the array. All tests were performed on a frequency of 99.1 megahertz, which is the center of the FM broadcast channel assigned to KCMY.

Pattern measurements were made on a sixty-acre antenna pattern range that is owned and operated by Electronics Research, Inc. The tests were performed under the direction of Thomas B. Silliman, president of Electronics Research, Inc. Mr. Silliman has the Bachelor of Electrical Engineering and the Master of Electrical Engineering degrees from Cornell University and is a registered professional engineer in the states of Indiana, Maryland and Minnesota.

Directional Antenna System For KCMY, Gardnerville-Minden, Nevada

(Continued)

DESCRIPTION OF THE TEST PROCEDURE


The test antenna consisted of a full-scale model of the complete circular polarized system with the associated horizontal parasitic elements. The elements and brackets that were used in this test are electrically equivalent to those that will be supplied with the antenna. A section of 1 5/8 inch o.d. rigid coaxial line was used to feed the test antenna, and a section of 1 5/8 inch o.d. rigid outer conductor only was attached above the test antenna. The lines were properly grounded during all tests.

The power distribution and phase relationship to the antenna elements was adjusted in order to achieve the directional radiation patterns for both horizontal and vertical polarization components.

The proof-of-performance was accomplished using a 42" face tower with identical dimension and configuration including all braces, ladders, conduits, coaxial lines and other appurtenances that are included in the actual aperture at which the antenna will be installed. The structure was erected vertically on a turntable mounted on a non-metallic building with the antenna centered vertically on the structure, making the center of radiation of the test approximately 30 feet above ground. The turntable is equipped with a motor drive and a North Atlantic Model 8500 angle position indicator. The resolution of this angle position indicator is one-hundredth of a degree.

The antenna under test was operated in the transmitting mode and fed from a HP8657D signal generator calibrated 1-05. The frequency of the signal source was set at 99.1 MHz and was constantly monitored by an Anritsu Model ML521B measuring receiver calibrated 6-05.

A broadband horizontal and vertical dipole system, located approximately 628 feet from the test antenna, was used to receive the emitted test signals. The dipole system was mounted at the same height above terrain as the center of the antenna under test. The signals received by the dipole system were fed to the test building by way of two buried Heliax cables to an Anritsu Model ML521B measuring receiver.



Directional Antenna System
For
KCMY, Gardnerville-Minden, Nevada

(Continued)

This data was interfaced to a Hewlett-Packard Laser Jet 4P printer by means of a Pentium computer system. Relative field strength was plotted as a function of azimuth.

The measurements were performed by rotating the test antenna in a counter-clockwise direction and plotting the received signal on polar coordinated graph paper in a clockwise direction. Both horizontal and vertical components were recorded separately.

CONCLUSIONS

The circular polarized system consists of two half-wavelength spaced bays using one driven circular polarized radiating element per bay and two horizontal parasitic elements per bay. The power distribution and phase relationship will be fixed when antenna is manufactured. Proper maintenance of the elements should be all that is required to maintain the pattern in adjustment.

The LP-2E-DA-HW array is to be mounted on the North 310 degrees East tower leg of the 42" face tower at a bearing of North 280 degrees East. Blue prints provided with the antenna will show the proper antenna orientation alignment. The antenna alignment procedure should be directed by a licensed surveyor as prescribed by the FCC.

Figure #1 represents the maximum value of either the horizontal or vertical component at any azimuth. The measured horizontal plane relative field pattern, for both the horizontal and vertical polarization components, is shown on Figure #2 attached. The actual measured pattern does not exceed the authorized FCC composite pattern at any azimuth. A calculated vertical plane relative field pattern is shown on Figure #3 attached. The power in the maximum will reach .41 kilowatts (-3.872 dBk).

The RMS of the vertically polarized horizontal plane component does not exceed the RMS of the horizontally polarized horizontal plane component.

The composite horizontal and vertical maximum relative field pattern obtained from the measured data as shown on Figure #1 has an RMS that is greater than 85% of the filed composite pattern.

The clear vertical length of the structure required to support the antenna is 20 feet if the antenna is to be top mounted.

Directional Antenna System
For
KCMY, Gardnerville-Minden, Nevada

(Continued)

The directional antenna should not be mounted on the top of an antenna tower that includes a top-mounted platform larger than the cross-sectional area of the tower in the horizontal plane. No obstructions other than those that are specified by the blue prints supplied with the antenna are to be mounted within 75 ft. horizontally of the system. The vertical distance to the nearest obstruction should be a minimum of 10 ft. from the directional antenna. Metallic guy wires should be a minimum distance of forty feet horizontally from the antenna.

ELECTRONICS RESEARCH, INC.


A handwritten signature in cursive script, appearing to read "Tom Schoof".

ERI[®] Horizontal Plane Relative Field Pattern

Electronics Research, Inc. 7777 Gardner Rd. Chandler, In 47610 Phone (812) 925-6000 Fax (812) 925-4030 <http://www.eriinc.com/>

FIGURE NO: 1
STATION: KCMY
LOCATION: GARDNERVILLE, NV
ANTENNA: LP-2E-DA-HW
STRUCTURE: 42" FACE TOWER

DATE: 12/6/05
FREQUENCY: 99.1 MHz
ORIENTATION: 280° TRUE
MOUNTING: STANDARD
BAYS TESTED: TWO



FCC COMPOSITE
RMS: 0.979
MAXIMUM: 1.000 @ 0° TRUE
MINIMUM: 0.790 @ 70° TRUE

Measured Composite:
RMS: 0.833
Maximum: 1.000 @ 189° True
Minimum: 0.337 @ 114° True

COMMENTS: COMPOSITE PATTERN: THIS PATTERN SHOWS THE MAXIMUM OF EITHER THE H OR V AZIMUTH VALUES. THIS PATTERN IS GREATER THAN 85% OF THE FCC FILED COMPOSITE PATTERN BMPH-20050215ABQ

ERI® *Horizontal Plane Relative Field List*

Electronics Research, Inc. 7777 Gardner Rd. Chandler, In 47610 Phone (812) 925-6000 Fax (812) 925-4030 <http://www.eriinc.com/>

Station: KCMY
Location: Gardnerville, NV
Frequency: 99.1 MHz

Antenna: LP-2E-DA-HW
Orientation: 280° True
Tower: 42" face tower

Figure: 1
Date: 12/6/05
Reference: kcmym1m.fig

Angle	Envelope			Polarization	Angle	Envelope			Polarization
	Field	kW	dBk			Field	kW	dBk	
0°	0.983	0.40	-4.02	Vertical	180°	0.965	0.38	-4.18	Horizontal
5°	0.977	0.39	-4.08	Vertical	185°	0.993	0.40	-3.93	Horizontal
10°	0.963	0.38	-4.20	Vertical	190°	1.000	0.41	-3.87	Horizontal
15°	0.941	0.36	-4.40	Vertical	195°	0.987	0.40	-3.98	Horizontal
20°	0.912	0.34	-4.67	Vertical	200°	0.964	0.38	-4.19	Vertical
25°	0.880	0.32	-4.98	Horizontal	205°	0.982	0.40	-4.03	Vertical
30°	0.873	0.31	-5.05	Horizontal	210°	0.994	0.41	-3.92	Vertical
35°	0.867	0.31	-5.11	Horizontal	215°	1.000	0.41	-3.87	Vertical
40°	0.862	0.30	-5.17	Horizontal	220°	0.999	0.41	-3.88	Vertical
45°	0.851	0.30	-5.27	Horizontal	225°	0.995	0.41	-3.92	Vertical
50°	0.829	0.28	-5.51	Horizontal	230°	0.988	0.40	-3.97	Vertical
55°	0.786	0.25	-5.96	Horizontal	235°	0.979	0.39	-4.06	Vertical
60°	0.738	0.22	-6.51	Horizontal	240°	0.967	0.38	-4.17	Vertical
65°	0.691	0.20	-7.08	Horizontal	245°	0.967	0.38	-4.17	Horizontal
70°	0.636	0.17	-7.80	Horizontal	250°	0.974	0.39	-4.10	Horizontal
75°	0.577	0.14	-8.65	Horizontal	255°	0.970	0.39	-4.14	Horizontal
80°	0.516	0.11	-9.61	Horizontal	260°	0.958	0.38	-4.24	Horizontal
85°	0.461	0.09	-10.59	Horizontal	265°	0.940	0.36	-4.41	Horizontal
90°	0.417	0.07	-11.47	Horizontal	270°	0.914	0.34	-4.65	Horizontal
95°	0.383	0.06	-12.22	Horizontal	275°	0.897	0.33	-4.82	Vertical
100°	0.358	0.05	-12.79	Horizontal	280°	0.898	0.33	-4.81	Vertical
105°	0.345	0.05	-13.12	Horizontal	285°	0.901	0.33	-4.78	Vertical
110°	0.339	0.05	-13.27	Horizontal	290°	0.907	0.34	-4.72	Vertical
115°	0.337	0.05	-13.32	Horizontal	295°	0.915	0.34	-4.65	Vertical
120°	0.340	0.05	-13.23	Horizontal	300°	0.924	0.35	-4.55	Vertical
125°	0.349	0.05	-13.02	Horizontal	305°	0.933	0.36	-4.48	Vertical
130°	0.364	0.05	-12.65	Horizontal	310°	0.939	0.36	-4.42	Vertical
135°	0.389	0.06	-12.07	Horizontal	315°	0.943	0.36	-4.39	Vertical
140°	0.420	0.07	-11.41	Horizontal	320°	0.944	0.37	-4.37	Vertical
145°	0.454	0.08	-10.73	Horizontal	325°	0.953	0.37	-4.29	Vertical
150°	0.513	0.11	-9.67	Horizontal	330°	0.961	0.38	-4.22	Vertical
155°	0.592	0.14	-8.43	Horizontal	335°	0.968	0.38	-4.15	Vertical
160°	0.678	0.19	-7.24	Horizontal	340°	0.974	0.39	-4.11	Vertical
165°	0.766	0.24	-6.18	Horizontal	345°	0.978	0.39	-4.07	Vertical
170°	0.848	0.29	-5.31	Horizontal	350°	0.981	0.39	-4.04	Vertical
175°	0.916	0.34	-4.63	Horizontal	355°	0.983	0.40	-4.03	Vertical

Polarization:
Maximum Field:
Minimum Field:
RMS:
Maximum ERP:
Maximum Power Gain:

Envelope
1.000 @ 189° True
0.337 @ 114° True
0.833
0.410 kW
1.082 (0.341 dB)


Total Input Power: 0.379 kW

ERI® *Horizontal Plane Relative Field Pattern*

Electronics Research, Inc. 7777 Gardner Rd. Chandler, In 47610 Phone (812) 925-6000 Fax (812) 925-4030 <http://www.eriinc.com/>

FIGURE NO: 2
STATION: KCMY
LOCATION: GARDNERVILLE, NV
ANTENNA: LP-2E-DA-HW
STRUCTURE: 42" FACE TOWER

DATE: 12/6/05
FREQUENCY: 99.1 MHz
ORIENTATION: 280° TRUE
MOUNTING: STANDARD
BAYS TESTED: TWO



VERTICAL

RMS: 0.780
MAXIMUM: 1.000 @ 216° TRUE
MINIMUM: 0.216 @ 93° TRUE

Horizontal

RMS: 0.791
Maximum: 1.000 @ 189° True
Minimum: 0.337 @ 114° True

COMMENTS: MEASURED PATTERNS OF THE HORIZONTAL AND VERTICAL COMPONENTS.

ERI[®] *Horizontal Plane Relative Field List*

Electronics Research, Inc. 7777 Gardner Rd. Chandler, In 47610 Phone (812) 925-6000 Fax (812) 925-4030 <http://www.eriinc.com/>

Station: KCMY
Location: Gardnerville, NV
Frequency: 99.1 MHz

Antenna: LP-2E-DA-HW
Orientation: 280° True
Tower: 42" face tower

Figure: 2
Date: 12/6/05
Reference: kcmym1m.fig

Angle	Horizontal			Vertical			Angle	Horizontal			Vertical		
	Field	kW	dBk	Field	kW	dBk		Field	kW	dBk	Field	kW	dBk
0°	0.949	0.37	-4.33	0.983	0.40	-4.02	180°	0.965	0.38	-4.18	0.823	0.28	-5.57
5°	0.933	0.36	-4.47	0.977	0.39	-4.08	185°	0.993	0.40	-3.93	0.868	0.31	-5.10
10°	0.915	0.34	-4.64	0.963	0.38	-4.20	190°	1.000	0.41	-3.87	0.906	0.34	-4.72
15°	0.899	0.33	-4.80	0.941	0.36	-4.40	195°	0.987	0.40	-3.98	0.938	0.36	-4.42
20°	0.888	0.32	-4.90	0.912	0.34	-4.67	200°	0.960	0.38	-4.22	0.964	0.38	-4.19
25°	0.880	0.32	-4.98	0.875	0.31	-5.03	205°	0.924	0.35	-4.56	0.982	0.40	-4.03
30°	0.873	0.31	-5.05	0.831	0.28	-5.48	210°	0.891	0.33	-4.88	0.994	0.41	-3.92
35°	0.867	0.31	-5.11	0.779	0.25	-6.04	215°	0.868	0.31	-5.11	1.000	0.41	-3.87
40°	0.862	0.30	-5.17	0.719	0.21	-6.74	220°	0.859	0.30	-5.19	0.999	0.41	-3.88
45°	0.851	0.30	-5.27	0.659	0.18	-7.50	225°	0.866	0.31	-5.12	0.995	0.41	-3.92
50°	0.829	0.28	-5.51	0.593	0.14	-8.41	230°	0.885	0.32	-4.93	0.988	0.40	-3.97
55°	0.786	0.25	-5.96	0.526	0.11	-9.46	235°	0.917	0.34	-4.63	0.979	0.39	-4.06
60°	0.738	0.22	-6.51	0.458	0.09	-10.65	240°	0.948	0.37	-4.34	0.967	0.38	-4.17
65°	0.691	0.20	-7.08	0.394	0.06	-11.95	245°	0.967	0.38	-4.17	0.952	0.37	-4.30
70°	0.636	0.17	-7.80	0.337	0.05	-13.33	250°	0.974	0.39	-4.10	0.936	0.36	-4.45
75°	0.577	0.14	-8.65	0.289	0.03	-14.65	255°	0.970	0.39	-4.14	0.923	0.35	-4.57
80°	0.516	0.11	-9.61	0.253	0.03	-15.81	260°	0.958	0.38	-4.24	0.912	0.34	-4.67
85°	0.461	0.09	-10.59	0.229	0.02	-16.67	265°	0.940	0.36	-4.41	0.904	0.34	-4.75
90°	0.417	0.07	-11.47	0.218	0.02	-17.11	270°	0.914	0.34	-4.65	0.899	0.33	-4.79
95°	0.383	0.06	-12.22	0.217	0.02	-17.16	275°	0.882	0.32	-4.97	0.897	0.33	-4.82
100°	0.358	0.05	-12.79	0.221	0.02	-17.00	280°	0.844	0.29	-5.34	0.898	0.33	-4.81
105°	0.345	0.05	-13.12	0.226	0.02	-16.79	285°	0.813	0.27	-5.67	0.901	0.33	-4.78
110°	0.339	0.05	-13.27	0.232	0.02	-16.56	290°	0.789	0.26	-5.93	0.907	0.34	-4.72
115°	0.337	0.05	-13.32	0.237	0.02	-16.36	295°	0.772	0.24	-6.12	0.915	0.34	-4.65
120°	0.340	0.05	-13.23	0.243	0.02	-16.15	300°	0.762	0.24	-6.23	0.924	0.35	-4.55
125°	0.349	0.05	-13.02	0.251	0.03	-15.89	305°	0.759	0.24	-6.26	0.933	0.36	-4.48
130°	0.364	0.05	-12.65	0.257	0.03	-15.66	310°	0.764	0.24	-6.21	0.939	0.36	-4.42
135°	0.389	0.06	-12.07	0.275	0.03	-15.08	315°	0.774	0.25	-6.09	0.943	0.36	-4.39
140°	0.420	0.07	-11.41	0.304	0.04	-14.21	320°	0.791	0.26	-5.91	0.944	0.37	-4.37
145°	0.454	0.08	-10.73	0.344	0.05	-13.13	325°	0.813	0.27	-5.67	0.953	0.37	-4.29
150°	0.513	0.11	-9.67	0.396	0.06	-11.93	330°	0.841	0.29	-5.38	0.961	0.38	-4.22
155°	0.592	0.14	-8.43	0.458	0.09	-10.66	335°	0.873	0.31	-5.05	0.968	0.38	-4.15
160°	0.678	0.19	-7.24	0.531	0.12	-9.36	340°	0.900	0.33	-4.79	0.974	0.39	-4.11
165°	0.766	0.24	-6.18	0.616	0.16	-8.08	345°	0.921	0.35	-4.59	0.978	0.39	-4.07
170°	0.848	0.29	-5.31	0.704	0.20	-6.92	350°	0.936	0.36	-4.45	0.981	0.39	-4.04
175°	0.916	0.34	-4.63	0.771	0.24	-6.14	355°	0.945	0.37	-4.36	0.983	0.40	-4.03

Polarization:	Horizontal	Vertical
Maximum Field:	1.000 @ 189° True	1.000 @ 216° True
Minimum Field:	0.337 @ 114° True	0.216 @ 93° True
RMS:	0.791	0.780
Maximum ERP:	0.410 kW	0.410 kW
Maximum Power Gain:	1.082 (0.341 dB)	1.082 (0.341 dB)

Total Input Power: 0.379 kW




Vertical Plane Relative Field Pattern

KCMY, Gardnerville, NV, 99.1 MHz

Figure#: 3

Date: 12/6/05

A 2 level, .5 wave-length spaced LP-2E-DA-HW directional antenna
with 0° beam tilt, 0% null fill and a H/V maximum power ratio of 1.000



Vertical Polarization Gain:

Maximum: 1.082 (0.341 dB)

Horizontal Plane: 1.082 (0.341 dB)

Horizontal Polarization Gain:

Maximum: 1.082 (0.341 dB)

Horizontal Plane: 1.082 (0.341 dB)

Directional Antenna System for KCMY, Gardnerville-Minden, Nevada

(Continued)

ANTENNA SPECIFICATIONS

Antenna Type: LP-2E-DA-HW
Frequency: 99.1 MHz
Number of Bays: Two

MECHANICAL SPECIFICATIONS

Mounting: Standard
System length: 13 ft 5 in
Aperture length required: 24 ft 11 in
Orientation: 280° true
Input flange to the antenna 1 5/8 inch female

ELECTRICAL SPECIFICATIONS (For directional use)

Maximum horizontal ERP: 0.41 kW (-3.872 dBk)
Horizontal maximum power gain: 1.082 (0.341 dB)
Maximum vertical ERP: 0.41 kW (-3.872 dBk)
Vertical maximum power gain: 1.082 (0.341 dB)
Total input power: 0.379 kW (-4.211 dBk)

