

EXHIBIT #22

R.F. EMISSION COMPLIANCE STATEMENT

Minnesota Public Radio

Minor Amendment to Pending Application

BMPED-20071016AHI

Ely, MN

May 2008

CH 207C3

19 kW H & V

The proposed six-bay, circularly polarized antenna will be energized such that it produces 19 kW effective radiated power from a center of radiation of 90 meters above ground. Using the formulas expressed in the OET Bulletin, No. 65, August 1997, "Evaluating Compliance with F.C.C. Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", published by the Federal Communication Commission's Office of Science and Engineering, and then by applying a combination of the element and array pattern as defined in E.P.A. study PB85-245868 ("**Engineering Assessment of the Potential Impact of the Federal Radiation Protection Guidance on the AM, FM and TV Broadcast Services**") the predicted level of RF non-ionization emissions at a position of 2 meters above ground (head-height) at the base of the tower for the proposed 6-bay Shively 6813 (Type #6) antenna is 0.8197 microwatts per square centimeter, which is 0.082 percent of the maximum for a controlled area and 0.41 percent of maximum for an uncontrolled area.

Since the predicted level of emissions is less than 1% of maximum, no further calculations were deemed necessary.

The applicant will protect workers on the tower by either reducing ERP or terminating transmission.

Consequently, it appears that the proposed FM station will be in full compliance with the Commission's human exposure to radiofrequency electromagnetic field rules and regulations.