

EXHIBIT 15-G-2 Tabulation of Distance to WAMM Daytime Allocation Contour

WAMM 1230 kHz Lic ND1U BL831123AF 01-Jan-2007
 VA WOODSTOCK 1.000 kW 1 Tower 0 Augmentations
 N. Lat: 38 51 11 W. Lon: 78 31 30 0 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.
 All distances are in kilometers (US metric curves)
 All radiations are in mV/m at one kilometer

Bearing	Radiation	Distance to Contour 5.000
-----	-----	-----
0.0	280.8	9.84
5.0	280.8	9.84
10.0	280.8	9.84
15.0	280.8	9.84
20.0	280.8	9.84
25.0	280.8	9.84
30.0	280.8	9.84
35.0	280.8	9.84
40.0	280.8	9.84
45.0	280.8	9.84
50.0	280.8	9.84
55.0	280.8	9.84
60.0	280.8	9.84
65.0	280.8	9.84
70.0	280.8	9.84
75.0	280.8	9.84
80.0	280.8	9.84
85.0	280.8	9.84
90.0	280.8	9.84
95.0	280.8	9.84
100.0	280.8	9.84
105.0	280.8	9.84
110.0	280.8	9.84
115.0	280.8	9.84
120.0	280.8	9.84
125.0	280.8	9.84
130.0	280.8	9.84
135.0	280.8	9.84
140.0	280.8	9.84
145.0	280.8	9.84
150.0	280.8	9.84
155.0	280.8	9.84
160.0	280.8	9.84
165.0	280.8	9.84
170.0	280.8	9.84
175.0	280.8	9.84

EXHIBIT 15-G-2 (cont.)
 Tabulation of Distance to WAMM Daytime Allocation Contour

WAMM	1230 kHz	Lic	ND1U	BL831123AF	01-Jan-2007
VA	WOODSTOCK		1.000 kW	1 Tower	0 Augmentations
N. Lat:	38 51 11	W. Lon:	78 31 30		0 Measured Cond

Bearing	Radiation	Distance to Contour 5.000
-----	-----	-----
180.0	280.8	9.84
185.0	280.8	9.84
190.0	280.8	9.84
195.0	280.8	9.84
200.0	280.8	9.84
205.0	280.8	9.84
210.0	280.8	9.84
215.0	280.8	9.84
220.0	280.8	9.84
225.0	280.8	9.84
230.0	280.8	9.84
235.0	280.8	9.84
240.0	280.8	9.84
245.0	280.8	9.84
250.0	280.8	9.84
255.0	280.8	9.84
260.0	280.8	9.84
265.0	280.8	9.84
270.0	280.8	9.84
275.0	280.8	9.84
280.0	280.8	9.84
285.0	280.8	9.84
290.0	280.8	9.84
295.0	280.8	9.84
300.0	280.8	9.84
305.0	280.8	9.84
310.0	280.8	9.84
315.0	280.8	9.84
320.0	280.8	9.84
325.0	280.8	9.84
330.0	280.8	9.84
335.0	280.8	9.84
340.0	280.8	9.84
345.0	280.8	9.84
350.0	280.8	9.84
355.0	280.8	9.84