

Exhibit RFR-1
KBEH1-DT Los Angeles, CA Channel 24
Prepared by WES Broadcast Consultants, INC.

GUIDELINES FOR HUMAN EXPOSURE TO RADIOFREQUENCY RADIATION
EVALUATION OF COMPLIANCE WITH FCC-SPECIFIED GUIDELINES FOR
EXPOSURE TO RADIOFREQUENCY RADIATION FROM A SINGLE
UHF TV BROADCAST STATION

CHANNEL 24	530-536 Mhz		
VISUAL CARRIER 531.25 Mhz	VISUAL ERP	1.0 KW	
AURAL CARRIER 535.75 Mhz	AURAL ERP	0.0 KW	

MAXIMUM POWER DENSITY AT CHANNEL 24	1.771 mW/CM2
ANTENNA COR AGL	61.0M 200.1 FT
POWER DENSITY AT 200 FT FROM COR (WORST CASE)	0.004 mW/cm2
POWER DENSITY AT 200 FT FROM COR (.1 REL FIELD)	0.000 mW/cm2

MINIMUM REQUIRED DISTANCE (WORST CASE)	2.7 M	9.0 FT
MINIMUM REQUIRED DISTANCE (.1 REL FIELD)	0.3 M	0.9 FT

CLEAR BY (COR-MAH) (WORST CASE)	58.2 M	191.1 FT
CLEAR BY (COR-MAH) (.1 REL FIELD)	60.7 M	199.2 FT

FOR MULTIPLE SOURCES: SUM PERCENTAGES OF ANSI STANDARDS
SUMATION NOT TO EXCEED 100 %

PERCENT OF ANSI STANDARD AT GROUND LEVEL (WORST CASE)	0.2 %
PERCENT OF ANSI STANDARD AT GROUND LEVEL (0.1 REL FIELD)	0.0 %

THE TOWER IS CLEARLY MARKED WITH A CLEARLY VISIBLE RADIATION HAZARD
PLACARD.

IN THE EVENT THAT MAINTENANCE IS TO BE PERFORMED PERSONNEL ARE TRAINED
TO LOWER POWER OR SHUT OFF TRANSMITTER.