

Sterling CO K201IP											
Calvary Chapel Of Twin Falls, Inc.											
REFERENCE	CH#	201D	-	88.1	MHZ,	Pwr= 0.075 kw,	HAAT= 110.5 M,	COR= 1416 M	DISPLAY DATES		
40 31 57.0 N.									DATA 08-06-18		
103 07 22.0 W.									SEARCH 08-13-18		
Average Protected F(50-50)= 10.09 km											
Omni-directional											
CH	CALL	TYPE	ANT	AZI	DIST	LAT	PWR(kw)	INT(km)	PRO(km)	*IN*	*OUT*
CITY		STATE		<--	FILE #	LNG	HAAT(M)	COR(M)	LICENSEE	(Overlap	in km)
201D	K201IP	CP	_C_	0.0	0.00	40 31 57.0	0.092		---Reference---		
Sterling		CO		0.0	BPFT20180702ABD	103 07 22.0		1394	Calvary Chapel Of Twin Fal		
201D	K201IP	LIC	_V_	85.8	6.35	40 32 12.0	0.075		---Reference---		
Sterling		CO		265.8	BLFT20121105AKX	103 02 52.0	120	1446	Calvary Chapel Of Twin Fal		
202D	K202EK	LIC	_C_	148.8	50.58	40 08 35.0	0.113	15.0	10.7	29.1	31.5
Yuma		CO		329.0	BLFT20130603BED	102 48 51.0	117	1398	Community Radio For Northe		

Terrain database is USGS 03 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
In & Out distances between contours are shown at closest points. Reference zone= West Zone, Co to 3rd adjacent.
All separation margins (if shown) include rounding.
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
"*"affixed to 'IN' or 'OUT' values = site inside restricted contour.