

**Exhibit 42-E1 - K29KP-D Table of Technical Parameters**

BNPDTL-20100713APN	<b>Approved CP</b>	<b>Proposed CP</b>	<b>Proposed STA</b>
<b>Site</b>			
Latitude, North, NAD 27	33° 09' 38.50"	33° 09' 38.50"	33° 09' 38.50"
Longitude, West, NAD 27	111° 48' 4.10 "	111° 48' 4.10 "	111° 48' 4.10 "
FAA Study Number	N/A	N/A	N/A
Antenna Site Registration Number	N/A	N/A	N/A
<b>Emission Characteristics</b>			
Channel	29 Digital	29 Digital	29 Digital
Frequency	560 - 566 MHz	560 - 566 MHz	560 - 566 MHz
Emission Characteristics	Stringent	Stringent	Stringent
<b>Elevations</b>			
Elevation of Site Above Mean Sea Level (AMSL)	375 m	375 m	375 m
Overall Height of Structure Above Ground (AGL)	61 m	36.6 m	36.6 m
Overall Height of Structure Above Mean Sea Level	436 m	411.6 m	411.6 m
Average Terrain	406.9 m	406.9 m	406.9 m
Antenna Center of Radiation Above Ground	54.9 m	33.1 m	33.1 m
Antenna Center of Radiation Above Average Terrain	23.0 m	1.2 m	1.2 m
Antennna Center of Radiation Above Mean Sea Level	429.9 m	408.1 m	408.1 m
<b>RF Transmission</b>			
Maximum Effective Radiated Power	15 kW	15 kW	2.7 kW
Antenna Gain	11.6 dBd	12.9 dBd	12.9 dBd
Transmission Line Loss	2.0 dB	1.5 dB	1.5 dB
Transmitter Power Output	650 W	1087 W	196 W
Antenna Make and Model	Scala 4DR-16S	Dielectric DLP-10B-29	Dielectric DLP-10B-29
Antenna Rotation	65°	(omni-directional)	(omni-directional)