



Exhibit 30
73.215 Clearance To WPAT
WEHM - 141 M HAAT - 3.1 KW (DA)
Manorville, NY

Bromo Communications, Inc.
 Atlanta, Georgia
 January 2007

Bromo Communications, Inc.
01-13-2007 30 Sec. Terrain Data

WPAT-F BPH20021107AAD
Channel = 226B
Max ERP = 6 kW
RCAMSL = 429 M
N. Lat = 40 44 54
W. Lng = 73 59 10

WEHM
Channel = 225A
Max ERP = 3.1 kW
RCAMSL = 157 M
N. Lat = 405118
W. Lng = 724611

Protected
54 dBu

Interfering
48 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
065.0	006.0000	0425.6	066.4	291.2	000.6727	0136.5	045.4	46.1
066.0	006.0000	0425.5	066.4	290.2	000.6397	0136.4	044.5	46.3
067.0	006.0000	0425.3	066.4	289.1	000.6097	0136.3	043.7	46.4
068.0	006.0000	0425.1	066.4	287.9	000.5799	0136.3	042.9	46.5
069.0	006.0000	0424.8	066.4	286.6	000.5492	0136.1	042.2	46.6
070.0	006.0000	0424.2	066.3	285.3	000.5178	0135.8	041.6	46.6
071.0	006.0000	0423.5	066.3	283.9	000.4859	0135.7	041.0	46.5
072.0	006.0000	0422.7	066.2	282.5	000.4537	0135.7	040.4	46.5
073.0	006.0000	0421.9	066.2	281.0	000.4215	0135.8	039.9	46.4
074.0	006.0000	0421.0	066.1	279.5	000.3999	0136.3	039.5	46.4
075.0	006.0000	0420.2	066.1	277.9	000.3999	0136.3	039.1	46.6
076.0	006.0000	0419.6	066.0	276.3	000.3999	0136.3	038.7	46.8
077.0	006.0000	0419.1	066.0	274.7	000.3999	0136.2	038.3	46.9
078.0	006.0000	0418.7	066.0	273.0	000.3999	0135.5	038.1	47.0
079.0	006.0000	0418.6	066.0	271.3	000.3999	0134.1	037.8	47.1
080.0	006.0000	0418.6	066.0	269.6	000.3999	0133.3	037.6	47.1
081.0	006.0000	0418.5	066.0	267.8	000.3999	0131.8	037.4	47.1
082.0	006.0000	0418.2	066.0	266.0	000.3999	0132.8	037.4	47.2
083.0	006.0000	0418.2	066.0	264.3	000.3999	0134.4	037.3	47.3
084.0	006.0000	0418.5	066.0	262.5	000.3999	0133.9	037.3	47.3
085.0	006.0000	0418.8	066.0	260.7	000.3999	0134.0	037.4	47.3
086.0	006.0000	0418.9	066.0	259.0	000.3999	0134.6	037.5	47.2
087.0	006.0000	0418.6	066.0	257.2	000.3999	0135.0	037.7	47.2
088.0	006.0000	0418.2	066.0	255.5	000.3999	0135.3	037.9	47.1
089.0	006.0000	0417.9	065.9	253.8	000.3999	0136.3	038.2	47.0
090.0	006.0000	0417.5	065.9	252.2	000.3999	0138.1	038.6	46.9
091.0	006.0000	0417.2	065.9	250.6	000.3999	0139.1	039.0	46.8
092.0	006.0000	0416.8	065.9	249.1	000.4196	0141.0	039.5	46.9
093.0	006.0000	0416.4	065.8	247.6	000.4520	0141.7	040.0	47.0
094.0	006.0000	0415.6	065.8	246.1	000.4840	0142.7	040.5	47.1
095.0	006.0000	0414.9	065.7	244.8	000.5158	0143.1	041.1	47.2

73.215 Clearance to WPAT

At no point on the WPAT Protected 54 dBu contour does WEHM deliver more than 48 dBu Interfering.

Exhibit 30 (Continued)
WEHM – 141 M HAAT – 3.1 KW (DA)
Manorville, NY
January 2007

BROMO
COMMUNICATIONS
BROADCAST
TECHNICAL CONSULTANTS